



PE4124

High Linearity MOSFET Quad Mixer For GSM800 & Cellular BTS

Features

- Integrated, Single Ended RF & LO Interfaces
- High linearity: IIP3 >+30 dBm, 820 – 920 MHz (+17 dBm LO)
- Low conversion loss: 8 dB (+17 dBm LO)
- High Isolation: Typical LO-IF at 38 dB
Typical LO-RF at 38 dB
- Designed for Low-Side LO Injection


Product Description

The PE4124 is a high linearity, passive MOSFET Quad Mixer for GSM800 & Cellular Base Station Receivers and exhibits high dynamic range performance over an LO drive range of 14 dBm to 20 dBm. This mixer integrates passive matching networks to provide single ended interfaces for the RF and LO ports, eliminating the need for external RF baluns or matching networks. The PE4124 is optimized for frequency down conversion using low-side LO injection for GSM800 & Cellular Base Station applications.


The PE4124 is manufactured in Peregrine's patented Ultra Thin Silicon (UTSi) CMOS process, offering the performance of GaAs with the economy and integration of conventional CMOS.

Package Drawings

8 lead TSSOP



Functional Schematic Diagram



Electrical Specifications @ +25°C

Parameter	Minimum	Typical	Maximum	Units
Frequency Range:				
LO	750		850	MHz
RF	820		920	MHz
IF	50	70	90	MHz
Conversion Loss		8		dB
Isolation:				
LO-RF		38		dB
LO-IF		38		dB
RF-IF		-		dB
VSWR:				
LO		1.5:1	2:1	dB
RF		1.6:1	2:1	dB
IF		1.7:1	2:1	dB
Input IP3		30		dBm
Input 1 dB Compression		20		dBm


Test conditions unless otherwise noted: LO input drive = 17 dBm

Peregrine Semiconductor Corp.



6175 Nancy Ridge Drive, San Diego, CA 92121
Tel (858) 455-0660 Fax (858) 455-0770
<http://www.peregrine-semi.com>

Pin Configuration



Pin Descriptions

Pin #	Pin Name	Description
1	LO	LO input
2	GND	Ground connection for Mixer. Traces should be physically short and connect immediately to ground plane for best performance.
3	RF	RF Input
4	GND	Ground connection for Mixer. Traces should be physically short and connect immediately to ground plane for best performance.
5	GND	Ground connection for Mixer. Traces should be physically short and connect immediately to ground plane for best performance.
6	IF1	IF differential output
7	IF2	IF differential output
8	GND	Ground connection for Mixer. Traces should be physically short and connect immediately to ground plane for best performance.


Absolute Maximum Ratings

Symbol	Parameter/Conditions	Min	Max	Units
T_{ST}	Storage temperature range	-65	150	°C
T_{OP}	Operating temperature range	-40	85	°C
P_{LO}	LO input power		20	dBm
P_{RF}	RF input power		20	dBm
ESD	ESD Sensitive Device		100	V

When handling this UTSi device, observe the same precautions that you would use with other ESD-sensitive devices.



Typical Application Schematic




U4 M/A-Com E-Series RF 4:1 Transformer 2.0 – 1000 MHz ETK4-2T



Package Drawing

Symbol	8-pin Variation		
	MIN	NOM	MAX
<i>D</i>	2.9	3	3.1
<i>E1</i>	4.3	4.4	4.5
<i>E</i>	6.4 BSC		
<i>e</i>	0.65 BSC		
<i>N</i>	8		
<i>Note</i>	1.2		
<i>Issue</i>	A		



Ordering information

Order Code	Part Marking	Description	Package	Shipping Method
4124-21	4124	Screened to Commercial Flow	8 pin TSSOP	100pcs./Tube
4124-22	4124	Screened to Commercial Flow	8 pin TSSOP	2000pcs./T&R
4124-00	PE4124-EK		Evaluation Board	1/Box



Sales Offices

United States

Peregrine Semiconductor Corp.
6175 Nancy Ridge Drive
San Diego, CA 92121
Tel (619) 455-0660
Fax (619) 455-0770

Europe

Peregrine Semiconductor Europe
Aix-En-Provence office
Parc Club du Golf, bat 9
13856 Aix-En-Provence Cedex 3
France
Tel +33 (0)4 4239-3360
Fax +33 (0)4 4239 7227

For a list of representatives in your area,
please refer to our website at
www.peregrine-semi.com

Data Sheet Identification

Advance Information

The product is in a formative or design stage. The data sheet contains design target specifications for product development. Specifications and features may change in any manner without notice.

Preliminary Specification

The data sheet contains preliminary data. Additional data may be added at a later date. Peregrine reserves the right to change specifications at any time without notice in order to supply the best possible product.

Product Specification

The data sheet contains final data. In the event Peregrine decides to change the specifications, Peregrine will notify customers of the intended changes by issuing a PCN (Product Change Notice).

The information in this data sheet is believed to be reliable. However, Peregrine assumes no liability for the use of this information. Use shall be entirely at the user's own risk.

No patent rights or licenses to any circuits described in this data sheet are implied or granted to any third party.

Peregrine's products are not designed or intended for use in devices or systems intended for surgical implant, or in other applications intended to support or sustain life, or in any application in which the failure of the Peregrine product could create a situation in which personal injury or death might occur. Peregrine assumes no liability for damages, including consequential or incidental damages, arising out of the use of its products in such applications.

Peregrine products are protected under one or more of the following US patents: 5,416,043; 5,600,169; 5,572,040; 5,492,857; 5,663,570; 5,596,205; 5,610,790. Other patents may be pending or applied for.

