

$V_{DSM} = 5200 \text{ V}$
 $I_{TAVM} = 1975 \text{ A}$
 $I_{TRMS} = 3100 \text{ A}$
 $I_{TSM} = 29000 \text{ A}$
 $V_{T0} = 1.02 \text{ V}$
 $r_T = 0.320 \text{ m}\Omega$

Phase Control Thyristor

5STP 17H5200

Doc. No. 5SYA1049-02 Sep. 01

- Patented free-floating silicon technology
- Low on-state and switching losses
- Designed for traction, energy and industrial applications
- Optimum power handling capability
- Interdigitated amplifying gate

Blocking

Part Number	5STP 17H5200	5STP 17H5000	5STP 17H4600	Conditions
V_{DSM} V_{RSM}	5200 V	5000 V	4600 V	$f = 5 \text{ Hz}$, $t_p = 10 \text{ ms}$
V_{DRM} V_{RRM}	4400 V	4200 V	4000 V	$f = 50 \text{ Hz}$, $t_p = 10 \text{ ms}$
V_{RSM1}	5700 V	5500 V	5100 V	$t_p = 5 \text{ ms}$, single pulse
I_{DSM}	$\leq 400 \text{ mA}$			V_{DSM} $T_j = 125^\circ\text{C}$
I_{RSM}	$\leq 400 \text{ mA}$			V_{RSM}
dV/dt_{crit}	2000 V/ μs			Exp. to $0.67 \times V_{DRM}$, $T_j = 125^\circ\text{C}$

V_{DRM}/V_{RRM} are equal to V_{DSM}/V_{RSM} values up to $T_j = 110^\circ\text{C}$

Mechanical data

F_M	Mounting force	nom.	50 kN
		min.	45 kN
		max.	60 kN
a	Acceleration		
	Device unclamped		50 m/s ²
	Device clamped		100 m/s ²
m	Weight		0.9 kg
D_S	Surface creepage distance		36 mm
D_a	Air strike distance		15 mm




ABB Semiconductors AG reserves the right to change specifications without notice.

ABB

On-state

I _{TAVM}	Max. average on-state current	1975 A	Half sine wave, T _C = 70°C	
I _{TRMS}	Max. RMS on-state current	3100 A		
I _{TSM}	Max. peak non-repetitive	29000 A	tp = 10 ms	T _j = 125°C
	surge current	31000 A	tp = 8.3 ms	After surge:
I ² t	Limiting load integral	4205 kA ² s	tp = 10 ms	V _D = V _R = 0V
		3990 kA ² s	tp = 8.3 ms	
V _T	On-state voltage	1.68 V	I _T = 2000 A	T _j = 125°C
V _{T0}	Threshold voltage	1.02 V	I _T = 1000 - 3000 A	
r _T	Slope resistance	0.320 mΩ		
I _H	Holding current	30-80 mA	T _j = 25°C	
		15-60 mA	T _j = 125°C	
I _L	Latching current	150- mA	T _j = 25°C	
		50-200 mA	T _j = 125°C	

Switching

di/dt_{crit}	Critical rate of rise of on-state current	100 A/ μs	Cont. $f = 50\text{ Hz}$	$V_D \leq 0.67 \cdot V_{DRM}$, $T_j = 125^\circ\text{C}$ $I_{TRM} = 3000\text{ A}$ $I_{FG} = 2\text{ A}$, $t_r = 0.5\text{ }\mu\text{s}$
		200 A/ μs	60 sec. $f = 50\text{ Hz}$	
t_d	Delay time	$\leq 3.0\text{ }\mu\text{s}$	$V_D = 0.4 \cdot V_{DRM}$	$I_{FG} = 2\text{ A}$, $t_r = 0.5\text{ }\mu\text{s}$
t_q	Turn-off time	$\leq 700\text{ }\mu\text{s}$	$V_D \leq 0.67 \cdot V_{DRM}$ $dv_D/dt = 20\text{ V}/\mu\text{s}$	$I_{TRM} = 3000\text{ A}$, $T_j = 125^\circ\text{C}$ $V_R > 200\text{ V}$, $di_T/dt = -5\text{ A}/\mu\text{s}$
Q_{rr}	Recovery charge	min	4800 μAs	
		max	6200 μAs	

Triggering

V_{GT}	Gate trigger voltage	2.6 V	$T_j = 25^\circ$
I_{GT}	Gate trigger current	400 mA	$T_j = 25^\circ$
V_{GD}	Gate non-trigger voltage	0.3 V	$V_D = 0.4 \times V_{DRM}$
I_{GD}	Gate non-trigger current	10 mA	$V_D = 0.4 \times V_{DRM}$
V_{FGM}	Peak forward gate voltage	12 V	
I_{FGM}	Peak forward gate current	10 A	
V_{RGM}	Peak reverse gate voltage	10 V	
P_G	Gate power loss	3 W	

Thermal

T_{jmax}	Max. operating junction temperature range	125 °C	
T_{stg}	Storage temperature range	-40...140 °C	
R_{thJC}	Thermal resistance junction to case	20 K/kW	Anode side cooled
		20 K/kW	Cathode side cooled
		10 K/kW	Double side cooled
R_{thCH}	Thermal resistance case to heat sink	4 K/kW	Single side cooled
		2 K/kW	Double side cooled

Analytical function for transient thermal impedance:

$$Z_{thJC}(t) = \sum_{i=1}^n R_i(1 - e^{-t/\tau_i})$$

i	1	2	3	4
R_i (K/kW)	6.52	1.55	1.67	0.49
τ_i (s)	0.4562	0.0792	0.0088	0.0037




Fig. 1 Transient thermal impedance junction to case.




Fig. 2 On-state characteristics.




Fig. 3 On-state characteristics.
 $T_j=125^\circ\text{C}$, 10ms half sine




Fig. 4 On-state power dissipation vs. mean on-state current. Turn-on losses excluded.




Fig. 5 Max. permissible case temperature vs. mean on-state current.




Fig. 6 Surge on-state current vs. pulse length. Half-sine wave.




Fig. 7 Surge on-state current vs. number of pulses. Half-sine wave, 10 ms, 50Hz.




Fig. 8 Gate trigger characteristics.




Fig. 9 Max. peak gate power loss.




Fig. 10 Recovery charge vs. decay rate of on-state current.




Fig. 11 Peak reverse recovery current vs. decay rate of on-state current.

ABB Semiconductors AG reserves the right to change specifications without notice.



ABB Semiconductors AG
 Fabrikstrasse 3
 CH-5600 Lenzburg, Switzerland

Telephone +41 (0)62 888 6419
 Fax +41 (0)62 888 6306
 Email abbsem@ch.abb.com
 Internet www.abbsem.com