



EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : CDLE-532-085

REV.: 1

5.0mm Round Type LED Lamps

PART NO. : 5323ID

ECN :

Page: 1/4

■ Features :

- Choice of various viewing angles
- Available on tape and reel.
- Reliable and robust


■ Descriptions :

- The series is specially designed for applications requiring higher brightness
- The led lamps are available with different colors, intensities, epoxy colors, etc.

■ Applications :

- TV set
- Monitor
- Telephone
- Computer

■ Package Dimensions:



■ Notes :

1. All dimensions are in millimeters.
2. An epoxy meniscus may extend about 1.5mm(0.059") down to the lead.
3. Tolerances unless Dimension ± 0.25 mm.

PART NO.	Chip		Lens Color
	Material	Emitted Color	
5323ID	GaAsP/GaP	Hi-Eff Red	Red Diffused

Office : 7C Building, Lian Hua Port Industrial District, Lian Hua Shan

Bonded Pricessing Zone Pan Yu, Guang Zhou, China

TEL. : (020)84860913,84860914

FAX : (020)84860600

http : //www.everlight.com

A0112042,YG0112007



5.0mm Round Type LED Lamps

PART NO. : 5323IDECN : Page: 2/4

■ Absolute Maximum Ratings at Ta = 25°C

Parameter	Symbol	Rating	Unit
Forward Current	IF	30	mA
Operating Temperature	Topr	-40 to +85	°C
Storage Temperature	Tstg	-40 to +100	°C
Soldering Temperature	Tsol	260 ± 5	°C
Power Dissipation	Pd	100	mW
Peak Forward Current(Duty 1/10 @ 1KHz)	IF(Peak)	160	mA
Reverse Voltage	VR	5	V

■ Electronic Optical Characteristics :

Parameter	Symbol	Min	Typ.	Max.	Unit	Condition
Luminous Intensity	Iv	4.00	8.00	/	mcd	IF= 10 mA
Viewing Angle	2θ 1/2	/	X=60 Y=90	/	deg	IF= 20 mA
Peak Wavelength	λ p	/	635	/	nm	IF= 20 mA
Dominant Wavelength	λ d	/	625	/	nm	IF= 20 mA
Spectrum Radiation Bandwidth	△ λ	/	45	/	nm	IF= 20 mA
Forward Voltage	VF	1.70	2.00	2.40	V	IF= 20 mA
Reverse Current	IR	/	/	10	μ A	VR= 5 V



EVERLIGHT ELECTRONICS CO.,LTD.







Device Number : CDLE-031-077 REV.: 1

5.0mm Round Type LED Lamps

PART NO. : 5323ID ECN : Page: 3/4

■ Typical Electro-Optical Characteristic Curves:

< I >





EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : CDLE-532-085 REV.: 1

5.0mm Round Type LED Lamps

PART NO. : 313-2UBC/C470 ECN : Page: 4/4

■ Reliability test items and conditions:

NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Solder Heat	TEMP : 260°C ± 5 °C	5 SEC	76 PCS	0/1
2	Temperature Cycle	H : +85°C 30min § 5 min L : -55°C 30min	50 CYCLES	76 PCS	0/1
3	Thermal Shock	H : +100°C 5min § 10 sec	50 CYCLES	76 PCS	0/1
4	High Temperature Storage	TEMP : 100°C	1000 HRS	76 PCS	0/1
5	Low Temperature Storage	TEMP : -55°C	1000 HRS	76 PCS	0/1
6	DC Operating Life	TEMP : 25°C If = 20 mA	1000 HRS	76 PCS	0/1
7	High Temperature / High Humidity	85°C / 85% RH	1000 HRS	76 PCS	0/1