

MN54ACTQ16373-X REV 1A0

 Original Creation Date: 07/12/96
 Last Update Date: 09/11/96
 Last Major Revision Date: 07/12/96

16-Bit Transceiver with TRI-STATE Outputs
General Description

The ACTQ16373 contains sixteen non-inverting latches with TRI-STATE outputs and is intended for bus oriented applications. The device is byte controlled. The flip-flops appear transparent to the data when the Latch Enable (LE) is HIGH. When LE is low, the data that meets the setup time is latched. Data appears on the bus when the Output Enable (OE) is LOW. When OE is HIGH, the outputs are in high Z state. The ACTQ16373 utilizes NSC Quiet Series technology to guarantee quiet output switching and improved dynamic threshold performance. FACT Quiet Series TM features GTO TM output control for superior performance.

Industry Part Number

54ACTQ16373

NS Part Numbers

54ACTQ16373FMQB

Prime Die

D16373

Processing

MIL-STD-883, Method 5004

Quality Conformance Inspection

MIL-STD-883 5005

Subgrp Description Temp (°C)

1	Static tests at	+25 C
2	Static tests at	+125 C
3	Static tests at	-55 C
4	Dynamic tests at	+25 C
5	Dynamic tests at	+125 C
6	Dynamic tests at	-55 C
7	Functional tests at	+25 C
8A	Functional tests at	+125 C
8B	Functional tests at	-55 C
9	Switching tests at	+25 C
10	Switching tests at	+125 C
11	Switching tests at	-55 C

Features

- Utilizes NSC FACT Quiet Series technology
- Guaranteed simultaneous switching noise level and dynamic threshold performance
- Guaranteed pin-to-pin output skew
- Separate control logic for each byte
- 16-bit version of the ACTQ373
- Outputs source/sink 24 mA
- Addition specs for Multiple Output Switching
- Output Loading specs for both 50 pF and 250 pF loads

(Absolute Maximum Ratings)

(Note 1)

Supply Voltage (Vcc)	-0.5V to +7.0V
DC Input Diode Current (Iik)	
Vi = -0.5V	-20 mA
Vi = Vcc +0.5V	+20 mA
DC Output Diode Current (Iok)	
Vo = -0.5V	-20 mA
Vo = Vcc +0.5V	+20 mA
DC Output Voltage (Vo)	-0.5V to Vcc +0.5V
DC Vcc or Ground Current Per Output Pin	±50 mA
Junction Temperature (Tj)	
Ceramic Flatpack	+175 C
Thermal Resistance	
Junction-To-Case (Theta JC)	10 C/Watt
Junction-To-Ambient (Theta JA)	80 C/Watt
Storage Temperature	-65 C to + 150 C
Lead Temperature	
(Soldering , 10 Seconds)	+ 300 C
ESD Classification	Class 1
Maximum Power Dissipation	750 mW
DC Output Source/Sink Current (Io)	±50 mA

Note 1: Absolute maximum ratings are those values beyond which damage to the device may occur. The databook specifications should be met, without exception, to ensure that the system design is reliable over its power supply, temperature, and output/input loading variables. National does not recommend operation of FACT TM circuits outside databook specifications.

Recommended Operating Conditions

Supply Voltage (Vcc)	4.5V to 5.5V
Input Voltage (Vi)	0V to Vcc
Output Voltage (Vo)	0V to Vcc
Operating Temperature (Ta)	-55 C to +125 C
Minimum Input Edge Rate (Delta V/Delta t)	
ACTQ Devices	
Vin from 0.8V to 2.0V	
Vcc @ 4.5V, 5.5V	125 mV/ns
Maximum Output Current	
High Level (IOH)	-24 mA
Low Level (IOL)	24 mA

Electrical Characteristics

DC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)

DC: VCC 4.5V to 5.5V, Temp. Range: -55C to 125C. NOTE: -55C TEMPERATURE, SUBGROUP 3 IS GUARANTEED BUT NOT TESTED.

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
IIH	High Level input Current	VCC=5.5V, VIH=5.5V	1, 2	INPUT		0.1	uA	1
			1, 2	INPUT		1.0	uA	2, 3
IIL	Low Level input Current	VCC=5.5V, VIL=0.0V	1, 2	INPUT		-0.1	uA	1
			1, 2	INPUT		-1.0	uA	2, 3
VOL	Low level output voltage	VCC=4.5V, VIL=0.8V, IOL=24.0mA, VIH=2.0V	1, 2	OUTPUT		.36	V	1
			1, 2	OUTPUT		.50	V	2, 3
		VCC=4.5V, VIL=0.8V, IOL=50.0uA, VIH=2.0V	1, 2	OUTPUT		.10	V	1, 2, 3
			1, 2	OUTPUT		.36	V	1
		VCC=5.5V, VIL=0.8V, IOL=24.0mA, VIH=2.0V	1, 2	OUTPUT		.50	V	2, 3
			1, 2	OUTPUT		.10	V	1, 2, 3
VIOL	Dynamic Output Current LOW	VCC=5.5V, VIH=5.5V, VIL=0.0V, IOL=50.0mA	1, 2, 5	OUTPUT		1.65	V	1, 2, 3
VOH	High Level Output Voltage	VCC=4.5V, VIL=0.8V, IOL=-24.0mA, VIH=2.0V	1, 2	OUTPUT	3.86		V	1
			1, 2	OUTPUT	3.70		V	2, 3
		VCC=4.5V, VIL=0.8V, IOL=-50.0uA, VIH=2.0V	1, 2	OUTPUT	4.4		V	1, 2, 3
			1, 2	OUTPUT	4.86		V	1
		VCC=5.5V, VIL=0.8V, IOL=-24.0mA, VIH=2.0V	1, 2	OUTPUT	4.7		V	2, 3
			1, 2	OUTPUT	5.4		V	1, 2, 3
VIOH	Dynamic Output Current HIGH	VCC=5.5V, VIH=5.5V, VIL=0.0V, IOL=-50.0mA	1, 2, 5	OUTPUT	3.85		V	1, 2, 3
ICC	Supply Current	VCC=5.5V, VIN=5.5V or Gnd	1, 2	VCC		8.0	uA	1
			1, 2	VCC		160	uA	2, 3
ICCT	Supply Current	VCC=5.5V, VINH=3.4V	1, 2	VCC		1.0	mA	1
			1, 2	VCC		1.6	mA	2, 3
IOZH	Maximum TRI-STATE Leakage Current	VCC=4.5V, VOUT=4.5V, VIL=0.0V, VIH(OE)=2.0V	1, 2	OUTPUT		0.5	uA	1
			1, 2	OUTPUT		10	uA	2, 3
		VCC=5.5V, VOUT=5.5V, VIL=0.0V, VIH(OE)=2.0V	1, 2	OUTPUT		0.5	uA	1
			1, 2	OUTPUT		10	uA	2, 3

Electrical Characteristics

DC PARAMETERS(Continued)

(The following conditions apply to all the following parameters, unless otherwise specified.)

DC: VCC 4.5V to 5.5V, Temp. Range: -55C to 125C. NOTE: -55C TEMPERATURE, SUBGROUP 3 IS GUARANTEED BUT NOT TESTED.

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
IOZL	Maximum TRI-STATE Leakage Current	VCC=4.5V, VOUT=4.5V, VIL=4.5V, VIH(OE)=2.0V	1, 2	OUTPUT		-0.5	uA	1
			1, 2	OUTPUT		-10	uA	2, 3
		VCC=5.5V, VOUT=5.5V, VIL=5.5V, VIH(OE)=2.0V	1, 2	OUTPUT		-0.5	uA	1
			1, 2	OUTPUT		-10	uA	2, 3
VIKL		VCC=4.5V, IKL=-18mA	1, 2	INPUT		-1.2	V	1, 2, 3
VIKH		VCC=4.5V, IKH=18mA	1, 2	INPUT		5.7	V	1, 2, 3
CIN	INPUT PIN CAPACITANCE		6	INPUT		10	pF	4
COUT	OUTPUT PIN CAPACITANCE		6	OUTPUT		15	pF	4
CPD	POWER DISSIPATION CAPACITANCE		6			100	pF	4
VILD	Maximum Low Dynamic Input Voltage Level	VCC=5.0V, LOAD 50pF / 500 OHMS	6, 9	INPUT		0.8	V	4
VIHD	Minimum High Dynamic Input Voltage Level	VCC=5.0V, LOAD 50pF / 500 OHMS	6, 9	INPUT	2.0		V	4
VOLP	Quiet Output Maximum Dynamic Vol	VCC=5.0V, LOAD 50pF / 500 OHMS Maximum High Output Noise	6, 8	OUTPUT		0.8	V	4
VOLV	Quiet Output Minimum Dynamic Vol	VCC=5.0V, LOAD 50pF / 500 OHMS Maximum Low Output Noise	6, 8	OUTPUT		-0.8	V	4
VOHP	Maximum Overshoot	VCC=5.0V, LOAD 50pF / 500 OHMS Maximum Overshoot	6, 8	OUTPUT		VOH +1.0	V	4
VOHV	Minimum Vcc Droop	VCC=5.0V, LOAD 50pF / 500 OHMS Minimum Vcc Droop	6, 8	OUTPUT		VOH -1.0	V	4

AC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)

AC: CL=50pf, RL=500 OHMS, TR/TFALL=3.0ns, Temp range: -55C to +125C. NOTE: -55C TEMPERATURE, SUBGROUP 11 GUARANTEED BUT NOT TESTED.

tpLH(1)	Propagation Delay	VCC=4.5V	3, 4, 7	Dn to On	3.0	9.0	ns	9
			3, 4, 7	Dn to On	3.0	10.5	ns	10, 11

Electrical Characteristics

AC PARAMETERS(Continued)

(The following conditions apply to all the following parameters, unless otherwise specified.)

AC: CL=50pf, RL=500 OHMS, TR/TFALL=3.0ns, Temp range: -55C to +125C. NOTE: -55C TEMPERATURE, SUBGROUP 11
GUARANTEED BUT NOT TESTED.

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
tpHL(1)	Propagation Delay	VCC=4.5V	3, 4, 7	Dn to On	3.0	8.5	ns	9
			3, 4, 7	Dn to On	3.0	10.0	ns	10, 11
tpLH(2)	Propagation Delay	VCC=4.5V	3, 4, 7	LE to On	3.0	9.5	ns	9
			3, 4, 7	LE to On	3.0	11.0	ns	10, 11
tpHL(2)	Propagation Delay	VCC=4.5V	3, 4, 7	LE to On	3.0	8.5	ns	9
			3, 4, 7	LE to On	3.0	10.0	ns	10, 11
tpLZ	Output Disable Time	VCC=4.5V	3, 4, 7	$\overline{OE}$ to On	2.0	8.0	ns	9
			3, 4, 7	$\overline{OE}$ to On	2.0	9.0	ns	10, 11
tpHZ	Output Disable Time	VCC=4.5V	3, 4, 7	$\overline{OE}$ to On	2.0	8.0	ns	9
			3, 4, 7	$\overline{OE}$ to On	2.0	9.0	ns	10, 11
tpZL	Output Enable Time	VCC=4.5V	3, 4, 7	$\overline{OE}$ to On	2.5	9.5	ns	9
			3, 4, 7	$\overline{OE}$ to On	2.5	11.0	ns	10, 11
tpZH	Output Enable Time	VCC=4.5V	3, 4, 7	$\overline{OE}$ to On	2.5	8.5	ns	9
			3, 4, 7	$\overline{OE}$ to On	2.5	10.0	ns	10, 11
Tset(L/H)	Set-up time	VCC=4.5V	6	Dn to LE	3.0		ns	9, 10, 11
Thold(L/H)	Hold time	VCC=4.5V	6	Dn to LE	1.5		ns	9, 10, 11
Twidth(H)	Pulse width	VCC=4.5V	6	LE	4.0		ns	9, 10, 11
TOSHL	Pin to Pin Skew HL Data to Output	VCC=4.5V	6	Pin to Pin Skew		1.3	ns	9, 10, 11
TOSLH	Pin to Pin Skew LH Data to Output	VCC=4.5V	6	Pin to Pin Skew		2.1	ns	9, 10, 11

Electrical Characteristics

AC PARAMETERS(Continued)

(The following conditions apply to all the following parameters, unless otherwise specified.)

AC: CL=50pf, RL=500 OHMS, TR/TFALL=3.0ns, Temp range: -55C to +125C. NOTE: -55C TEMPERATURE, SUBGROUP 11 GUARANTEED BUT NOT TESTED.

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
TOST	Pin to Pin Skew LH/HL Data to Output	VCC=4.5V	6	Pin to Pin Skew		4.0	ns	9, 10, 11

- Note 1: SCREEN TESTED 100% ON EACH DEVICE AT +25C & +125C TEMPERATURE, SUBGROUPS 1, 2, 7, & 8.
- Note 2: SAMPLE TESTED (METHOD 5005, TABLE 1) ON EACH MFG. LOT AT +25C & +125C TEMPERATURE, SUBGROUPS A1, 2, 7, & 8.
- Note 3: SCREEN TESTED 100% ON EACH DEVICE AT +25C TEMPERATURE ONLY SUBGROUP A9.
- Note 4: SAMPLE TESTED (METHOD 5005, TABLE 1) ON EACH MFG. LOT AT +25C & +125C TEMPERATURE, SUBGROUPS A9 & 10.
- Note 5: TRANSMISSION LINE DRIVING TEST, GUARDBANDED LIMITS SET FOR +25C, 2 MSEC DURATION MAX.
- Note 6: GUARANTEED BUT NOT TESTED. (DESIGN CHARACTERIZATION DATA)
- Note 7: +25C & +125C MIN LIMITS GUARANTEED FOR 5.5V BY GUARDBANDING 4.5V MIN. LIMITS.
- Note 8: MAX NUMBER OF OUTPUTS DEFINED AS (N). DATA INPUTS ARE DRIVEN 0V TO 3V. ONE OUTPUT @ VOL.
- Note 9: MAX NUMBER OF DATA INPUTS (N) SWITCHING. (N-1) INPUTS SWITCHING 0V TO 3V. INPUT-UNDER-TEST SWITCHING 3V TO THRESHOLD (VILD), 0V TO THRESHOLD (VIHD), FREQ= 1 MHZ.