

MN54ACTQ533-X REV 1B0

 Original Creation Date: 07/16/96
 Last Update Date: 03/19/99
 Last Major Revision Date: 07/16/96

Octal Transparent Latch With 3-State Outputs

General Description

The ACTQ533 consists of eight latches with TRI-STATE outputs for bus organized system applications. The flip-flops appear transparent to the data when Latch Enable (LE) is HIGH. When LE is low, the data satisfying the input timing requirements is latched. Data appears on the bus when the Output Enable (OE) is LOW. When OE is HIGH, the bus output is in the high impedance state.

The ACTQ373 utilizes NSC Quiet Series technology to guarantee quiet output switching and improve dynamic threshold performance. FACT Quiet Series TM features GTO TM output control and undershoot corrector in addition to a split ground bus for superior performance.

Industry Part Number

54ACTQ533

NS Part Numbers

 54ACTQ533DMQB
 54ACTQ533FMQB
 54ACTQ533LMQB

Prime Die

D533

Processing

MIL-STD-883, Method 5004

Quality Conformance Inspection

MIL-STD-883, Method 5004

Subgrp	Description	Temp (°C)
1	Static tests at	+25 C
2	Static tests at	+125 C
3	Static tests at	-55 C
4	Dynamic tests at	+25 C
5	Dynamic tests at	+125 C
6	Dynamic tests at	-55 C
7	Functional tests at	+25 C
8A	Functional tests at	+125 C
8B	Functional tests at	-55 C
9	Switching tests at	+25 C
10	Switching tests at	+125 C
11	Switching tests at	-55 C

Features

- I_{cc} and I_{oz} reduced by 50%
- Guaranteed simultaneous switching noise level and dynamic threshold performance
- Guaranteed pin-to-pin skew AC performance
- Improved latch up immunity
- Eight latches in a single package
- TRI-STATE outputs drive bus lines or buffer memory address registers
- Outputs source/sink 24 mA
- 4 kV minimum ESD immunity

(Absolute Maximum Ratings)

(Note 1)

Supply Voltage (Vcc)	-0.5V to +7.0V
DC Input Diode Current (Iik)	
Vi = -0.5V	-20 mA
Vi = Vcc +0.5V	+20 mA
DC Input Voltage (Vi)	
	-0V to Vcc +0.5V
DC Output Diode Current (Iok)	
Vo = -0.5V	-20 mA
Vo = Vcc +0.5V	+20 mA
DC Output Voltage (Vo)	
	-0.5V to Vcc +0.5V
DC Output Source or Sink Current (Io)	
	±50 mA
DC Vcc or Ground Current per Output Pin (Icc or Ignd)	
	±50 mA
Storage Temperature (Tstg)	
	-65 C to +150 C
DC Latchup Source or Sink Current	
	±300 mA
Junction Temperature (Tj)	
CDIP	175 C

Note 1: Absolute maximum ratings are those values beyond which damage to the device may occur. The databook specification should be met, without exception, to ensure that the system design is reliable over its power supply, temperature and output/input loading variables. National does not recommend operation of FACT™ circuits outside databook specifications.

Recommended Operating Conditions

(Note 1)

Supply Voltage (Vcc)	4.5V to 5.5V
Input Voltage (Vi)	
	0V to Vcc
Output Voltage (Vo)	
	0V to Vcc
Operating Temperature (Ta)	
	-55 C to +125 C
Minimum Input Edge Rate Delta V/Delta t	
ACTQ Devices	
Vin from 0.8V to 2.0V	
Vcc @ 4.5V, 5.5V	125 mV/ns

Note 1: All commercial packaging is not recommended for applications requiring greater than 2000 temperature cycles from -40C to +125C.

Electrical Characteristics

DC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)

DC: VCC 4.5V to 5.5V, Temperature Range: -55C to 125C. NOTE: -55C TEMPERATURE, SUBGROUP 3 IS GUARANTEED BUT NOT TESTED.

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
IIH	High Level Input Current	VCC=5.5V, VM=5.5V	1, 2	INPUT		0.1	uA	1
			1, 2	INPUT		1.0	uA	2, 3
IIL	Low Level Input Current	VCC=5.5V, VM=0.0V	1, 2	INPUT		-0.1	uA	1
			1, 2	INPUT		-1.0	uA	2, 3
VOL	Low Level Output Voltage	VCC=4.5V, VIH=2.0V, VIL=0.8V, IOL=50.0uA	1, 2	OUTPUT		.10	V	1, 2, 3
		VCC=5.5V, VIH=2.0V, VIL=0.8V, IOL=50.0uA	1, 2	OUTPUT		.10	V	1, 2, 3
		VCC=4.5V, VIH=2.0V, VIL=0.8V, IOL=24.0mA	1, 2	OUTPUT		.36	V	1
		VCC=4.5V, VIH=2.0V, VIL=0.8V, IOL=24.0mA	1, 2	OUTPUT		.50	V	2, 3
		VCC=5.5V, VIH=2.0V, VIL=0.8V, IOL=24.0mA	1, 2	OUTPUT		.36	V	1
		VCC=5.5V, VIH=2.0V, VIL=0.8V, IOL=24.0mA	1, 2	OUTPUT		.50	V	2, 3
VIOL	Dynamic Output Current LOW	VCC=5.5V, VIH=5.5V, VIL=0.0V, IOL=50.0mA	1, 2, 5	OUTPUT		1.65	V	1, 2, 3
VOH	High Level Output Voltage	VCC=4.5V, VIH=2.0V, VIL=0.8V, IOH=-50.0uA	1, 2	OUTPUT	4.40		V	1, 2, 3
		VCC=5.5V, VIH=2.0V, VIL=0.8V, IOH=-50.0uA	1, 2	OUTPUT	5.40		V	1, 2, 3
		VCC=4.5V, VIH=2.0V, VIL=0.8V, IOH=-24.0mA	1, 2	OUTPUT	3.86		V	1
		VCC=4.5V, VIH=2.0V, VIL=0.8V, IOH=-24.0mA	1, 2	OUTPUT	3.70		V	2, 3
		VCC=5.5V, VIH=2.0V, VIL=0.8V, IOH=-24.0mA	1, 2	OUTPUT	4.86		V	1
		VCC=5.5V, VIH=2.0V, VIL=0.8V, IOH=-24.0mA	1, 2	OUTPUT	4.70		V	2, 3
VI0H	Dynamic Output Current HIGH	VCC=5.5V, VIH=5.5V, VIL=0.0V, IOH=-50.0mA	1, 2, 5	OUTPUT	3.85		V	1, 2, 3
IOZH	Maximum TRI-STATE Leakage Current	VCC=4.5V, VM=4.5V, VIH=2.0V, VINH=4.5V, VINL=0.0V	1, 2	OUTPUT		0.25	uA	1
		VCC=4.5V, VM=4.5V, VIH=2.0V, VINH=4.5V, VINL=0.0V	1, 2	OUTPUT		5.0	uA	2, 3
		VCC=5.5V, VM=5.5V, VIH=2.0V, VINH=5.5V, VINL=0.0V	1, 2	OUTPUT		0.25	uA	1
		VCC=5.5V, VM=5.5V, VIH=2.0V, VINH=5.5V, VINL=0.0V	1, 2	OUTPUT		5.0	uA	2, 3
IOZL	Maximum TRI-STATE Leakage Current	VCC=4.5V, VM=0.0V, VIH=2.0V, VINH=4.5V	1, 2	OUTPUT		-0.25	uA	1
		VCC=4.5V, VM=0.0V, VIH=2.0V, VINH=4.5V	1, 2	OUTPUT		-5.0	uA	2, 3
		VCC=5.5V, VM=0.0V, VIH=2.0V, VINH=5.5V	1, 2	OUTPUT		-0.25	uA	1
		VCC=5.5V, VM=0.0V, VIH=2.0V, VINH=5.5V	1, 2	OUTPUT		-5.0	uA	2, 3

Electrical Characteristics

DC PARAMETERS(Continued)

(The following conditions apply to all the following parameters, unless otherwise specified.)

DC: VCC 4.5V to 5.5V, Temperature Range: -55C to 125C. NOTE: -55C TEMPERATURE, SUBGROUP 3 IS GUARANTEED BUT NOT TESTED.

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
ICCH	Supply Current	VCC=5.5V, VINH=5.5V, VINL=0.0V	1, 2	VCC		4.0	uA	1
			1, 2	VCC		80	uA	2, 3
ICCL	Supply Current	VCC=5.5V, VINH=5.5V, VINL=0.0V	1, 2	VCC		4.0	uA	1
			1, 2	VCC		80	uA	2, 3
ICCZ	Supply Current	VCC=5.5V, VINH=5.5V, VINL=0.0V	1, 2	VCC		4.0	uA	1
			1, 2	VCC		80	uA	2, 3
ICCT	Supply Current	VCC=5.5V, VIHT=VCC-2.1V	1, 2	VCC		1.0	mA	1
			1, 2	VCC		1.6	mA	2, 3
VIKL		VCC=4.5V, IKL=-18mA	1, 2	INPUT		-1.2	V	1, 2, 3
VIKH		VCC=4.5V, IKH=18mA	1, 2	INPUT		5.7	V	1, 2, 3
VILD	Maximum Low Level Dynamic Input Voltage	VCC=5.0V, LOAD 50pF, 500 OHMS	6, 9	INPUT		0.8	V	4
VIHD	Minimum High Level Dynamic Input Voltage	VCC=5.0V, LOAD 50pF, 500 OHMS	6, 9	INPUT	2.0		V	4
VOLP	Quiet Output Maximum Dynamic VOL	VCC=5.0V, LOAD 50pF, 500 OHMS	6, 8	OUTPUT		1.7	V	4
VOLV	Quiet Output Minimum Dynamic VOL	VCC=5.0V, LOAD 50pF, 500 OHMS	6, 8	OUTPUT		-1.2	V	4

Electrical Characteristics

AC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)

AC: CL=50pF, RL=500 OHMS, TR=3.0ns, TF=3.0ns, Temp range: -55C to +125C. NOTE: -55C TEMPERATURE, SUBGROUP 11 IS GUARANTEED BUT NOT TESTED.

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
tpLH(1)	Propagation Delay	VCC=4.5V	3, 4, 7	Dn to On	1.5	8.0	ns	9
			3, 4, 7	Dn to On	1.5	9.0	ns	10, 11
tpHL(1)	Propagation Delay	VCC=4.5V	3, 4, 7	Dn to On	1.5	8.0	ns	9
			3, 4, 7	Dn to On	1.5	9.0	ns	10, 11
tpLH(2)	Propagation Delay	VCC=4.5V	3, 4, 7	Le to On	1.5	9.5	ns	9
			3, 4, 7	Le to On	1.5	10.5	ns	10, 11
tpHL(2)	Propagation Delay	VCC=4.5V	3, 4, 7	Le to On	1.5	9.5	ns	9
			3, 4, 7	Le to On	1.5	10.5	ns	10, 11
tpZH	Output Enable Time	VCC=4.5V	3, 4, 7	OE to On	1.5	9.0	ns	9
			3, 4, 7	OE to On	1.5	10.5	ns	10, 11
tpZL	Output Enable Time	VCC=4.5V	3, 4, 7	OE to On	1.5	9.0	ns	9
			3, 4, 7	OE to On	1.5	10.5	ns	10, 11
tpHZ	Output Disable Time	VCC=4.5V	3, 4, 7	OE to On	1.5	9.0	ns	9
			3, 4, 7	OE to On	1.5	10.5	ns	10, 11
tpLZ	Output Disable Time	VCC=4.5V	3, 4, 7	OE to On	1.5	6.0	ns	9
			3, 4, 7	OE to On	1.5	6.5	ns	10, 11
ts(H/L)	Setup Time HIGH or LOW	VCC=4.5V	6	Dn to Le	3.0		ns	9, 10, 11
th(H/L)	Hold Time HIGH or LOW	VCC=4.5V	6	Dn to Le	1.5		ns	9, 10, 11
tw(H)	Pulse Width	VCC=4.5V	6	LE PULSE Width	5.0		ns	9, 10, 11

Note 1: SCREEN TESTED 100% ON EACH DEVICE AT +25C & +125C TEMPERATURE, SUBGROUPS 1, 2, 7, 8.

(Continued)

- Note 2: SAMPLE TESTED (METHOD 5005, TABLE 1) ON EACH MFG. LOT AT +25C & +125C TEMPERATURE, SUBGROUPS A1, 2, 7, & 8.
- Note 3: SCREEN TESTED 100% ON EACH DEVICE AT +25C TEMPERATURE ONLY, SUBGROUP A9.
- Note 4: SAMPLE TESTED (METHOD 5005, TABLE 1) ON EACH MFG. LOT AT +25C & +125C TEMPERATURE, SUBGROUPS A9 & 10.
- Note 5: TRANSMISSION LINE DRIVING TEST, GUARDBAND LIMITS SET FOR +25C, 2 MSEC DURATION MAX.
- Note 6: DESIGN CHARACTERIZATION DATA ONLY.
- Note 7: +25C & +125C MIN LIMITS GUARANTEED FOR 5.5V BY GUARDBANDING 4.5V MIN. LIMITS.
- Note 8: MAX NUMBER OF OUTPUTS DEFINED AS (N). DATA INPUTS ARE DRIVEN 0V TO 3V. ONE OUTPUT @ GND.
- Note 9: MAX NUMBER OF DATA INPUTS (N) SWITCHING. N-1 INPUTS SWITCHING 0V TO 3V. INPUT-UNDER-TEST SWITCHING 3V TO THRESHOLD (VILD), 0V TO THRESHOLD (VIHD), FREQ. = 1 MHz.

Revision History

Rev	ECN #	Rel Date	Originator	Changes
1B0	M0003310	03/19/99	Linda Collins	Removed the reference to SMD 5962-92919 from the Features section.