

MN54AC245-X REV 2A0

Original Creation Date: 06/28/96

Last Update Date: 03/31/97

Last Major Revision Date: 03/26/97

Octal Bidirectional Transceiver With TRI- State Inputs/Outputs

General Description

The AC245 contains eight non-inverting bidirectional buffers with 3-state outputs and is intended for bus-oriented applications. Current sinking capability is 24 mA at the A and B ports. The Transmit/Receiver (T/R) input determines the direction of data flow through the bidirectional transceiver. Transmit (active HIGH) enables data from A ports to B ports; Receive (active LOW) enables data from B ports to A ports. The Output Enable input when HIGH, disables both A and B ports by placing them in a HIGH Z condition.

Industry Part Number

54AC245

Prime Die

Z245

NS Part Numbers

54AC245DMQB

54AC245FMQB

54AC245LMQB

Processing

MIL-STD-883, Method 5004

Quality Conformance Inspection

MIL-STD-883, Method 5005

Subgrp	Description	Temp (°C)
1	Static tests at	+25
2	Static tests at	+125
3	Static tests at	-55
4	Dynamic tests at	+25
5	Dynamic tests at	+125
6	Dynamic tests at	-55
7	Functional tests at	+25
8A	Functional tests at	+125
8B	Functional tests at	-55
9	Switching tests at	+25
10	Switching tests at	+125
11	Switching tests at	-55

Features

- I_{cc} and I_{oz} reduced by 50%
- Non-inverting buffers
- Bidirectional data path
- A and B Outputs source/sink 24 mA
- Standard Military Drawing (SMD)
- AC245: 5962- 87758

(Absolute Maximum Ratings)

(Note 1)

Supply Voltage (Vcc)	-0.5V to +7.0V
DC Input Diode Current (Iik)	
Vi = -0.5V	-20 mA
Vi = Vcc +0.5V	+20 mA
DC Input Voltage (Vi)	-0.5V to Vcc +0.5V
DC Output Diode Current (Iok)	
Vo = -0.5V	-20 mA
Vo = Vcc + 0.5V	+20 mA
DC Output Voltage (Vo)	-0.5V to Vcc +0.5V
DC Output Source or Sink Current (Io)	±50 mA
DC Vcc or Ground Current per Output Pin (Icc or Ignd)	±50 mA
Junction Temperature(Tj)	175 C
Storage Temperature (Tstg)	-65 C to +150 C

Note 1: Absolute maximum ratings are those values beyond which damage to the device may occur. The databook specification should be met, without exception, to ensure that the system design is reliable over its power supply, temperature, and output/input loading variables. National does not recommend operation of FACT TM circuits outside databook specifications.

Recommended Operating Conditions

Supply Voltage (Vcc)	2.0V to 6.0V
Input Voltage (Vi)	0V to Vcc
Output Voltage (Vo)	0V to Vcc
Operating Temperature (Ta)	-55 C to +125 C
Minimum Input Edge Rate (Delta V/ Delta t)	
AC Devices	
Vin from 30% to 70% of Vcc	
Vcc @ 3.0V, 4.5V, 5.5V	125 mV/ns

Electrical Characteristics

DC PARAMETER

(The following conditions apply to all the following parameters, unless otherwise specified.)

DC: VCC 3.0V to 5.5V, Temperature Range: -55C to 125C. NOTE: -55C TEMPERATURE, SUBGROUP 3 IS GUARANTEED BUT NOT TESTED.

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
IIH	High Level Input Current	VCC=5.5V, VM=5.5V, VINL=0.0V	1, 2	INPUT		0.1	uA	1
			1, 2	INPUT		1.0	uA	2, 3
IIL	Low Level Input Current	VCC=5.5V, VM=0.0V, VINL=0.0V	1, 2	INPUT		-0.1	uA	1
			1, 2	INPUT		-1.0	uA	2, 3
VOL	Low Level Output Voltage	VCC=3.0V, VIH=2.1V, VIL=0.9V, IOL=12.0mA	1, 2	OUTPUT		.36	V	1
			1, 2	OUTPUT		.50	V	2, 3
		VCC=3.0V, VIH=2.1V, VIL=0.9V, IOL=50.0uA	1, 2	OUTPUT		.10	V	1, 2, 3
			1, 2	OUTPUT		.10	V	1, 2, 3
		VCC=4.5V, VIH=3.15V, VIL=1.35V, IOL=50.0uA	1, 2	OUTPUT		.10	V	1, 2, 3
			1, 2	OUTPUT		.36	V	1
		VCC=5.5V, VIH=3.85V, VIL=1.65V, IOL=24.0mA	1, 2	OUTPUT		.36	V	1
			1, 2	OUTPUT		.50	V	2, 3
VIOL	Dynamic Output Current LOW	VCC=5.5V, VIH=3.85V, VIL=1.65V, IOL=50.0mA	1, 2, 5	OUTPUT		1.65	V	1, 2, 3
			1, 2, 5	OUTPUT		1.65	V	1, 2, 3
VOH	High Level Output Voltage	VCC=3.0V, VIH=2.1V, VIL=0.9V, IOH=-50.0uA	1, 2	OUTPUT	2.90		V	1, 2, 3
			1, 2	OUTPUT	2.56		V	1
		VCC=3.0V, VIH=2.1V, VIL=0.9V, IOH=-12.0mA	1, 2	OUTPUT	2.40		V	2, 3
			1, 2	OUTPUT	4.86		V	1
		VCC=5.5V, VIH=3.85V, VIL=1.65V, IOH=-24.0mA	1, 2	OUTPUT	4.70		V	2, 3
			1, 2	OUTPUT	3.86		V	1
		VCC=4.5V, VIH=3.15V, VIL=1.35V, IOH=-24.0mA	1, 2	OUTPUT	3.70		V	2, 3
			1, 2	OUTPUT	4.40		V	1, 2, 3
VIOH	Dynamic Output Current HIGH	VCC=5.5V, VIH=3.85V, VIL=1.65V, IOH=-50.0mA	1, 2, 5	OUTPUT	3.85		V	1, 2, 3
			1, 2, 5	OUTPUT	3.85		V	1, 2, 3

Electrical Characteristics

DC PARAMETER(Continued)

(The following conditions apply to all the following parameters, unless otherwise specified.)

DC: VCC 3.0V to 5.5V, Temperature Range: -55C to 125C. NOTE: -55C TEMPERATURE, SUBGROUP 3 IS GUARANTEED BUT NOT TESTED.

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
IOZH	Maximum TRI-STATE Leakage Current High	VCC=3.0V, VM=3.0V, VINH=0.0V, VINL=0.0V, VIH=2.1V	1, 2	OUTPUT		.3	uA	1
			1, 2	OUTPUT		5.5	uA	2, 3
		VCC=4.5V, VM=4.5V, VINH=4.5V, VINL=0.0V, VIH=3.15V	1, 2	OUTPUT		.3	uA	1
			1, 2	OUTPUT		5.5	uA	2, 3
		VCC=5.5V, VM=5.5V, VINH=5.5V, VINL=0.0V, VIH=3.85V	1, 2	OUTPUT		.3	uA	1
			1, 2	OUTPUT		5.5	uA	2, 3
IOZL	Maximum TRI-STATE Leakage Current Low	VCC=3.0V, VM=0.0V, VINH=3.0V, VINL=0.0V, VIH=2.1V	1, 2	OUTPUT		-.3	uA	1
			1, 2	OUTPUT		-5.5	uA	2, 3
		VCC=4.5V, VM=0.0V, VINH=4.5V, VINL=0.0V, VIH=3.15V	1, 2	OUTPUT		-.3	uA	1
			1, 2	OUTPUT		-5.5	uA	2, 3
		VCC=5.5V, VM=0.0V, VINH=5.5V, VINL=0.0V, VIH=3.85V	1, 2	OUTPUT		-.3	uA	1
			1, 2	OUTPUT		-5.5	uA	2, 3
ICCH	Supply Current	VCC=5.5V, VINH=5.5V, VINL=0.0V	1, 2	VCC		4	uA	1
			1, 2	VCC		80	uA	2, 3
ICCL	Supply Current	VCC=5.5V, VINH=5.5V, VINL=0.0V	1, 2	VCC		4	uA	1
			1, 2	VCC		80	uA	2, 3
ICCZ	Supply Current	VCC=5.5V, VINH=5.5V, VINL=0.0V	1, 2	VCC		4	uA	1
			1, 2	VCC		80	uA	2, 3

AC PARAMETER

(The following conditions apply to all the following parameters, unless otherwise specified.)

AC: CL=50pf, RL=500 OHMS, TRISE=3.0ns, TFALL=3.0ns, Temp Range: -55C to 125C. NOTE: -55C TEMPERATURE, SUBGROUP 11 IS GUARANTEED BUT NOT TESTED.

tpLH(1)	Propagation Delay	VCC=4.5V	3, 4, 6	A to B or B to A	1.5	6.5	ns	9
			3, 4, 6	A to B or B to A	1.5	8.5	ns	10, 11
tpHL(1)	Propagation Delay	VCC=4.5V	3, 4, 6	A to B or B to A	1.5	6.0	ns	9
			3, 4, 6	A to B or B to A	1.5	7.5	ns	10, 11

Electrical Characteristics

AC PARAMETER(Continued)

(The following conditions apply to all the following parameters, unless otherwise specified.)

AC: CL=50pf, RL=500 OHMS, TRISE=3.0ns, TFALL=3.0ns, Temp Range: -55C to 125C. NOTE: -55C TEMPERATURE, SUBGROUP 11 IS GUARANTEED BUT NOT TESTED.

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
tpZL(1)	Output Enable Time	VCC=4.5V	3, 4, 6	OE to An or Bn	1.5	9.0	ns	9
			3, 4, 6	OE to An or Bn	1.5	10.5	ns	10, 11
tpZH(1)	Output Enable Time	VCC=4.5V	3, 4, 6	OE to An or Bn	1.5	8.5	ns	9
			3, 4, 6	OE to An or Bn	1.5	10.0	ns	10, 11
tpHZ(1)	Output Disable Time	VCC=4.5V	3, 4, 6	OE to An or Bn	1.5	9.0	ns	9
			3, 4, 6	OE to An or Bn	1.5	10.5	ns	10, 11
tpLZ(1)	Output Disable Time	VCC=4.5V	3, 4, 6	OE to An or Bn	1.5	9.0	ns	9
			3, 4, 6	OE to An or Bn	1.5	10.5	ns	10, 11
tpLH(2)	Propagation Delay	VCC=3.0V	3, 4	A to B or B to A	1.0	8.5	ns	9
			3, 4	A to B or B to A	1.0	11.5	ns	10, 11
tpHL(2)	Propagation Delay	VCC=3.0V	3, 4	A to B or B to A	1.0	8.5	ns	9
			3, 4	A to B or B to A	1.0	10.0	ns	10, 11
tpZL(2)	Output Enable Time	VCC=3.0V	3, 4	OE to An or Bn	1.0	12.0	ns	9
			3, 4	OE to An or Bn	1.0	14.5	ns	10, 11

Electrical Characteristics

AC PARAMETER(Continued)

(The following conditions apply to all the following parameters, unless otherwise specified.)

AC: CL=50pf, RL=500 OHMS, TRISE=3.0ns, TFALL=3.0ns, Temp Range: -55C to 125C. NOTE: -55C TEMPERATURE, SUBGROUP 11 IS GUARANTEED BUT NOT TESTED.

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
tpZH(2)	Output Enable Time	VCC=3.0V	3, 4	OE to An or Bn	1.0	11.5	ns	9
			3, 4	OE to An or Bn	1.0	13.5	ns	10, 11
tpHZ(2)	Output Disable Time	VCC=3.0V	3, 4	OE to An or Bn	1.0	12.0	ns	9
			3, 4	OE to An or Bn	1.0	13.5	ns	10, 11
tpLZ(2)	Output Disable Time	VCC=3.0V	3, 4	OE to An or Bn	1.0	11.5	ns	9
			3, 4	OE to An or Bn	1.0	14.0	ns	10, 11

Note 1: SCREEN TESTED 100% ON EACH DEVICE AT +25C & +125C TEMPERATURE, SUBGROUPS 1, 2, 7, & 8.

Note 2: SAMPLE TESTED (METHOD 5005, TABLE 1) ON EACH MFG. LOT AT +25C & +125C TEMPERATURE, SUBGROUPS A1, 2, 7, & 8.

Note 3: SCREEN TESTED 100% ON EACH DEVICE AT +25C TEMPERATURE ONLY, SUBGROUP A9.

Note 4: SAMPLE TESTED (METHOD 5005, TABLE 1) ON EACH MFG. LOT AT +25C & +125C TEMPERATURE, SUBGROUPS A9 & 10.

Note 5: TRANSMISSION LINE DRIVING TEST, GUARDBAND LIMITS SET FOR +25C, 2 MSEC DURATION MAX.

Note 6: +25C & +125C MIN LIMITS GUARANTEED FOR 5.5V BY GUARDBANDING 4.5V MIN. LIMITS.