

# SN54HC652, SN74HC652 OCTAL BUS TRANSCEIVERS AND REGISTERS WITH 3-STATE OUTPUTS

SCLS151B – DECEMBER 1982 – REVISED MAY 1997

- Independent Registers and Enables for A and B Buses
- Multiplexed Real-Time and Stored Data
- True Data Paths
- High-Current 3-State Outputs Can Drive up to 15 LSTTL Loads
- Package Options Include Plastic Small-Outline (DW) and Ceramic Flat (W) Packages, Ceramic Chip Carriers (FK), and Standard Plastic (NT) and Ceramic (JT) 300-mil DIPs


## description

These devices consist of bus-transceiver circuits, D-type flip-flops, and control circuitry arranged for multiplexed transmission of data directly from the data bus or from the internal storage registers. Output-enable (OEAB and OEBA) inputs are provided to control the transceiver functions. Select-control (SAB and SBA) inputs are provided to select real-time or stored data transfer. A low input level selects real-time data, and a high input level selects stored data. Figure 1 illustrates the four fundamental bus-management functions that can be performed with the 'HC652.


Data on the A or B data bus, or both, can be stored in the internal D-type flip-flops by low-to-high transitions at the appropriate clock (CLKAB or CLKBA) terminals regardless of the select- or output-control terminals. When SAB and SBA are in the real-time transfer mode, it is possible to store data without using the internal D-type flip-flops by simultaneously enabling OEAB and OEBA. In this configuration, each output reinforces its input. When all other data sources to the two sets of bus lines are at high impedance, each set of bus lines remains at its last state.

The SN54HC652 is characterized for operation over the full military temperature range of  $-55^{\circ}\text{C}$  to  $125^{\circ}\text{C}$ . The SN74HC652 is characterized for operation from  $-40^{\circ}\text{C}$  to  $85^{\circ}\text{C}$ .

SN54HC652 . . . JT OR W PACKAGE  
SN74HC652 . . . DW OR NT PACKAGE  
(TOP VIEW)



SN54HC652 . . . FK PACKAGE  
(TOP VIEW)



NC – No internal connection



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

UNLESS OTHERWISE NOTED this document contains PRODUCTION DATA information current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

**TEXAS  
INSTRUMENTS**

POST OFFICE BOX 655303 • DALLAS, TEXAS 75265


Copyright © 1997, Texas Instruments Incorporated

# SN54HC652, SN74HC652

## OCTAL BUS TRANSCEIVERS AND REGISTERS

### WITH 3-STATE OUTPUTS

SCLS151B – DECEMBER 1982 – REVISED MAY 1997



Pin numbers shown are for the DW, JT, NT, and W packages.

**Figure 1. Bus-Management Functions**

# SN54HC652, SN74HC652

## OCTAL BUS TRANSCEIVERS AND REGISTERS

### WITH 3-STATE OUTPUTS

SCLS151B – DECEMBER 1982 – REVISED MAY 1997

FUNCTION TABLE


| INPUTS |      |        |        |     |     | DATA I/O†    |              | OPERATION OR FUNCTION                             |
|--------|------|--------|--------|-----|-----|--------------|--------------|---|
| OEAB   | OEBA | CLKAB  | CLKBA  | SAB | SBA | A1–A8        | B1–B8        |   |
| L      | H    | H or L | H or L | X   | X   | Input        | Input        | Isolation   |
| L      | H    | ↑      | ↑      | X   | X   | Input        | Input        | Store A and B data                                |
| X      | H    | ↑      | H or L | X   | X   | Input        | Unspecified‡ | Store A, hold B                                   |
| H      | H    | ↑      | ↑      | X‡  | X   | Input        | Output       | Store A in both registers                         |
| L      | X    | H or L | ↑      | X   | X   | Unspecified‡ | Input        | Hold A, store B                                   |
| L      | L    | ↑      | ↑      | X   | X‡  | Output       | Input        | Store B in both registers                         |
| L      | L    | X      | X      | X   | L   | Output       | Input        | Real-time B data to A bus                         |
| L      | L    | X      | H or L | X   | H   | Output       | Input        | Stored B data to A bus                            |
| H      | H    | X      | X      | L   | X   | Input        | Output       | Real-time A data to B bus                         |
| H      | H    | H or L | X      | H   | X   | Input        | Output       | Stored A data to B bus                            |
| H      | L    | H or L | H or L | H   | H   | Output       | Output       | Stored A data to B bus and stored B data to A bus |

† The data-output functions are enabled or disabled by a variety of level combinations at OEAB or OEBA. Data-input functions are always enabled; i.e., data at the bus terminals is stored on every low-to-high transition on the clock inputs.

‡ Select control = L; clocks can occur simultaneously.

Select control = H; clocks must be staggered to load both registers.

### logic symbols§



§ This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12. Pin numbers shown are for the DW, JT, NT, and W packages.


# SN54HC652, SN74HC652

## OCTAL BUS TRANSCEIVERS AND REGISTERS

### WITH 3-STATE OUTPUTS

SCLS151B – DECEMBER 1982 – REVISED MAY 1997

#### logic diagram (positive logic)



Pin numbers shown are for the DW, JT, NT, and W packages.

#### absolute maximum ratings over operating free-air temperature range†

|   |                |
|---|----------------|
| Supply voltage range, $V_{CC}$  | –0.5 V to 7 V  |
| Input clamp current, $I_{IK}$ ( $V_I < 0$ or $V_I > V_{CC}$ ) (see Note 1)  | ±20 mA         |
| Output clamp current, $I_{OK}$ ( $V_O < 0$ or $V_O > V_{CC}$ ) (see Note 1) | ±20 mA         |
| Continuous output current, $I_O$ ( $V_O = 0$ to $V_{CC}$ )                  | ±35 mA         |
| Continuous current through $V_{CC}$ or GND                                  | ±70 mA         |
| Package thermal impedance, $\theta_{JA}$ (see Note 2): DW package           | 81°C/W         |
| NT package  | 67°C/W         |
| Storage temperature range, $T_{stg}$  | –65°C to 150°C |

† Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTES: 1. The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

2. The package thermal impedance is calculated in accordance with JESD 51, except for through-hole packages, which use a trace length of zero.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

# SN54HC652, SN74HC652

## OCTAL BUS TRANSCEIVERS AND REGISTERS

### WITH 3-STATE OUTPUTS

SCLS151B – DECEMBER 1982 – REVISED MAY 1997

#### recommended operating conditions

|                 |                                       |                         | SN54HC652 |     |                 | SN74HC652 |     |                 | UNIT |
|-----------------|---------------------------------------|-------------------------|-----------|-----|-----------------|-----------|-----|-----------------|------|
|                 |                                       |                         | MIN       | NOM | MAX             | MIN       | NOM | MAX             |      |
| V <sub>CC</sub> | Supply voltage                        |                         | 2         | 5   | 6               | 2         | 5   | 6               | V    |
| V <sub>IH</sub> | High-level input voltage              | V <sub>CC</sub> = 2 V   | 1.5       |     |                 | 1.5       |     |                 | V    |
|                 |                                       | V <sub>CC</sub> = 4.5 V | 3.15      |     |                 | 3.15      |     |                 |      |
|                 |                                       | V <sub>CC</sub> = 6 V   | 4.2       |     |                 | 4.2       |     |                 |      |
| V <sub>IL</sub> | Low-level input voltage               | V <sub>CC</sub> = 2 V   | 0         |     | 0.5             | 0         |     | 0.5             | V    |
|                 |                                       | V <sub>CC</sub> = 4.5 V | 0         |     | 1.35            | 0         |     | 1.35            |      |
|                 |                                       | V <sub>CC</sub> = 6 V   | 0         |     | 1.8             | 0         |     | 1.8             |      |
| V <sub>I</sub>  | Input voltage                         |                         | 0         |     | V <sub>CC</sub> | 0         |     | V <sub>CC</sub> | V    |
| V <sub>O</sub>  | Output voltage                        |                         | 0         |     | V <sub>CC</sub> | 0         |     | V <sub>CC</sub> | V    |
| t <sub>t</sub>  | Input transition (rise and fall) time | V <sub>CC</sub> = 2 V   | 0         |     | 1000            | 0         |     | 1000            | ns   |
|                 |                                       | V <sub>CC</sub> = 4.5 V | 0         |     | 500             | 0         |     | 500             |      |
|                 |                                       | V <sub>CC</sub> = 6 V   | 0         |     | 400             | 0         |     | 400             |      |
| T <sub>A</sub>  | Operating free-air temperature        |                         | –55       |     | 125             | –40       |     | 85              | °C   |

#### electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER       |                | TEST CONDITIONS   | V <sub>CC</sub>          | T <sub>A</sub> = 25°C |       |       | SN54HC652 |     | SN74HC652 |     | UNIT |
|-----------------|----------------|---|--------------------------|-----------------------|-------|-------|-----------|-----|-----------|-----|------|
|                 |                |   |                          | MIN                   | TYP   | MAX   | MIN       | MAX | MIN       | MAX |      |
| V <sub>OH</sub> |                | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>       | I <sub>OH</sub> = –20 µA | 2 V                   | 1.9   | 1.998 | 1.9       |     | 1.9       |     | V    |
|                 |                |   |                          | 4.5 V                 | 4.4   | 4.499 | 4.4       |     | 4.4       |     |      |
|                 |                |   |                          | 6 V                   | 5.9   | 5.999 | 5.9       |     | 5.9       |     |      |
|                 |                | I <sub>OH</sub> = –6 mA                                   | 4.5 V                    | 3.98                  | 4.3   |       | 3.7       |     | 3.84      |     |      |
|                 |                |   | 6 V                      | 5.48                  | 5.8   |       | 5.2       |     | 5.34      |     |      |
| V <sub>OL</sub> |                | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>       | I <sub>OL</sub> = 20 µA  | 2 V                   | 0.002 | 0.1   | 0.1       |     | 0.1       |     | V    |
|                 |                |   |                          | 4.5 V                 | 0.001 | 0.1   | 0.1       |     | 0.1       |     |      |
|                 |                |   |                          | 6 V                   | 0.001 | 0.1   | 0.1       |     | 0.1       |     |      |
|                 |                | I <sub>OL</sub> = 6 mA                                    | 4.5 V                    | 0.17                  | 0.26  |       | 0.4       |     | 0.33      |     |      |
|                 |                |   | 6 V                      | 0.15                  | 0.26  |       | 0.4       |     | 0.33      |     |      |
| I <sub>I</sub>  | Control inputs | V <sub>I</sub> = V <sub>CC</sub> or 0                     | 6 V                      | ±0.1                  | ±100  |       | ±1000     |     | ±1000     |     | nA   |
| I <sub>OZ</sub> | A or B         | V <sub>O</sub> = V <sub>CC</sub> or GND                   | 6 V                      | ±0.01                 | ±0.5  |       | ±10       |     | ±5        |     | µA   |
| I <sub>CC</sub> |                | V <sub>I</sub> = V <sub>CC</sub> or 0, I <sub>O</sub> = 0 | 6 V                      |                       | 8     |       | 160       |     | 80        |     | µA   |
| C <sub>i</sub>  | Control inputs |   | 2 V to 6 V               |                       | 3     | 10    | 10        |     | 10        |     | pF   |

PRODUCT PREVIEW information concerns products in the formative or design phase of development. Characteristic data and other specifications are design goals. Texas Instruments reserves the right to change or discontinue these products without notice.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

# SN54HC652, SN74HC652

## OCTAL BUS TRANSCEIVERS AND REGISTERS

### WITH 3-STATE OUTPUTS

SCLS151B – DECEMBER 1982 – REVISED MAY 1997

**timing requirements over recommended operating free-air temperature range (unless otherwise noted)**

|   | $V_{CC}$ | $T_A = 25^\circ\text{C}$ |     | SN54HC652 |     | SN74HC652 |     | UNIT |
|---|----------|--------------------------|-----|-----------|-----|-----------|-----|------|
|   |          | MIN                      | MAX | MIN       | MAX | MIN       | MAX |      |
| $f_{\text{clock}}$ Clock frequency  | 2 V      | 0                        | 6   | 0         | 4.3 | 0         | 5.5 | MHz  |
|   | 4.5 V    | 0                        | 31  | 0         | 22  | 0         | 27  |      |
|   | 6 V      | 0                        | 36  | 0         | 25  | 0         | 31  |      |
| $t_w$ Pulse duration, CLKBA or CLKAB high or low                            | 2 V      | 80                       |     | 115       |     | 95        |     | ns   |
|   | 4.5 V    | 16                       |     | 23        |     | 19        |     |      |
|   | 6 V      | 14                       |     | 20        |     | 16        |     |      |
| $t_{su}$ Setup time, A before CLKAB $\uparrow$ or B before CLKBA $\uparrow$ | 2 V      | 100                      |     | 150       |     | 125       |     | ns   |
|   | 4.5 V    | 20                       |     | 30        |     | 25        |     |      |
|   | 6 V      | 17                       |     | 26        |     | 21        |     |      |
| $t_h$ Hold time, A after CLKAB $\uparrow$ or B after CLKBA $\uparrow$       | 2 V      | 5                        |     | 5         |     | 5         |     | ns   |
|   | 4.5 V    | 5                        |     | 5         |     | 5         |     |      |
|   | 6 V      | 5                        |     | 5         |     | 5         |     |      |

**switching characteristics over recommended operating free-air temperature range,  $C_L = 50$  pF (unless otherwise noted) (see Figure 2)**

| PARAMETER        | FROM (INPUT)                     | TO (OUTPUT) | $V_{CC}$ | $T_A = 25^\circ\text{C}$ |     |     | SN54HC652 |     | SN74HC652 |     | UNIT |
|------------------|----------------------------------|-------------|----------|--------------------------|-----|-----|-----------|-----|-----------|-----|------|
|                  |                                  |             |          | MIN                      | TYP | MAX | MIN       | MAX | MIN       | MAX |      |
| $f_{\text{max}}$ |                                  |             | 2 V      | 6                        | 10  |     | 4.3       |     | 5.5       |     | MHz  |
|                  |                                  |             | 4.5 V    | 31                       | 40  |     | 22        |     | 27        |     |      |
|                  |                                  |             | 6 V      | 36                       | 45  |     | 25        |     | 31        |     |      |
| $t_{pd}$         | CLKBA or CLKAB                   | A or B      | 2 V      |                          | 65  | 180 |           | 270 |           | 225 | ns   |
|                  |                                  |             | 4.5 V    |                          | 18  | 36  |           | 54  |           | 45  |      |
|                  |                                  |             | 6 V      |                          | 14  | 31  |           | 46  |           | 38  |      |
|                  | A or B                           | B or A      | 2 V      |                          | 50  | 135 |           | 205 |           | 170 |      |
|                  |                                  |             | 4.5 V    |                          | 14  | 27  |           | 41  |           | 34  |      |
|                  |                                  |             | 6 V      |                          | 11  | 23  |           | 35  |           | 29  |      |
|                  | SBA or SAB $\uparrow$            | A or B      | 2 V      |                          | 70  | 190 |           | 285 |           | 240 |      |
|                  |                                  |             | 4.5 V    |                          | 20  | 38  |           | 57  |           | 48  |      |
|                  |                                  |             | 6 V      |                          | 16  | 32  |           | 48  |           | 41  |      |
| $t_{en}$         | $\overline{\text{OEBA}}$ or OEAB | A or B      | 2 V      |                          | 85  | 245 |           | 370 |           | 305 | ns   |
|                  |                                  |             | 4.5 V    |                          | 25  | 49  |           | 74  |           | 61  |      |
|                  |                                  |             | 6 V      |                          | 20  | 42  |           | 63  |           | 52  |      |
| $t_{dis}$        | $\overline{\text{OEBA}}$ or OEAB | A or B      | 2 V      |                          | 50  | 245 |           | 370 |           | 305 | ns   |
|                  |                                  |             | 4.5 V    |                          | 23  | 49  |           | 74  |           | 61  |      |
|                  |                                  |             | 6 V      |                          | 20  | 42  |           | 63  |           | 52  |      |
| $t_t$            |                                  | Any         | 2 V      |                          | 28  | 60  |           | 90  |           | 75  | ns   |
|                  |                                  |             | 4.5 V    |                          | 8   | 12  |           | 18  |           | 15  |      |
|                  |                                  |             | 6 V      |                          | 6   | 10  |           | 15  |           | 13  |      |

$\uparrow$  These parameters are measured with the internal output state of the storage register opposite that of the bus input.

PRODUCT PREVIEW information concerns products in the formative or design phase of development. Characteristic data and other specifications are design goals. Texas Instruments reserves the right to change or discontinue these products without notice.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

# SN54HC652, SN74HC652 OCTAL BUS TRANSCEIVERS AND REGISTERS WITH 3-STATE OUTPUTS

SCLS151B – DECEMBER 1982 – REVISED MAY 1997

switching characteristics over recommended operating free-air temperature range,  $C_L = 150 \text{ pF}$   
(unless otherwise noted) (see Figure 2)

| PARAMETER | FROM<br>(INPUT)                  | TO<br>(OUTPUT) | $V_{CC}$ | $T_A = 25^\circ\text{C}$ |     |     | SN54HC652 |     | SN74HC652 |     | UNIT |
|-----------|----------------------------------|----------------|----------|--------------------------|-----|-----|-----------|-----|-----------|-----|------|
|           |                                  |                |          | MIN                      | TYP | MAX | MIN       | MAX | MIN       | MAX |      |
| $t_{pd}$  | CLKBA or CLKAB                   | A or B         | 2 V      |                          | 90  | 265 |           | 400 |           | 330 | ns   |
|           |                                  |                | 4.5 V    |                          | 24  | 53  |           | 80  |           | 66  |      |
|           |                                  |                | 6 V      |                          | 18  | 46  |           | 68  |           | 57  |      |
|           | A or B                           | B or A         | 2 V      |                          | 70  | 220 |           | 335 |           | 275 |      |
|           |                                  |                | 4.5 V    |                          | 20  | 44  |           | 70  |           | 55  |      |
|           |                                  |                | 6 V      |                          | 15  | 38  |           | 57  |           | 48  |      |
|           | SBA or SAB <sup>†</sup>          | A or B         | 2 V      |                          | 80  | 275 |           | 415 |           | 345 |      |
|           |                                  |                | 4.5 V    |                          | 24  | 55  |           | 83  |           | 69  |      |
|           |                                  |                | 6 V      |                          | 20  | 47  |           | 70  |           | 60  |      |
| $t_{en}$  | $\overline{\text{OEBA}}$ or OEAB | A or B         | 2 V      |                          | 100 | 330 |           | 500 |           | 410 | ns   |
|           |                                  |                | 4.5 V    |                          | 33  | 66  |           | 100 |           | 82  |      |
|           |                                  |                | 6 V      |                          | 27  | 57  |           | 85  |           | 71  |      |
| $t_t$     |                                  | Any            | 2 V      |                          | 45  | 210 |           | 315 |           | 265 | ns   |
|           |                                  |                | 4.5 V    |                          | 17  | 42  |           | 63  |           | 53  |      |
|           |                                  |                | 6 V      |                          | 13  | 36  |           | 53  |           | 43  |      |

<sup>†</sup> These parameters are measured with the internal output state of the storage register opposite that of the bus input.

## operating characteristics, $T_A = 25^\circ\text{C}$

| PARAMETER |                               | TEST CONDITIONS | TYP | UNIT |
|-----------|-------------------------------|-----------------|-----|------|
| $C_{pd}$  | Power dissipation capacitance | No load         | 50  | pF   |

PRODUCT PREVIEW information concerns products in the formative or design phase of development. Characteristic data and other specifications are design goals. Texas Instruments reserves the right to change or discontinue these products without notice.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265


# SN54HC652, SN74HC652

## OCTAL BUS TRANSCEIVERS AND REGISTERS





### WITH 3-STATE OUTPUTS

SCLS151B – DECEMBER 1982 – REVISED MAY 1997

#### PARAMETER MEASUREMENT INFORMATION



| PARAMETER         | $R_L$        | $C_L$           | S1     | S2     |
|-------------------|--------------|-----------------|--------|--------|
| $t_{en}$          | 1 k $\Omega$ | 50 pF or 150 pF | Open   | Closed |
|                   |              |                 | Closed | Open   |
| $t_{dis}$         | 1 k $\Omega$ | 50 pF           | Open   | Closed |
|                   |              |                 | Closed | Open   |
| $t_{pd}$ or $t_t$ | —            | 50 pF or 150 pF | Open   | Open   |



- NOTES:
- $C_L$  includes probe and test-fixture capacitance.
  - Waveform 1 is for an output with internal conditions such that the output is low except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high except when disabled by the output control.
  - Phase relationships between waveforms were chosen arbitrarily. All input pulses are supplied by generators having the following characteristics:  $PRR \leq 1$  MHz,  $Z_O = 50 \Omega$ ,  $t_r = 6$  ns,  $t_f = 6$  ns.
  - For clock inputs,  $f_{max}$  is measured when the input duty cycle is 50%.
  - The outputs are measured one at a time with one input transition per measurement.
  - $t_{PLZ}$  and  $t_{PHZ}$  are the same as  $t_{dis}$ .
  - $t_{PZL}$  and  $t_{PZH}$  are the same as  $t_{en}$ .
  - $t_{PLH}$  and  $t_{PHL}$  are the same as  $t_{pd}$ .

Figure 2. Load Circuit and Voltage Waveforms



## **IMPORTANT NOTICE**

Texas Instruments and its subsidiaries (TI) reserve the right to make changes to their products or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgement, including those pertaining to warranty, patent infringement, and limitation of liability.

TI warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

CERTAIN APPLICATIONS USING SEMICONDUCTOR PRODUCTS MAY INVOLVE POTENTIAL RISKS OF DEATH, PERSONAL INJURY, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE ("CRITICAL APPLICATIONS"). TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS. INCLUSION OF TI PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE FULLY AT THE CUSTOMER'S RISK.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards must be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance or customer product design. TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used. TI's publication of information regarding any third party's products or services does not constitute TI's approval, warranty or endorsement thereof.