

74LCX240

Low Voltage Octal Buffer/Line Driver with 5V Tolerant Inputs and Outputs

General Description

The LCX240 is an inverting octal buffer and line driver designed to be employed as a memory address driver, clock driver and bus oriented transmitter or receiver. The device is designed for low voltage (2.5V or 3.3V) V_{CC} applications with capability of interfacing to a 5V signal environment.

The LCX240 is fabricated with an advanced CMOS technology to achieve high speed operation while maintaining CMOS low power dissipation.

Features

- 5V tolerant inputs and outputs
- 2.3V–3.6V V_{CC} specifications provided
- 6.5 ns t_{PD} max ($V_{CC} = 3.3V$), 10 μA I_{CC} max
- Power-down high impedance inputs and outputs
- Supports live insertion/withdrawal (Note 1)
- ± 24 mA output drive ($V_{CC} = 3.0V$)
- Implements patented noise/EMI reduction circuitry
- Latch-up performance exceeds 500 mA
- ESD performance:
 - Human body model > 2000V
 - Machine model > 200V


Note 1: To ensure the high-impedance state during power up or down, $\overline{OE}$ should be tied to V_{CC} through a pull-up resistor: the minimum value or the resistor is determined by the current-sourcing capability of the driver.

Ordering Code:


Order Number	Package Number	Package Description
74LCX240WM	M20B	20-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300" Wide
74LCX240SJ	M20D	20-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide
74LCX240MSA	MSA20	20-Lead Shrink Small Outline Package (SSOP), EIAJ TYPE II, 5.3mm Wide
74LCX240MTC	MTC20	20-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide

Devices also available in Tape and Reel. Specify by appending the suffix letter "X" to the ordering code.

Logic Diagram



Connection Diagram



Pin Descriptions

Pin Names	Description
$\overline{OE}_1, \overline{OE}_2$	3-STATE Output Enable Inputs
I_0-I_7	Inputs
$\overline{O}_0-\overline{O}_7$	Outputs

Truth Tables

Inputs		Outputs
$\overline{OE}_1$	I_n	(Pins 12, 14, 16, 18)
L	L	H
L	H	L
H	X	Z

Inputs		Outputs
$\overline{OE}_2$	I_n	(Pins 3, 5, 7, 9)
L	L	H
L	H	L
H	X	Z

H = HIGH Voltage Level
 L = LOW Voltage Level
 X = Immaterial
 Z = High Impedance

Absolute Maximum Ratings ^(Note 2)				
Symbol	Parameter	Value	Conditions	Units
V _{CC}	Supply Voltage	−0.5 to +7.0		V
V _I	DC Input Voltage	−0.5 to +7.0		V
V _O	DC Output Voltage	−0.5 to +7.0	Output in 3-STATE	V
		−0.5 to V _{CC} + 0.5	Output in HIGH or LOW State (Note 3)	V
I _{IK}	DC Input Diode Current	−50	V _I < GND	mA
I _{OK}	DC Output Diode Current	−50	V _O < GND	mA
		+50	V _O > V _{CC}	
I _O	DC Output Source/Sink Current	±50		mA
I _{CC}	DC Supply Current per Supply Pin	±100		mA
I _{GND}	DC Ground Current per Ground Pin	±100		mA
T _{STG}	Storage Temperature	−65 to +150		°C

Recommended Operating Conditions ^(Note 4)

Symbol	Parameter	Min	Max	Units	
V _{CC}	Supply Voltage	Operating	2.0	3.6	V
		Data Retention	1.5	3.6	
V _I	Input Voltage	0	5.5	V	
V _O	Output Voltage	HIGH or LOW State	0	V _{CC}	V
		3-STATE	0	5.5	
I _{OH} /I _{OL}	Output Current	V _{CC} = 3.0V – 3.6V V _{CC} = 2.7V – 3.0V V _{CC} = 2.3V – 2.7V		±24 ±12 ±8	mA
T _A	Free-Air Operating Temperature	−40	85	°C	
Δt/ΔV	Input Edge Rate, V _{IN} = 0.8V–2.0V, V _{CC} = 3.0V	0	10	ns/V	

Note 2: The Absolute Maximum Ratings are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the Electrical Characteristics tables are not guaranteed at the Absolute Maximum Ratings. The “Recommended Operating Conditions” table will define the conditions for actual device operation.

Note 3: I_O Absolute Maximum Rating must be observed.

Note 4: Unused inputs must be held HIGH or LOW. They may not float.

DC Electrical Characteristics

Symbol	Parameter	Conditions	V _{CC} (V)	T _A = −40°C to +85°C		Units
				Min	Max	
V _{IH}	HIGH Level Input Voltage		2.3 – 2.7	1.7		V
			2.7 – 3.6	2.0		
V _{IL}	LOW Level Input Voltage		2.3 – 2.7		0.7	V
			2.7 – 3.6		0.8	
V _{OH}	HIGH Level Output Voltage	I _{OH} = −100μA	2.3 – 3.6	V _{CC} - 0.2		V
		I _{OH} = -8 mA	2.3	1.8		
		I _{OH} = −12 mA	2.7	2.2		
		I _{OH} = −18 mA	3.0	2.4		
		I _{OH} = −24 mA	3.0	2.2		
V _{OL}	LOW Level Output Voltage	I _{OL} = 100μA	2.3 – 3.6		0.2	V
		I _{OL} = 8mA	2.3		0.6	
		I _{OL} = 12 mA	2.7		0.4	
		I _{OL} = 16 mA	3.0		0.4	
		I _{OL} = 24 mA	3.0		0.55	
I _I	Input Leakage Current	0 ≤ V _I ≤ 5.5V	2.3 – 3.6		±5.0	μA
I _{OFF}	Power-Off Leakage Current	V _I or V _O = 5.5V			10	μA
I _{CC}	Quiescent Supply Current	V _I = V _{CC} or GND	2.3 – 3.6		10	μA
		3.6V ≤ V _I , V _O ≤ 5.5V (Note 5)	2.3 – 3.6		±10	
ΔI _{CC}	Increase in I _{CC} per Input	V _{IH} = V _{CC} = 0.6V	2.3 – 3.6		500	μA

DC Electrical Characteristics (Continued)

Note 5: Outputs disabled or 3-STATE only.

AC Electrical Characteristics

Symbol	Parameter	T _A = −40°C to +85°C, R _L = 500Ω						Units
		V _{CC} = 3.3V ± 0.3V		V _{CC} = 2.7V		V _{CC} = 2.5V ± 0.2V		
		C _L = 50 pF		C _L = 50 pF		C _L = 30 pF		
		Min	Max	Min	Max	Min	Max	
t _{PHL} t _{PLH}	Propagation Delay	1.5	6.5	1.5	7.5	1.5	7.8	ns
t _{PZL} t _{PZH}	Output Enable Time	1.5	8.0	1.5	9.0	1.5	10.0	ns
t _{PLZ} t _{PHZ}	Output Disable Time	1.5	7.0	1.5	8.0	1.5	8.4	ns
t _{OSHL} t _{OSLH}	Output to Output Skew (Note 6)		1.0					ns

Note 6: Skew is defined as the absolute value of the difference between the actual propagation delay for any two separate outputs of the same device. The specification applies to any outputs switching in the same direction, either HIGH-to-LOW (t_{OSHL}) or LOW-to-HIGH (t_{OSLH}).

Dynamic Switching Characteristics

Symbol	Parameter	Conditions	V_{CC} (V)	$T_A = 25^\circ\text{C}$	Units
				Typical	
V_{OLP}	Quiet Output Dynamic Peak V_{OL}	$C_L = 50\text{ pF}, V_{IH} = 3.3V, V_{IL} = 0V$ $C_L = 30\text{ pF}, V_{IH} = 2.5V, V_{IL} = 0V$	3.3 2.5	0.8 0.6	V
V_{OLV}	Quiet Output Dynamic Valley V_{OL}	$C_L = 50\text{ pF}, V_{IH} = 3.3V, V_{IL} = 0V$ $C_L = 30\text{ pF}, V_{IH} = 2.5V, V_{IL} = 0V$	3.3 2.5	-0.8 -0.6	V

Capacitance

Symbol	Parameter	Conditions	Typical	Units
C_{IN}	Input Capacitance	$V_{CC} = \text{Open}, V_I = 0V \text{ or } V_{CC}$	7	pF
C_{OUT}	Output Capacitance	$V_{CC} = 3.3V, V_I = 0V \text{ or } V_{CC}$	8	pF
C_{PD}	Power Dissipation Capacitance	$V_{CC} = 3.3V, V_I = 0V \text{ or } V_{CC}, f = 10\text{ MHz}$	25	pF

AC Loading and Waveforms

Generic for LCX Family






FIGURE 1. AC Test Circuit
(C_L includes probe and jig capacitance)


Test	Switch
t_{PLH}, t_{PHL}	Open
t_{PZL}, t_{PLZ}	6V at $V_{CC} = 3.3 \pm 0.3V$ $V_{CC} \times 2$ at $V_{CC} = 2.5 \pm 0.2V$
t_{PZH}, t_{PHZ}	GND




Waveform for Inverting and Non-Inverting Functions




Propagation Delay, Pulse Width and t_{rec} Waveforms



3-STATE Output High Enable and Disable Times for Logic



3-STATE Output Low Enable and Disable Times for Logic



Setup Time, Hold Time and Recovery Time for Logic






FIGURE 2. Waveforms

(Input Pulse Characteristics; $f = 1\text{MHz}$, $t_r = t_f = 3\text{ns}$)


Symbol	V_{CC}		
	$3.3V \pm 0.3V$	$2.7V$	$2.5V \pm 0.2V$
V_{mi}	$1.5V$	$1.5V$	$V_{CC}/2$
V_{mo}	$1.5V$	$1.5V$	$V_{CC}/2$
V_X	$V_{OL} + 0.3V$	$V_{OL} + 0.3V$	$V_{OL} + 0.15V$
V_Y	$V_{OH} - 0.3V$	$V_{OH} - 0.3V$	$V_{OH} - 0.15V$

Schematic Diagram Generic for LCX Family



Physical Dimensions inches (millimeters) unless otherwise noted


20-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300" Wide
Package Number M20B



Technical drawing of a 1/2" 11.5° 2-Flute End Mill. The drawing shows two views: a side view and a top view. The side view shows a length of 2.1 MAX. and a diameter of 1.27 TYP. The top view shows a diameter of 1.8 ± 0.1 and a width of 0.35-0.51. The drawing includes a table of material specifications and a table of material specifications.

Material	Grade	Hardness	Material	Grade	Hardness
Aluminum	6061-T6	15-20 HRC	Aluminum	7075-T6	20-25 HRC
Aluminum	2024-T3	15-20 HRC	Aluminum	5052-H32	15-20 HRC
Aluminum	6063-T5	15-20 HRC	Aluminum	3003-H14	15-20 HRC
Aluminum	6061-T6	15-20 HRC	Aluminum	7075-T6	20-25 HRC
Aluminum	2024-T3	15-20 HRC	Aluminum	5052-H32	15-20 HRC
Aluminum	6063-T5	15-20 HRC	Aluminum	3003-H14	15-20 HRC
Aluminum	6061-T6	15-20 HRC	Aluminum	7075-T6	20-25 HRC
Aluminum	2024-T3	15-20 HRC	Aluminum	5052-H32	15-20 HRC
Aluminum	6063-T5	15-20 HRC	Aluminum	3003-H14	15-20 HRC
Aluminum	6061-T6	15-20 HRC	Aluminum	7075-T6	20-25 HRC
Aluminum	2024-T3	15-20 HRC	Aluminum	5052-H32	15-20 HRC
Aluminum	6063-T5	15-20 HRC	Aluminum	3003-H14	15-20 HRC
Aluminum	6061-T6	15-20 HRC	Aluminum	7075-T6	20-25 HRC
Aluminum	2024-T3	15-20 HRC	Aluminum	5052-H32	15-20 HRC
Aluminum	6063-T5	15-20 HRC	Aluminum	3003-H14	15-20 HRC
Aluminum	6061-T6	15-20 HRC	Aluminum	7075-T6	20-25 HRC
Aluminum	2024-T3	15-20 HRC	Aluminum	5052-H32	15-20 HRC
Aluminum	6063-T5	15-20 HRC	Aluminum	3003-H14	15-20 HRC
Aluminum	6061-T6	15-20 HRC	Aluminum	7075-T6	20-25 HRC
Aluminum	2024-T3	15-20 HRC	Aluminum	5052-H32	15-20 HRC
Aluminum	6063-T5	15-20 HRC	Aluminum	3003-H14	15-20 HRC
Aluminum	6061-T6	15-20 HRC	Aluminum	7075-T6	20-25 HRC
Aluminum	2024-T3	15-20 HRC	Aluminum	5052-H32	15-20 HRC
Aluminum	6063-T5	15-20 HRC	Aluminum	3003-H14	15-20 HRC
Aluminum	6061-T6	15-20 HRC	Aluminum	7075-T6	20-25 HRC
Aluminum	2024-T3	15-20 HRC	Aluminum	5052-H32	15-20 HRC
Aluminum	6063-T5	15-20 HRC	Aluminum	3003-H14	15-20 HRC
Aluminum	6061-T6	15-20 HRC	Aluminum	7075-T6	20-25 HRC
Aluminum	2024-T3	15-20 HRC	Aluminum	5052-H32	15-20 HRC
Aluminum	6063-T5	15-20 HRC	Aluminum	3003-H14	15-20 HRC
Aluminum	6061-T6	15-20 HRC	Aluminum	7075-T6	20-25 HRC
Aluminum	2024-T3	15-20 HRC	Aluminum	5052-H32	15-20 HRC
Aluminum	6063-T5	15-20 HRC	Aluminum	3003-H14	15-20 HRC
Aluminum	6061-T6	15-20 HRC	Aluminum	7075-T6	20-25 HRC
Aluminum	2024-T3	15-20 HRC	Aluminum	5052-H32	15-20 HRC
Aluminum	6063-T5	15-20 HRC	Aluminum	3003-H14	15-20 HRC
Aluminum	6061-T6	15-20 HRC	Aluminum	7075-T6	20-25 HRC
Aluminum	2024-T3	15-20 HRC	Aluminum	5052-H32	15-20 HRC
Aluminum	6063-T5	15-20 HRC	Aluminum	3003-H14	15-20 HRC
Aluminum	6061-T6	15-20 HRC	Aluminum	7075-T6	20-25 HRC
Aluminum	2024-T3	15-20 HRC	Aluminum	5052-H32	15-20 HRC
Aluminum	6063-T5	15-20 HRC	Aluminum	3003-H14	15-20 HRC
Aluminum	6061-T6	15-20 HRC	Aluminum	7075-T6	20-25 HRC
Aluminum	2024-T3	15-20 HRC	Aluminum	5052-H32	15-20 HRC
Aluminum	6063-T5	15-20 HRC	Aluminum	3003-H14	15-20 HRC
Aluminum	6061-T6	15-20 HRC	Aluminum	7075-T6	20-25 HRC
Aluminum	2024-T3	15-20 HRC	Aluminum	5052-H32	15-20 HRC
Aluminum	6063-T5	15-20 HRC	Aluminum	3003-H14	15-20 HRC
Aluminum	6061-T6	15-20 HRC	Aluminum	7075-T6	20-25 HRC
Aluminum	2024-T3	15-20 HRC	Aluminum	5052-H32	15-20 HRC
Aluminum	6063-T5	15-20 HRC	Aluminum	3003-H14	15-20 HRC
Aluminum	6061-T6	15-20 HRC	Aluminum		

A. CONFORMS TO EIAJ EDR-7320 REGISTRATION, ESTABLISHED IN DECEMBER, 1998.


B. DIMENSIONS ARE IN MILLIMETERS.

C. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.



Technical drawing of a mechanical part with the following dimensions and labels:

- Top surface taper: 7° TYP
- Bottom surface taper: 0°-8° TYP
- Dimension 1: 0.60 ± 0.15
- Dimension 2: 1.25
- Dimension 3: 0.25
- Labels: GAGE PLANE, SEATING PLANE

**20-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide
Package Number M20D**

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)


20-Lead Shrink Small Outline Package (SSOP), EIAJ TYPE II, 5.3mm Wide
Package Number MSA20


Physical Dimensions inches (millimeters) unless otherwise noted (Continued)

DIMENSIONS ARE IN MILLIMETERS

NOTES:

- A. CONFORMS TO JEDEC REGISTRATION MO-153, VARIATION AC, REF NOTE 6, DATE 7/93.
- B. DIMENSIONS ARE IN MILLIMETERS.
- C. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.
- D. DIMENSIONS AND TOLERANCES PER ANSI Y14.5M, 1982.

MTC20RevD1



**20-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide
Package Number MTC20**

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
 2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.
- www.fairchildsemi.com**

www.fairchildsemi.com