

FS6M07652RTC

Fairchild Power Switch(FPS)

Features


- Fixed frequency
- Internal Burst mode Controller for Stand-by mode
- Pulse by pulse over current limiting
- Over current protection(Auto restart mode)
- Over voltage protection (Auto restart mode)
- Over load protection(Auto restart mode)
- Internal thermal shutdown function(Latch mode)
- Under voltage lockout
- Internal high voltage sense FET
- Soft start

Description

The Fairchild Power Switch(FPS) product family is specially designed for an off line SMPS with minimal external components. The Fairchild Power Switch(FPS) consist of high voltage power SenseFET and current mode PWM IC. Included PWM controller features integrated fixed oscillator, under voltage lock out, leading edge blanking, optimized gate turn-on/turn-off driver, thermal shut down protection, over voltage protection, and temperature compensated precision current sources for loop compensation and fault protection circuitry. compared to discrete MOSFET and controller or RCC switching converter solution, a Fairchild Power Switch(FPS) can reduce total component count, design size, and weight and at the same time increase efficiency, productivity, and system reliability. It has a basic platform well suited for cost effective LCD monitor power supply.



Internal Block Diagram



Rev.1.0.2

Absolute Maximum Ratings

(Ta=25°C, unless otherwise specified)

Characteristic	Symbol	Value	Unit
Drain to PKG Breakdown Voltage	V _{BV} , PKG	3500	V
Maximum Drain Voltage	V _D , MAX	650	V
Drain-Gate Voltage (R _{GS} =1MΩ)	V _{DGR}	650	V
Gate-Source (GND) Voltage	V _G S	±30	V
Drain Current Pulsed ⁽¹⁾	I _{DM}	14.4	ADC
Continuous Drain Current (T _c = 25°C)	I _D	3.6	ADC
Continuous Drain Current (T _C =100°C)	I _D	2.28	ADC
Single Pulsed Avalanche Current ⁽³⁾ (Energy ⁽²⁾)	I _{AS(EAS)}	17(570)	A(mJ)
Maximum Supply Voltage	V _{CC} , MAX	35	V
Input Voltage Range	V _{FB}	-0.3 to V _{CC}	V
	V _{SS}	-0.3 to 10	V
Total Power Dissipation	P _D (Watt H/S)	46	W
	Derating	0.37	W/°C
Operating Junction Temperature	T _j	+150	°C
Operating Ambient Temperature	T _A	-25 to +85	°C
Storage Temperature Range	T _{STG}	-55 to +150	°C

Notes:

1. Repetitive rating: Pulse width limited by maximum junction temperature
2. L=81mH, starting T_j=25°C
3. L=13uH, starting T_j=25°C

Electrical Characteristics (SFET part)

(Ta=25°C unless otherwise specified)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Drain-Source Breakdown Voltage	BVDSS	VGS=0V, ID=250µA	650	-	-	V
Zero Gate Voltage Drain Current	IDSS	VDS=650V, VGS=0V	-	-	200	µA
		VDS=520V VGS=0V, TC=125°C	-	-	300	µA
Static Drain-source On Resistance ⁽¹⁾	RDS(ON)	VGS=10V, ID=1.8A	-	1.3	1.6	Ω
Forward transconductance ⁽²⁾	gfs	VDS=50V, ID=1.8A	-	3.3	-	S
Input capacitance	Ciss	VGS=0V, VDS=25V, f = 1MHz	-	1200	1560	pF
Output capacitance	Coss		-	125	160	
Reverse transfer capacitance	Crss		-	23	30	
Turn on delay time	td(on)	VDD=325V, ID=6.5A (MOSFET switching time are essentially independent of operating temperature)	-	22	55	nS
Rise time	tr		-	70	150	
Turn off delay time	td(off)		-	105	220	
Fall time	tf		-	65	140	
Total gate charge (gate-source+gate-drain)	Qg	VGS=10V, ID=6.5A, VDS=520V (MOSFET Switching time are Essentially independent of Operating temperature)	-	40	52	nC
Gate source charge	Qgs		-	6.5	-	
Gate drain (Miller) charge	Qgd		-	18	-	

Note:

1. Pulse test : Pulse width ≤ 300µS, duty 2%

$$2. S = \frac{1}{R}$$

Electrical Characteristics

(Ta=25°C unless otherwise specified)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
UVLO SECTION						
Start Threshold Voltage	VSTART	VFB = GND	14	15	16	V
Stop Threshold Voltage	VSTOP	VFB = GND	8	9	10	V
OSCILLATOR SECTION						
Initial Frequency	FOSC	-	63	70	77	kHz
Voltage Stability	FSTABLE	12V ≤ VCC ≤ 23V	0	1	3	%
Temperature Stability (2)	ΔFOSC	-25°C ≤ Ta ≤ 85°C	0	±5	±10	%
Maximum Duty Cycle	DMAX	-	75	80	85	%
Minimum Duty Cycle	DMIN	-	-	-	0	%
FEEDBACK SECTION						
Feedback Source Current	I _{FB}	VFB = GND	0.7	0.9	1.1	mA
Shutdown Feedback Voltage	V _{SD}	VFB ≥ 6.9V	6.9	7.5	8.1	V
Shutdown Delay Current	I _{DELAY}	VFB = 5V	3.2	4.0	4.8	μA
SOFTSTART SECTION						
Softstart Vortage	V _{SS}	VFB = 2	4.7	5.0	5.3	V
Softstart Current	I _{SS}	V _{SS} = V	0.8	1.0	1.2	mA
BURST MODE SECTION						
Burst Mode Low Threshold Voltage	V _{BURL}	VFB = 0V	10.4	11.0	11.6	V
Burst Mode High Threshold Voltage	V _{BURH}	VFB = 0V	11.4	12.0	12.6	V
Burst Mode Enable Feedback Voltage	V _{BEN}	VCC = 10.5V	0.7	1.0	1.3	V
Burst Mode Peak Current Limit (4)	I _{BURPK}	VCC = 10.5V, VFB = 0V	0.38	0.5	0.62	V
Burst Mode Frequency	F _{BUR}	VCC = 10.5V, VFB = 0V	63	70	77	KHz
CURRENT LIMIT(SELF-PROTECTION)SECTION						
Peak Current Limit (4)	I _{OVER}	-	1.76	2.0	2.24	A
PROTECTION SECTION						
Over Voltage Protection	V _{OVP}	VCC ≥ 29V	29	33	37	V
Over Current Latch Voltage (3)	V _{OCL}	-	1.8	2.0	2.2	V
Thermal Shutdown Temp (2)	T _{SD}	-	140	160	-	°C
TOTAL DEVICE SECTION						
Start Up Current	I _{START}	VFB = GND, VCC = 14V	-	0.1	0.17	mA
Operating Supply Current (1)	I _{OP}	VFB = GND, VCC = 16V	-	10	15	mA
	I _{OP(MIN)}	VFB = GND, VCC = 12V				
	I _{OP(MAX)}	VFB = GND, VCC = 30V				

Notes:

- These parameters is the current flowing in the Control IC.
- These parameters, although guranteed at the design, are not 100% tested in production.
- These parameters, although guaranteed, are tested in EDS(wafer test) process.
- These parameters indicate Inductor current.

Typical Performance Characteristics




Figure 1. Start Up Current vs. Temp




Figure 2. Operating Current vs. Temp




Figure 3. Start Threshold Voltage vs. Temp




Figure 4. Stop Threshold Voltage vs. Temp




Figure 5. Initial Frequency vs. Temp




Figure 6. Maximum Duty vs. Temp

Typical Performance Characteristics (Continued)




Figure 7. Feedback Offset Voltage vs. Temp




Figure 8. Feedback Source Current vs. Temp




Figure 9. ShutDown Delay Current vs. Temp




Figure 10 . ShutDown Feedback Voltage vs. Temp




Figure 11 . Softstart Voltage vs. Temp




Figure 12 . Over Voltage Protection vs. Temp

Typical Performance Characteristics (Continued)




Figure 13 . Burst Mode Low Voltage vs. Temp




Figure 14 . Burst Mode High Voltage vs. Temp




Figure 15 . Burst Mode Peak Current vs. Temp





Figure 16 . Over Current Limit vs. Temp


Package Dimensions

TO-220F-5L



Package Dimensions (Continued)

TO-220F-5L(Forming)



Ordering Information

Product Number	Package	Marking Code	BVdss	Rds(on)
FS6M07652RTC-TU	TO-220F-5L	6M07652R	650V	1.3
FS6M07652RTC-YDT	TO-220F-5L(Forming)	C		

TU : Non Forming Type

YDT : Forming Type

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
- 2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.