


ELECTRICAL SPECIFICATIONS

FREQUENCY RANGE (GHz): 1.700-2.200
 IMPEDANCE (NOMINAL): 50 OHMS
 VSWR: INPUT: 1.15:1 TYPICAL/1.20:1 MAX
 OUTPUT: 1.10:1 TYPICAL/1.15:1 MAX
 INSERTION LOSS (dB): 0.35 TYPICAL/0.40 MAX
 AMPLITUDE BALANCE (MAX): 0.2 dB
 PHASE BALANCE (MAX): 3 DEGREES
 ISOLATION (dB): 35 TYPICAL/30 MIN
 RF POWER (TOTAL MAX): 10 WATTS INPUT WITH LOAD
 VSWR 1.2:1 OR BETTER

MECHANICAL SPECIFICATIONS

*CONNECTORS: N-FEMALE, BRASS, NICKEL PLATE
 CONNECTOR PINS: BERYLLIUM COPPER, GOLD PLATE
 HOUSING: ALUMINUM, YELLOW IRIDITE
 INSULATORS: TEFLON®, VIRGIN ELECTRICAL GRADE
 TEMPERATURE: -55°C TO +70°C

*CONNECTORS MEET MATING CHARACTERISTICS OF MIL-STD-348A



A	REDRAWN	10/03/00	MJD	MATERIAL: SEE ABOVE		UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES		 ELECTRONICS, INC. DENVER, NEW JERSEY e-meca.com	
				FINISH: SEE ABOVE		TOLERANCES 2 PLACES: ± .02 3 PLACES: ± .010 ANGLES: ± ---			
				DRAWN: LB	DATE: 10/03/00	TIR:		TITLE 3-WAY, IN-PHASE (0 DEGREE), POWER DIVIDER/COMBINER, N-FEMALE	
				APPROVED: MJD	DATE: 10/03/00	SCALE: NTS	SIZE A		
LTR	DESCRIPTION	DATE	APP			SHEET: 1 OF 3			CODE IDENT. NO. 22424