



ELECTRICAL SPECIFICATIONS

FREQUENCY RANGE (GHz): 5.600-6.600
 IMPEDANCE (NOMINAL): 50 OHMS
 VSWR: INPUT: 1.15:1 TYPICAL/1.20:1 MAX
 OUTPUT: 1.10:1 TYPICAL/1.15:1 MAX
 INSERTION LOSS (dB): 0.6 TYPICAL/0.7 MAX
 AMPLITUDE BALANCE (MAX): 0.2 dB
 ISOLATION (dB): 30 TYPICAL/25 MIN
 PHASE BALANCE (MAX): 4 DEGREES
 RF POWER (TOTAL MAX): 10 WATTS INPUT WITH LOAD
 VSWR 1.2:1 OR BETTER

MECHANICAL SPECIFICATIONS

*CONNECTORS: SMA-FEMALE, STAINLESS STEEL, PASSIVATE
 CONNECTOR PINS: BERYLLIUM COPPER, GOLD PLATE
 HOUSING: ALUMINUM, YELLOW IRIDITE
 INSULATORS: TEFLON[®], VIRGIN ELECTRICAL GRADE
 TEMPERATURE: -55°C TO +70°C

*CONNECTORS MEET MATING CHARACTERISTICS OF MIL-STD-348A



A	REDRAWN	10/06/00	MJD	MATERIAL:		UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES		 ELECTRONICS, INC. DENVER, NEW JERSEY e-meca.com	
				SEE ABOVE					
				FINISH:		TOLERANCES			
				SEE ABOVE		2 PLACES: ± .02 3 PLACES: ± .010 ANGLES: ± ---			
LTR	DESCRIPTION	DATE	APP	DRAWN:	DATE:	TIR:		TITLE 4-WAY, IN-PHASE (0 DEGREE), POWER DIVIDER/COMBINER, SMA-FEMALE	
				LB	10/06/00				
				APPROVED:	DATE:	SCALE: 1 : 0.8	SIZE A	CODE IDENT. NO. 22424	DRAWING NO. 804-2-6.100
				MJD	10/06/00	SHEET: 1 OF 3			