

10/100BASE-TX LAN MAGNETICS

belMag™ Integrated Modules with Status Indicators

bel

LM00401


- Shielded connector with integrated 10/100 magnetics
- Reduced pin count for improved crosstalk and optimum PCB trace routing
- Complies with IEEE standards and all 10/100 Ethernet specifications
- Operating temperature 0° to 70° C
- Embedded system status indicators (LEDs)
- Adaptable, modular design provides higher reliability
- Integrated design conserves valuable board space
- Compatible with a variety of 10/100 transceiver ICs
- Minimum interwinding breakdown voltage of 1500 Vrms

ELECTRICAL SPECIFICATIONS AT 25° C


Part Number	Insertion Loss dB max	Return Loss dB min			Common to Differential Mode Rejection dB min	Common to Common Mode Rejection dB min	Crosstalk dB min			
	1MHz to 100MHz	1MHz to 30MHz	30MHz to 60MHz	60MHz to 80MHz	100kHz to 100MHz		1MHz	30MHz	60MHz	100MHz
0810-1XX1-01	-1.0	-18	18 - 20 log (f/30MHz)	-12	40	30	-65	-45	-37	-35
0810-1XX1-02	-1.0	-18	18 - 20 log (f/30MHz)	-12	40	30	-65	-45	-37	-35
0810-1XX1-03	-1.0	-18	18 - 20 log (f/30MHz)	-12	40	30	-65	-45	-37	-35

SCHEMATICS

0810-1XX1-01
0810-1XX1-02





0810-1XX1-03




©2000 Bel Fuse Inc. Specifications subject to change without notice. 01.00

MECHANICAL

0810-1XX1-01
0810-1XX1-02
0810-1XX1-03



Suggested PCB Pad Layout



Notes

Plastic Housing	Thermoplastic PBT Flammability rating UL 94V-0
Contacts	50 micro-inch hard gold plating with underplating of 50 micro-inch nickel
Pins	Tin-coated copper wire, dia. 0.018 inch
Solderability	Per MIL Std. 202, method 208
Metal Shield	Pre-tinned phosphor bronze, 0.01 thick

Dimensions are in inches [millimeters].

Standard dimension tolerance is ± 0.010 [0.25] unless otherwise noted.

©2000 Bel Fuse Inc. Specifications subject to change without notice. 01.00

CORPORATE

Bel Fuse Inc.
198 Van Vorst Street
Jersey City, NJ 07302
Tel 201-432-0463
Fax 201-432-9542
www.belfuse.com

FAR EAST

Bel Fuse Ltd.
8F / 8 Luk Hop Street
San Po Kong
Kowloon, Hong Kong
Tel 852-2328-5515
Fax 852-2352-3706
www.belfuse.com

EUROPE

Bel Fuse Europe Ltd.
Preston Technology Management Centre
Marsh Lane, Suite F23, Preston
Lancashire, PR1 8UD, U.K.
Tel 44-1772-556601
Fax 44-1772-888366
www.belfuse.com