



ADSL-Transformer

WSL-A32.329

Specifications



Schematics & Mechanicals (mm)

Application
Generic

EP Core Design

EP 13 shown
For smaller sizes down to EP 7,
contact WICKMANN

Features

Optimized magnetic shielding for low
interference
High performance, high quality design
Surface Mount and Through Hole package

WebLinks

Data Sheet

www.wickmann.com/products/WSL_A32329.pdf

Packaging

www.wickmann.com/pack

Packaging

100 pcs./tray
7 trays/carton

Mounting

Through-Hole
For Surface Mount version,
contact WICKMANN

Solderability

270 - 300°C

Isolation voltage

1875 VAC

Operation Temperature Range



-40°C to +85°C

Marking

 Model No.

Unit Weight

7g



DC Resistance:

0,42 Ω (1-4) max. ±10%
0,42 Ω (2-5) max. ±10%
0,42 Ω (9-6) max. ±10%
0,42 Ω (10-7) max. ±10%

Open Circuit Inductance:

1,25mH ±5% @ 10kHz, 50mVAC, (1-5), short (2+4)

Turns Ratio:

1:1 ± 1%, (2-5):(1-4)
1:1 ± 1%, (10-6):(1-5)

Leakage Inductance:

12μH max. @ 100kHz, 50mVAC, (1-5), short (2+4, 7+9, 10+6)

Longitudinal Balance:

-

Return Loss:

-

Reflects 100Ω @ R_L =

-

Insertion Loss:

-

Total Harmonic Distortion (THD):

-

Order
Information

Qty.	Order Number
	960 4 632329 9