



[2 YEAR WARRANTY]



BXA15 SERIES

Single and dual output

- Pin-compatible with BXA30 series
- Designed to meet telecom power supply interface standard ETS300-132-2
- UL, VDE and CSA safety approvals
- VDE0878 and EN55022 conducted emissions level A
- EN61000-4-2, -3, -4, -5, -6 compliant
- Fixed frequency operation at 350kHz
- MTBF in excess of 7,005,000 hours (demonstrated)
- Basic insulation system

The BXA15 Series, comprising 15 different models, has been conceived as an applications specific range of DC/DC converters, specifically addressing telecommunications, industrial electronics, test equipment, mobile telecommunications and distributed power applications. The series offers three wide input voltage ranges, 9-18VDC, 18-36VDC and 36-75VDC, and is available in single and dual output versions. Designed to meet ETSI telecoms interface standards ETS300-132-2 and BTR2511, together with internal filtering to EN55022 level A, safety approval to EN60950 and UL1950, and isolation of 1500VDC, the 48VDC models are ideal for telecommunications applications. The 12V and 24V models are particularly suited to industrial, mobile telecom and test equipment applications, offering EN61000-4-2, -3, -4, -5 and -6 immunity compliance. Other features include low output ripple, overvoltage protection, continuous short circuit protection, remote enable and remote sense.

SPECIFICATION

All specifications are typical at nominal input, full load at 25°C unless otherwise stated

OUTPUT SPECIFICATIONS		
Voltage adjustability		±10%
Line regulation	LL to HL (single/dual)	±0.2%/±0.4%
Load regulation	FL to NL (single/dual)	±0.2%/±0.4%
Ripple and noise 20MHz bandwidth	5.0V All others All models	60mV pk-pk 100mV pk-pk 20mV rms
Temperature coefficient		±0.02%/°C
Overvoltage protection	Transient	135% Vout
Short circuit protection	Singles Duals (single short) Duals (dual short)	Continuous (See Design Note 100) Continuous
Transient response	25% to 100% load	4.0%
Voltage accuracy		±1.5%
Load cross regulation	Dual output 30% to 100% output variation	3.0%
INPUT SPECIFICATIONS		
Input voltage range	12Vin nominal 24Vin nominal 48Vin nominal	9 to 18VDC 18 to 36VDC 36 to 75VDC
Reverse voltage protection	(See Note 6)	Yes
Max. input rise and fall time	48V ETS300-132	5V/ms
Remote ON/OFF Logic compatibility ON OFF		CMOS/TTL Open circuit <1VDC

EMC CHARACTERISTICS		
Conducted emissions	EN55022, FCC part 15 (Note 4) Level A EN55022, FCC part 15 (Note 5) Level B VDE0878 (Note 4) (48V) Level A	
Radiated emissions	EN55022, FCC part 15 Level A	
ESD air	EN61000-4-2, level 3	Perf. criteria 2
ESD contact	EN61000-4-2, level 4	Perf. criteria 2
Surge	EN61000-4-5, level 3	Perf. criteria 2
Fast transients	EN61000-4-4, level 3	Perf. criteria 2
Radiated immunity	EN61000-4-3, level 3	Perf. criteria 2
Conducted immunity	EN61000-4-6, level 3	Perf. criteria 2
GENERAL SPECIFICATIONS		
Efficiency		See table
Isolation voltage	Input/output	1500VDC
Basic insulation	Input/case, 48V models	1500VDC
Switching frequency	Fixed	350kHz
Approvals and standards (See Note 9)	VDE0805, EN60950 IEC950, UL1950, UL1459 CSA C22.2 No. 950	
Case material	Aluminum substrate with plastic case	
Material flammability	UL94V-0	
Weight	120g (4.24oz)	
MTBF (See Note 8)	Demonstrated @ 25°C	7,005,000 hours
ENVIRONMENTAL SPECIFICATIONS		
Thermal performance	Baseplate operating temperature (See Notes 7) Non-operating	-25°C to +100°C -55°C to +100°C
Thermal impedance baseplate to air	Free air convection	6.5°C/W
Thermal impedance with heatsink	(See Note 7)	5.2°C/W

15 Watt Wide input DC/DC converters

INPUT VOLTAGE	OUTPUT VOLTAGE	OUTPUT CURRENT (MAX.)	INPUT CURRENT (1)	TYPICAL EFFICIENCY	REGULATION		MODEL NUMBER
					LINE (2)	LOAD (3)	
9-18VDC	5.0V	3.0A	100mA	80%	0.2%	0.2%	BXA15-12S05
9-18VDC	12.0V	1.25A	100mA	83%	0.2%	0.2%	BXA15-12S12
9-18VDC	15.0V	1.0A	100mA	85%	0.2%	0.2%	BXA15-12S15
9-18VDC	±12.0V	±0.625A	100mA	83%	0.4%	0.4%	BXA15-12D12
18-36VDC	5.0V	3.0A	60mA	80%	0.2%	0.2%	BXA15-24S05
18-36VDC	12.0V	1.25A	60mA	83%	0.2%	0.2%	BXA15-24S12
18-36VDC	15.0V	1.0A	60mA	85%	0.2%	0.2%	BXA15-24S15
18-36VDC	±12.0V	±0.625A	60mA	83%	0.4%	0.4%	BXA15-24D12
18-36VDC	±15.0V	±0.5A	60mA	85%	0.4%	0.4%	BXA15-24D15
36-75VDC	5.0V	3.0A	35mA	80%	0.2%	0.2%	BXA15-48S05
36-75VDC	12.0V	1.25A	35mA	84%	0.2%	0.2%	BXA15-48S12
36-75VDC	15.0V	1.0A	35mA	86%	0.2%	0.2%	BXA15-48S15
36-75VDC	±5.0V	±1.5A	35mA	80%	0.4%	0.4%	BXA15-48D05
36-75VDC	±12.0V	±0.625A	35mA	83%	0.4%	0.4%	BXA15-48D12
36-75VDC	±15.0V	±0.5A	35mA	85%	0.4%	0.4%	BXA15-48D15

Notes


- 1 Nominal, at no load.
- 2 Low line to high line.
- 3 Full load to no-load. For duals, the value stated is for balanced loads.
- 4 An optional internal filter is available, which will meet VDE0871 level A, VDE0878 level A and EN55022 level A. Add the suffix '-F' to the model number, e.g. **BXA15-48S12-F**.
- 5 For conducted noise operation of the BXA30 to VDE0871, VDE0878 and EN55022 level B, see BXA15 and BXA30 Design Note 100.
- 6 Reverse voltage protection can be implemented by putting a slow blow fuse on the negative input rail. Rate the fuse for 48VDC at 1.5A; 24VDC at 3A; 12VDC at 6A.
- 7 The maximum operating ambient temperature, without derating depends on internal power dissipation and hence efficiency and cooling method. BXA15 and BXA30 Design Note 100 provides detailed thermal calculations and design-in details.
- 8 Test results to-date are 1,590,000 hours @ 46°C. The MTBF figure shown includes a calculated acceleration factor of 4.1 based on an activation energy of -0.55 eV.
- 9 This product is only for inclusion by professional installers within other equipment and must not be operated as a stand alone product.
- 10 Visit the Artesyn website to download a copy of Design Note 100.

PIN CONNECTIONS

PIN NUMBER	SINGLE OUTPUT	DUAL OUTPUT
1	+ Vin	+ Vin
2	- Vin	- Vin
3	+ Sense	+ Vout
4	Trim	Common
5	- Sense	- Vout
6	+ Vout	No Pin
7	- Vout	No Pin
8	Remote ON/OFF	Remote ON/OFF

EXTERNAL OUTPUT TRIMMING

Single output models can be externally trimmed by ±10% using either method shown below.



International Safety Standard Approvals

VDE0805/EN60950/IEC950 File No. 14501-3336-7006, Licence No. 6231

UL1950 File No. E174104

CSA C22.2-234 No. 950 File No. LR41062C

Data Sheet © Artesyn Technologies® 2000

The information and specifications contained in this data sheet are believed to be correct at time of publication. However, Artesyn Technologies accepts no responsibility for consequences arising from printing errors or inaccuracies. Specifications are subject to change without notice. No rights under any patent accompany the sale of any such product(s) or information contained herein.