



[ 2 YEAR WARRANTY ]



## BXA15 SERIES

Triple output

- Pin-compatible with BXA30 series
- Designed to meet telecom power supply interface standard ETS300-132-2
- UL, VDE and CSA safety approvals
- VDE0878 and EN55022 conducted emissions level A
- EN61000-4-2, -3, -4, -5, -6 immunity compliant
- Fixed frequency operation at 350kHz
- MTBF in excess of 7,005,000 hours (demonstrated)
- Basic insulation system

The BXA15 triple output series, comprising 4 different models, has been conceived as an applications specific range of DC/DC converters, specifically addressing telecommunications, industrial electronics, test equipment, mobile telecommunications and distributed power applications. The series offers two wide input voltage ranges, 18-36VDC and 36-75VDC. Designed to meet ETSI telecoms interface standards ETS300-132-2 and BTR2511, together with internal filtering to EN55022 level A, safety approval to EN60950 and UL1950, and basic isolation of 1500VDC, the 48VDC models are ideal for telecommunications applications. The 24V models are particularly suited to industrial, mobile telecom and test equipment applications, featuring EN61000-4-2, -3, -4, -5 and -6 immunity compliance. Other features include low output ripple, overvoltage protection, short circuit protection, remote enable.

## SPECIFICATION

All specifications are typical at nominal input, full load at 25°C unless otherwise stated

OUTPUT SPECIFICATIONS		
Output power		15W
Line regulation (See Note 1)	Main output Auxiliary output	±0.5% ±2.0%
Load regulation (See Note 2)	Main output Auxiliary output	±1.0% ±3.0%
Ripple and noise 20MHz bandwidth	Main output Auxiliary outputs	75mV pk-pk 15mV rms 100mV pk-pk 20mV rms
Temperature coefficient		±0.02%/°C
Overvoltage protection	Transient, all outputs	135% Vout init.
Short circuit protection	All outputs (See BXA15 and BXA30 Design Note 100)	Yes
Transient response	25% to 100% load, all outputs	10%
Voltage accuracy	Main output Auxiliary output	±1.5% ±3.0%
Load cross regulation	40% to 100% load, all outputs Main output Auxiliary output	1.0% 10%
Minimum load	Main output for auxiliary regulation (See Note 8)	≥20%
INPUT SPECIFICATIONS		
Input voltage range	24Vin nominal 48Vin nominal	18 to 36VDC 36 to 75VDC
Reverse voltage protection	(See Note 5)	Yes
Max. input rise and fall time	48V	5V/ms ETS300-132
Remote ON/OFF Logic compatibility ON OFF		CMOS/TTL Open circuit <1VDC

EMC CHARACTERISTICS		
Conducted noise	EN55022, FCC part 15 (Note 3) Level A EN55022, FCC part 15 (Note 4) Level A VDE0878 (Note 3) (48V) Level A	
Radiated emissions	EN55022, FCC part 15 Level A	
ESD air	EN61000-4-2, level 3	Perf. criteria 2
ESD contact	EN61000-4-2, level 4	Perf. criteria 2
Surge	EN61000-4-5, level 3	Perf. criteria 2
Fast transients	EN61000-4-4, level 3	Perf. criteria 2
Radiated immunity	EN61000-4-3, level 3	Perf. criteria 2
Conducted immunity	EN61000-4-6, level 3	Perf. criteria 2
GENERAL SPECIFICATIONS		
Efficiency	See table	
Isolation voltage	Input/output	1500VDC
Basic insulation	Input/case, 48V models	1500VDC
Switching frequency	Fixed	350kHz, nom.
Approvals and standards (See Note 7)	VDE0805, EN60950 IEC950, UL1950 CSA C22.2 No. 950	
Case material	Aluminum substrate with plastic case	
Material flammability	UL94V-0	
Weight	130g (4.6oz)	
MTBF (See Note 9)	Demonstrated @ 25°C	7,005,000 hours
ENVIRONMENTAL SPECIFICATIONS		
Thermal performance	Baseplate operating temperature (Note 6) Non-operating	-25°C to +100°C -55°C to +100°C
Thermal impedance	Free air convection, baseplate to air	6.5°C/W

