



Micro Commercial Components
21201 Itasca Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

BU208

Features


- High voltage fast-switching NPN power transistors
- With TO-3 package
- Horizontal deflection for color TV

NPN Silicon Power Transistors

Maximum Ratings

Symbol	Rating	Rating	Unit
V_{CEO}	Collector-Emitter Voltage	700	V
V_{CBO}	Collector-Base Voltage	1500	V
V_{EBO}	Emitter-Base Voltage	5.0	V
I_{CP}	Peak Collector Current	7.5	A
I_C	Collector Current	5.0	A
P_C	Collector power dissipation	150	W
T_J	Junction Temperature	-55 to +150	°C
T_{STG}	Storage Temperature	-55 to +150	°C

TO-3



PIN 1. BASE
PIN 2. EMITTER
CASE. COLLECTOR

Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Max	Units
OFF CHARACTERISTICS				
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage ($I_C=100\text{mA}$, $I_B=0$)	700	---	Vdc
I_{CBO}	Collector-Base Cutoff Current ($V_{CB}=1500\text{Vdc}$, $I_E=0$)	---	1.0	mA
I_{EBO}	Emitter-Base Cutoff Current ($V_{EB}=5.0\text{Vdc}$, $I_C=0$)	---	10	mA

ON CHARACTERISTICS

h_{FE-1}	Forward Current Transfer ratio ($I_C=4.5\text{A}$, $V_{CE}=5.0\text{Vdc}$)	2.25	---	---
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage ($I_C=4.5\text{A}$, $I_B=2.0\text{A}$)	---	1.0	Vdc
$V_{BE(sat)}$	Base-Emitter Saturation Voltage ($I_C=4.5\text{A}$, $I_B=2.0\text{A}$)	---	1.5	Vdc

DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	1.550	REF	39.37	REF	
B	---	1.050	---	26.67	
C	.250	.335	6.35	8.51	
D	.038	.043	0.97	1.09	
E	0.55	0.70	1.40	1.77	
G	.430	BSC	10.92	BSC	
H	.215	BSC	5.46	BSC	
K	.440	.480	11.18	12.19	
L	.665	BSC	16.89	BSC	
N	---	.830	---	21.08	
Q	.151	.165	3.84	4.19	Ø
U	1.187	BSC	30.15	BSC	
V	.131	.188	3.33	4.77	