




**BVU-5M5GT4
BVT-5M5GT4**


PACKAGE CONFIGURATION

DESCRIPTION

Dice Material : GaN Bluish Green
Light Color : Bluish Green Color
Lens Color : Water Transparent
Stand-Off P/N : BVU-5M5GT4 R



RADIATION PATTERN



Tolerance ± 0.25 mm

ABSOLUTE MAXIMUM RATINGS AT Ta = 25 °C

PARAMETER	MAX.	UNIT
Power Dissipation	120	mW
Continuous Forward Current	30	mA
Peak Forward Current (1/10 Duty Cycle , 0.1ms Pulse Width)	100	mA
Reverse Voltage	5	V
Derating Linear From 25 °C	0.4	mA/°C
Operating Temperature Range	-30 °C to +85 °C	
Storage Temperature Range	-40 °C to +100 °C	
Lead Solder Temperature 1.6 mm Below Package	260 °C for 5 seconds	

ELECTRICAL / OPTICAL CHARACTERISTICS AT Ta = 25 °C

SYMBOL	PARAMETER	TEST COND.	MIN.	TYP.	MAX.	UNIT
V _F	Forward Voltage	I _F = 10 mA		3.2	3.7	V
I _R	Reverse Current	V _R = 5V			10	μA
λ _p	Peak Emission Wavelength	I _F = 10 mA		500		nm
λ _d	Dominant Wavelength	I _F = 10 mA		503		nm
2θ _{1/2}	Viewing Angle	I _F = 10 mA		30		Deg

BIN GRADE LIMITS (I_F = 10 mA) LUMINOUS INTENSITY / mcd

Bin	J	K	L	M	N	O
Min.	1000	1300	1680	2180	2800	3600
Max.	1300	1680	2180	2800	3600	4650

Tolerance ± 15% mcd

*Bright View reserves the rights to alter specifications and remove availability of products at any time without notice.

*Dominant Wavelength, λ_d is according to CIE Chromaticity Diagram base on color of lamps.

*θ_{1/2} is the off-axis angle where the luminous intensity is one half the on-axis intensity.

*These products are sensitive to static electricity. Caution must be taken strictly to avoid static electricity.