





BVU-940BE4

PACKAGE CONFIGURATION

DESCRIPTION

Dice Material : GaN/SiC Blue
Light Color : Blue Color
Lens Color : Water Transparent
Stand-Off P/N : BVU-940BE4 R

RADIATION PATTERN



Tolerance ± 0.25 mm

ABSOLUTE MAXIMUM RATINGS AT $T_a = 25^\circ\text{C}$

PARAMETER	MAX.	UNIT
Power Dissipation	110	mW
Continuous Forward Current	30	mA
Peak Forward Current (1/10 Duty Cycle , 0.1ms Pulse Width)	70	mA
Reverse Voltage	5	V
Derating Linear From 50 °C	0.4	mA/°C
Operating Temperature Range	−40 °C to + 100 °C	
Storage Temperature Range	−40 °C to + 100 °C	
Lead Solder Temperature 1.6 mm Below Package 260 °C for 5 seconds		

ELECTRICAL / OPTICAL CHARACTERISTICS AT $T_a = 25^\circ\text{C}$

SYMBOL	PARAMETER	TEST COND.	MIN.	TYP.	MAX.	UNIT
V _F	Forward Voltage	I _F = 20 mA		3.8	4.7	V
I _R	Reverse Current	V _R = 5V			10	μA
λ_p	Peak Emission Wavelength	I _F = 20 mA		428		nm
λ_d	Dominant Wavelength	I _F = 20 mA		466		nm
$2\theta_{1/2}$	Viewing Angle	I _F = 20 mA		50		Deg

BIN GRADE LIMITS (I_F = 20 mA) LUMINOUS INTENSITY / mcd

Bin	s	t	u	v	w	x
Min.	13	17	22	28	36	47
Max.	17	22	28	36	47	60

Tolerance $\pm 15\%$ mcd

*Bright View reserves the rights to alter specifications and remove availability of products at any time without notice.

*Dominant Wavelength, λ_d is according to CIE Chromaticity Diagram base on color of lamps.

* $\theta_{1/2}$ is the off-axis angle where the luminous intensity is one half the on-axis intensity.

*These products are sensitive to static electricity. Caution must be taken strictly to avoid static electricity.

PRELIMINARY