

BVG - 113G2


DESCRIPTION

Dice Materia : GaP/GaP Yellow Green


Light Color : Yellow Green

Lens Color : Water Transparent

PACKAGE CONFIGURATION



TYPICAL INTERNAL EQUIVALENT CIRCUIT



ABSOLUTE MAXIMUM RATINGS AT $T_a = 25^{\circ}\text{C}$

PARAMETER	MAX.	UNIT
Forward Voltage	25.3	V
Reverse Voltage	32.0	V
Power Dissipation	3.0	W
Operating Temperature Range	-10°C TO +60°C	
Storage Temperature Range	-25°C TO +80°C	

ELECTRICAL / OPTICAL CHARACTERISTICS AT Ta = 25°C

SYMBOL		PARAMETER	TEST COND.	MIN.	TYP.	MAX.	UNIT
I _{DD}	Forward	Current	V _{DD} = 24 V		95	120	mA
I _R	Reverse	Current	V _R = 32 V			0.5	mA
L _{vp}	Peak	Luminous	V _{DD} = 24 V	700	1100	1500	Lux
△EH	Uniformity		V _{DD} = 24 V			14	%
△L	Effective	Illuminated Width	V _{DD} = 24 V	3.0	4.6		mm
λ _p	Peak	Emission Wavelength	I _F = 20 mA		568		nm
△λ	Spectral	Line Half Width	I _F = 20 mA		30		nm
L	Effective	Illuminated Length	V _{DD} = 24 V		218		mm

* Bright View reserves the rights to alter specifications and remove availability of products at any time without notice.

* Dominant Wavelength, λ_d is according to CIE Chromaticity Diagram base on color of lamps.

* $\theta_{1/2}$ is the off-axis angle where the luminous intensity is one half the on-axis intensity.