

Low Voltage/1A Output LDO Regulator

BA□□BC0WFP/WT
BA□□BC0FP/T

● Description


BA□□BC0WFP/WT and BA□□BC0FP/T are PNP output LDO regulator ICs with the output current of 1A and voltage accuracy of $\pm 2\%$. Over-current protection circuit and thermal protection circuit are incorporated. BA□□BC0WFP/WT incorporates shutdown switch to control output ON/OFF.

[Series line-up]

Part No.	Output Current (A)	Output Voltage(V)										Package
		1.5	1.8	2.5	3	3.3	5	6	7	8	9	
BA□□BC0WFP	1.0	1.5	1.8	2.5	3	3.3	5	6	7	8	9	TO252-5
BA□□BC0WT		1.5	1.8	2.5	3	3.3	5	6	7	8	9	TO220FP-5
BA□□BC0FP		1.5	1.8	2.5	3	3.3	5	6	7	8	9	TO252-3
BA□□BC0T		1.5	1.8	2.5	3	3.3	5	6	7	8	9	TO220FP


● Dimension (Units :mm)

[BA□□BC0WFP]




TO252-5

[BA□□BC0WT]




TO220FP-5

[BA□□BC0FP]



TO252-3

[BA□□BC0T]



TO220FP

● Features

- 1) Maximum output current : 1A
- 2) Output voltage accuracy : $\pm 2\%$
- 3) Low drop-out voltage type with PNP output
- 4) Built-in over-current protection circuit and thermal protection circuit
- 5) Built-in shutdown circuit which circuit current is 0uA. (BA□□BC0WFP/WT)
- 6) Two types of package (Small mounting type and insertion type)

● Applications

Consumer products

● Absolute Maximum Ratings ($T_a=25^\circ C$)

Parameter	Symbol	Limits		Unit
Supply Voltage	Vcc	18	*1	V
Power Dissipation	Pd	1200	*2	mW
		1300	*3	
		2000	*4	
		2000	*4	
Operating Temperature Range	Topr	-40 ~ +105		°C
Storage Temperature Range	Tstg	-55 ~ +150		°C
Junction Temperature	Tjmax	150		°C

*1 Do not however exceed Pd.

*2 Mounted on 70mm x 70mm x 1.6mm glass-epoxy PCB Derating in done at 9.6mW/°C for operating above $T_a=25^\circ C$

*3 Mounted on 70mm x 70mm x 1.6mm glass-epoxy PCB Derating in done at 10.4mW/°C for operating above $T_a=25^\circ C$

*4 Derating in done at 16mW/°C for operating above $T_a=25^\circ C$

[BA□□BC0WFP/WT]

● Electrical Characteristics (Unless otherwise specified, Ta=25°C, Vcc=3.3V, VCTL=3V)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Shut down circuit current	Isd	—	0	10	μA	VCTL=0V, OFF MODE
Output voltage	Vo	0.98 x Vo	Vo	1.02 x Vo	V	Vo : Refer to the series line-up
Peak output current	Io	1.0	—	—	A	
Ripple rejection	R.R.	44	55	—	dB	f=120Hz, ein=−20dBV, Io=100mA
Line regulation	Reg.I	—	15	35	mV	Io=200mA
Load regulation	Reg.L	—	33	75	mV	Io=0mA → 1A
Temperature coefficient of output current *	Tcvo	—	±0.02	—	% / °C	Io=5mA, Tj=0~125°C
ON mode voltage	Vth1	2.0	—	—	V	Io=0mA
OFF mode voltage	Vth2	—	—	0.8	V	OFF MODE, Io=0mA
Input high current	Iin	40	80	130	μA	Io=0mA

* Designed Guarantee.(Outgoing inspection is not done all products.)

[BA□□BC0FP/T]


● Electrical Characteristics (Unless otherwise specified, Ta=25°C, Vcc=3.3V)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Output voltage	Vo	0.98 x Vo	Vo	1.02 x Vo	V	Vo : Refer to the series line-up
Peak output current	Io	1.0	—	—	A	
Ripple rejection	R.R.	44	55	—	dB	f=120Hz, ein=−20dBV, Io=100mA
Line regulation	Reg.I	—	15	35	mV	Io=200mA
Load regulation	Reg.L	—	33	75	mV	Io=0mA → 1A
Temperature coefficient of output current *	Tcvo	—	±0.02	—	% / °C	Io=5mA, Tj=0~125°C


* Designed Guarantee.(Outgoing inspection is not done all products.)

● Application Circuit


[BA□□BC0WFP]



[BA□□BC0WT]



[BA□□BC0FP]



[BA□□BC0T]

