

**SURFACE MOUNT
SCHOTTKY BARRIER RECTIFIERS**


REVERSE VOLTAGE - **20 to 60** Volts
FORWARD CURRENT - **5.0** Amperes

FEATURES

- For surface mounted applications
- Metal-Semiconductor junction with guardring
- Epitaxial construction
- Very Low forward voltage drop
- High current capability
- Plastic material has UL flammability classification 94V-0
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications

MECHANICAL DATA

- Case : Molded plastic
- Polarity : Color band denotes cathode
- Weight : 0.007 ounces, 0.21 grams

SMC


SMC		
DIM.	MIN.	MAX.
A	6.60	7.11
B	5.59	6.22
C	2.92	3.18
D	0.15	0.31
E	7.75	8.13
F	0.05	0.20
G	2.01	2.62
H	0.76	1.52
All Dimensions in millimeter		

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.
Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%

CHARACTERISTICS	SYMBOL	B520C	B530C	B540C	B550C	B560C	UNIT
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	20	30	40	50	60	V
Maximum RMS Voltage	V _{RMS}	14	21	28	35	42	V
Maximum DC Blocking Voltage	V _{DC}	20	30	40	50	60	V
Maximum Average Forward Rectified Current @TL =90℃	I(AV)	5.0					A
Peak Forward Surge Current 8.3ms single half sine-wave super imposed on rated load (JEDEC METHOD)	I _{FSM}	175					A
Maximum forward Voltage at 5.0A DC	V _F	0.55			0.70		V
Maximum DC Reverse Current @TJ =25℃ at Rated DC Blocking Voltage @TJ =100℃	I _R	0.5 20					mA
Typical Junction Capacitance (Note 1)	C _J	300					pF
Typical Thermal Resistance (Note 2)	RθJL	10					℃/W
Typical Thermal Resistance (Note 2)	RθJA	50					℃/W
Operating Temperature Range	T _J	-55 to +125					℃
Storage Temperature Range	T _{STG}	-55 to +150					℃

NOTES : 1. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.
2. Thermal Resistance Junction to Lead.

REV. 2, 01-Dec-2000, KSHC03

