



Capacitive sensor

BC10-Q14-AN4X2



- rectangular, height 14mm
- top active face
- plastic, PBT12-GF30-V0
- fine adjustment via potentiometer
- 3-wire DC, 10...65 VDC
- normally open npn output
- cable connection

Wiring diagram



Function principles


Capacitive proximity switches are designed for non-contact and wear-free detection of metal (electrically conductive) and non-metal (electrically non-conductive) objects.

Type	BC10-Q14-AN4X2
Ident-No.	2530010
Rated operating distance Sn	10 mm, flush mounting
Rated operating distance Sn	15 mm, non-flush mounting
Hysteresis (switching distance)	2... 20 %
Temperature drift	≤ ± 20 %
Min. repeat accuracy	≤ 2 %
Operating temperature	-25 ...+ 70 °C
Rated operational voltage (DC) U_B	10... 65 VDC
Max. ripple	≤ 10 % U _{pp}
Rated operational current (DC) I _e	≤ 200 mA
No-load current I ₀	≤ 15 mA
Max. OFF-state current	≤ 0,1 mA
Max. switching frequency	≤ 0,1 kHz
Rated insulation voltage	≤ 0,5 kV
Output function	3-wire, normally open, NPN
Short-circuit protection	yes, cyclic
Max. voltage drop at I _e	≤ 1,8 V
Wire breakage / reverse polarity protection	yes / complete
Housing style	rectangular; Q14
Dimensions	52 x 30 x 14 mm
Housing material	plastic, PBT-GF30-V0
Active face	plastic, PBT-GF30-V0
Wiring	cable
Cable	Ø 4, LifYY, PVC, 2 m
Cable cross section	3 x 0,25 mm ²
Vibration resistance	55 Hz (1 mm)
Shock resistance	30 x g (11 ms)
Degree of protection	IP67
Supply voltage indication	LED green
Switching status indication	LED yellow
Included with sensor	MH-Q14

Capacitive sensor

BC10-Q14-AN4X2

Accessories

Typ	Ident-No.	Description	Dimension drawing
MW-Q14/Q20	6945006	mounting bracket; material VA 1.4301	
MH-Q14	6950011	for mounting with active face downwards	