



Inductive sensor magnetic-field immune Bi2-Q5,5-AP6X/S34




- rectangular, height 5.5mm
- top active face
- plastic, PA12-GF30
- magnetic-field immunity (welding resistance) to AC and DC fields
- 3-wire DC, 10...30 VDC
- normally open pnp output
- cable connection

Wiring diagram



Function principles

Inductive proximity switches are designed for wear-free non-contact detection of metal objects. For this they use a high-frequency electro-magnetic AC field that interacts with the target. With inductive sensors, this field is generated by an LC resonant circuit with a ferrite core coil. Magnetic field sensors incorporate a special ferrite core which make them immune to magnetic AC and DC fields. They may thus be used in welding applications.



Type	Bi2-Q5,5-AP6X/S34
Ident-No.	1613001
Rated operating distance Sn	2 mm
Mounting mode	flush
Hysteresis (switching distance)	3... 15 %
Min. repeat accuracy	≤ 2 %
Temperature drift	≤ ± 10 %
Operating temperature	-25 ...+ 70 °C
Rated operational voltage (DC) U_B	10... 30 VDC
Max. ripple	≤ 10 % U _{pp}
Rated operational current (DC) I _e	≤ 150 mA
No-load current I ₀	≤ 15 mA
Max. OFF-state current	≤ 0,1 mA
Max. switching frequency	≤ 2 kHz
Rated insulation voltage	≤ 0,5 kV
Output function	3-wire, normally open, PNP
Short-circuit protection	yes, cyclic
Max. voltage drop at I _e	≤ 1,8 V
Wire breakage / reverse polarity protection	yes / complete
Housing style	rectangular; Q5,5
Dimensions	28 x 8 x 5,5 mm
Housing material	plastic, PA12-GF30
Active face	plastic, PA12-GF30
Wiring	cable
Cable	Ø 3, LifYY-11Y, PUR, 2 m
Cable cross section	3 x 0,14 mm ²
Vibration resistance	55 Hz (1 mm)
Shock resistance	30 x g (11 ms)
Degree of protection	IP67
Switching status indication	LED yellow

Inductive sensor magnetic-field immune Bi2-Q5,5-AP6X/S34

Mounting instructions

	minimum gap
Gap D	$2 \times B$
Gap W	$3 \times S_n$
Gap S	$1 \times B$
Gap G	$6 \times S_n$

Width of active face B

8 mm

