

ELECTRICAL SPECIFICATIONS

(25°C UNLESS OTHERWISE SPECIFIED)

INPUT (CONTROL) SPECIFICATIONS

Parameter	Min	Max	Units
Control Voltage Range (See Figures 1, 2 and Note 1)	3.8	32	Vdc
Input Current @ 5 V (See Figures 1 and 2)		14	mAdc
Must Turn-On Voltage	3.8		Vdc
Must Turn-Off Voltage (Guaranteed Off)		1.5	Vdc
Reverse Voltage Protection		-32	Vdc

OUTPUT (LOAD) SPECIFICATIONS

Parameter	DC		Bi-directional		Units
	Min	Max	Min	Max	
Load Voltage Rating	C47F-10	50	C46F-10	±50	Vdc
	C47F-20	90	C46F-20	±90	
	C47F-30	180	C46F-30	±180	
	C47F-40	360	C46F-40	±360	
Output Current Rating (See Figure 3)	C47F-10	1.75	C46F10	1.0	Adc
	C47F-20	1.0	C46F-20	0.75	
	C47F-30	0.6	C46F-30	0.4	
	C47F-40	0.4	C46F-40	0.25	
On Resistance (See Note 3)	C47F-10	0.15	C46F-10	0.3	Ohms
	C47F-20	0.35	C46F-20	0.7	
	C47F-30	1.0	C46F-30	2.0	
	C47F-40	2.0	C46F-40	4.0	
Leakage Current at 80% of V_L		10.0		10.0	μAdc
Surge Rating (% of Rated)		200		200	%
Turn On Time	C47F	1.5	C46F-10	2.5	ms
			C46F-20,30,40	1.5	
Turn Off Time		1.0		1.0	ms
Output Capacitance (Typical)	C47F-10	250	C46F-10	250	pF
	C47F-20	200	C46F-20	200	
	C47F-30	150	C46F-30	150	
	C47F-40	100	C46F-40	100	
Isolation (Input to Output)		10^9		10^9	Ohms
Dielectric Strength (Input to Output)	1500		1500		Vac
Capacitance (Input to Output)		10		10	pF
Junction Temperature (T_J)		125		125	°C




FEATURES/BENEFITS

- Power FET output with Very Low On Resistance - Virtually no offset with low leakage and voltage drop.
- Switches High Voltages and Currents - Voltages to 360 Vdc. Current to 1.75 Adc. DC, Bi-directional or AC models
- Optical Isolation - Isolates control elements from load transients. Eliminates ground loops and signal ground noise.
- Floating Output - Allows for high and low side switching.
- High Noise Immunity - Control circuit can not be triggered by output switching noise.
- 14 Pin DIP Package

DESCRIPTION




These miniature solid state relays utilize a photo-voltaic generator driving high performance power FET chips to provide low output on-resistance and high output switching capability. The series includes DC switching versions with output current ratings up to 1.75 amp, and bi-directional versions to switch AC or DC up to 1.0 amp. Output voltage ratings of both types range from 50 to 360 volts. The virtual elimination of offset voltage makes them ideal for low level switching applications as well. Input and output are optically isolated to protect input logic circuits from output voltage transients.

BLOCK DIAGRAM






C47 is the same configuration except Q_2 has been replaced with a wire short

CHARACTERISTIC CURVES




MECHANICAL SPECIFICATION




DIMENSIONS ARE SHOWN IN INCHES (MILLIMETERS)
Tolerances ± 0.015 (0.38) unless otherwise specified

- Operating Temperature -40°C to 100°C .
- Storage Temperature -40°C to 100°C .
- Weight: 2.0 grams maximum
- Case: 14 pin Dual-In-Line (TO-116)
- Case Material: Epoxy, self extinguishing

TYPICAL INTERFACE



BI-DIRECTIONAL OR AC MODELS



DC MODELS

Loads may be connected in either output terminal

NOTES:

1. For control voltages above 6 volts a series resistor is required. Use standard value selected from Figure 2.
2. Surge current duty cycle 10% maximum. Surge duration not to exceed 1 second.
3. To calculate output On-Resistance for junction temperatures other than 25°C use the following equation:

$$R_T = R_{25} e^{0.006 \times \Delta T} \quad \text{where } R_{25} = \text{Resistance at } 25^{\circ}\text{C}$$

R_T = Resistance at elevated temperature
 ΔT = Elevated temperature - 25°C