




40 LED Cluster, 15mm DC Bayonet Based Lamps

Packages	Replaces Incandescent	Part Number	Input Voltage	Power Watts (typ)	Intensity per LED I_v mcd (typ)	λ_p (nm)	View Angle $2\theta^{1/2}$	Custom Options
	73D,976,R24	DB640-0UR-014N	12/14V	1.4W to 2.7W	2000	660	12° to 15°	Replace N in part number with required viewing angle S - Standard (25° to 30°) M - Medium (45° to 50°) W - Wide (120° to 125°)
		DB640-0UR-024N	24V					
		DB640-0UR-028N	28V					
		DB640-0UR-036N	36V					
		DB640-0UR-120AN	120VAC					
	73D,976,R24	DB640-0ER-014N	12/14V	1.4W to 2.7W	3500	630	12° to 15°	Replace N in part number with required viewing angle S - Standard (25° to 30°) M - Medium (45° to 50°) W - Wide (120° to 125°)
		DB640-0ER-024N	24V					
		DB640-0ER-028N	28V					
		DB640-0ER-036N	36V					
		DB640-0ER-120AN	120VAC					
	73D,976,R24	DB640-0UO-014N	12/14V	1.4W to 2.7W	6500	612	12° to 15°	Replace N in part number with required viewing angle S - Standard (25° to 30°) M - Medium (45° to 50°) W - Wide (120° to 125°)
		DB640-0UO-024N	24V					
		DB640-0UO-028N	28V					
		DB640-0UO-036N	36V					
		DB640-0UO-120AN	120VAC					
	73D,976,R24	DB640-0UY-014N	12/14V	1.4W to 2.7W	5500	595	12° to 15°	Replace N in part number with required viewing angle S - Standard (25° to 30°) M - Medium (45° to 50°) W - Wide (120° to 125°)
		DB640-0UY-024N	24V					
		DB640-0UY-028N	28V					
		DB640-0UY-036N	36V					
		DB640-0UY-120AN	120VAC					
	73D,976,R24	DB640-0IW-014N	12/14V	1.4W to 2.7W	2000	4500K	12° to 15°	Replace N in part number with required viewing angle S - Standard (25° to 30°) M - Medium (45° to 50°) W - Wide (120° to 125°)
		DB640-0IW-024N	24V					
		DB640-0IW-028N	28V					
		DB640-0IW-036N	36V					
		DB640-0IW-120AN	120VAC					
	73D,976,R24	DB640-0CW-014N	12/14V	1.4W to 2.7W	6000	8000K	12° to 15°	Replace N in part number with required viewing angle S - Standard (25° to 30°) M - Medium (45° to 50°) W - Wide (120° to 125°)
		DB640-0CW-024N	24V					
		DB640-0CW-028N	28V					
		DB640-0CW-036N	36V					
		DB640-0CW-120AN	120VAC					
	73D,976,R24	DB640-0UG-014N	12/14V	1.4W to 2.7W	1000	570	12° to 15°	Replace N in part number with required viewing angle S - Standard (25° to 30°) M - Medium (45° to 50°) W - Wide (120° to 125°)
		DB640-0UG-024N	24V					
		DB640-0UG-028N	28V					
		DB640-0UG-036N	36V					
		DB640-0UG-120AN	120VAC					
	73D,976,R24	DB640-0AG-014N	12/14V	1.4W to 2.7W	10,000	525	12° to 15°	Replace N in part number with required viewing angle S - Standard (25° to 30°) M - Medium (45° to 50°) W - Wide (120° to 125°)
		DB640-0AG-024N	24V					
		DB640-0AG-028N	28V					
		DB640-0AG-036N	36V					
		DB640-0AG-120AN	120VAC					
	73D,976,R24	DB640-0BG-014N	12/14V	1.4W to 2.7W	2000	505	12° to 15°	Replace N in part number with required viewing angle S - Standard (25° to 30°) M - Medium (45° to 50°) W - Wide (120° to 125°)
		DB640-0BG-024N	24V					
		DB640-0BG-028N	28V					
		DB640-0BG-036N	36V					
		DB640-0BG-120AN	120VAC					
	73D,976,R24	DB640-0PB-014N	12/14V	1.4W to 2.7W	3000	470	12° to 15°	Replace N in part number with required viewing angle S - Standard (25° to 30°) M - Medium (45° to 50°) W - Wide (120° to 125°)
		DB640-0PB-024N	24V					
		DB640-0PB-028N	28V					
		DB640-0PB-036N	36V					
		DB640-0PB-120AN	120VAC					


Viewing Angle:
12° to 15°



Narrow Angle (N)


Optional Viewing Angles:

25° to 30°



Standard Angle (S)

45° to 50°



Medium Angle (M)

120 to 125




Wide Angle (W)


Notes:

- Not all possible combinations of voltage, intensity and angle are available
- Intensity shown is for narrow angle. Intensity is reduced 12° to 15° times when using extra wide angles

InfraReds
850/880/940nm




Dimensions



Low Cost Specials

8000K Cool White PN Example: DB640-1CW-120AN
525nm Aqua Green PN Example: DB640-1AG-120AN
505nm Blue Green PN Example: DB640-1BG-120AN
470nm Super Blue PN Example: DB640-1PB-120AN



Options: (Baseless with 12" wire leads)

Series: L640

PN Example: L640-0ER-120AN

LEDTRONICS, INC.
THE FUTURE OF LIGHT



23105 Kashiwa Court, Torrance, CA 90505
Phone: (800) 579-4875 or (310) 534-1505 Fax: (310) 534-1424
E-mail: webmaster@ledtronics.com
Website: http://www.ledtronics.com