

Actual Size


DMS-EB-HTB

High-Accuracy Temperature Sensor Boards DMS-30PC/LCD-0 Meters

Order online at www.datel.com

Features

- Accepts inputs from user-supplied solid-state temperature sensors
- Available in °C or °F output readings
- 6-wire screw-type terminal block
- Measures temperatures from -55 to +150°C (-67 to +199.9°F)
- Use with DMS-30PC/LCD-0 meters



Description: The DMS-EB-HTB Application Boards accept inputs from user-supplied, AD590 solid-state temperature sensors. The boards can be used with any of DATEL's ±200mV, 5V-powered DMS-30PC/LCD-0 Series, 3½ Digit, LED/LCD Display, Digital Panel Voltmeters — although better performance can be achieved with either LCD or low-power LED models. This meter/board combination provides extremely accurate (±0.3°C) temperature measurements over the range of -55 to +150°C (with DMS-EB-HTBC) or -67 to +199.9°F (DMS-EB-HTBF). Individual reference-adjust and probe-adjust potentiometers allow for "fine tuning" the AD590 output to precisely match the selected meter. A 6-wire, screw-type terminal block provides for quick, reliable, signal and power connections.

Calibration: R4 (Reference Adjust) is factory-calibrated to +459.8mV for °F and +273.2mV for °C (do not readjust). This measurement is taken between TB1 (pin 6) and pin 12 of the DMS-30PC/LCD-0. R1 (Probe Adjust) requires customer adjustment since every sensor has a slightly different zero offset. Calibration is simple: connect the sensor leads to TB1 and adjust R1 until the DMS-30's display matches a selected reference temperature indicator.

Functional Specifications (T_A = 25°C, V_{CC} = +5V)

Measurement Range:

DMS-EB-HTBC	-55 to +150°C
DMS-EB-HTBF	-67 to +199.9°F

Sensor Type

AD590 active linear device

Accuracy:

Typical	±0.3°C (or °F)
Maximum	±1.0°C (or °F)

Operating Voltage Range

+5V (±10%)

Input Current (Board only):

Typical	+0.8mA
Maximum	+1.0mA

Sensor Lead Length

3 feet, maximum

Operating Temperature Range

0 to +60°C

Storage Temperature Range

-20 to +75°C

Humidity (non-condensing)

0 to 95%,

Dimensions

2.02" (51.31mm)L
0.83" (21.08mm)W




Figure 1. DMS-EB-HTB Schematic Diagram

Ordering Information

DMS-EB-HTBC	High-accuracy temperature probe board, Celsius
DMS-EB-HTBF	High-accuracy temperature probe board, Fahrenheit
DMS-BZL1	Bezel assembly
DMS-BZL2	Bezel assembly with sealing gasket