

C & L-Band Tap Coupler

DC202-WB



Applications

- Monitoring Optical Amplifier, Mux/De-Mux and other modules in DWDM systems

Features

- Extra wide operating wavelength
- Small insertion loss fluctuation:
 - *Low wavelength dependent loss*
 - *Low polarization dependent loss*
 - *Low temperature dependent loss*
- Loose tube pigtails available


Specifications

Parameter		Specification			
Configuration		1 x 2, 2 x 2			
Operating Wavelength		1530 ~ 1610nm			
Operating Temperature		-10 ~ +70 °C			
Storage Temperature		-40 ~ +85 °C			
Split Ratio		50:50	90:10	95:5	98:2
Insertion Loss (dB)	Main port	≤ 3.60	≤ 0.75	≤ 0.48	≤ 0.25
	Tap port	≤ 3.60	9.5~11.0	12.0~14.0	16.0~18.0
Insertion Loss Flatness (dBp-p)	Main port	≤ 0.60	≤ 0.15	≤ 0.15	≤ 0.15
	Tap port	≤ 0.60	≤ 0.50	≤ 0.50	≤ 0.60
Polarization Dependent Loss (dBp-p)	Main port	≤ 0.20	≤ 0.10	≤ 0.10	≤ 0.10
	Tap port	≤ 0.20	≤ 0.20	≤ 0.20	≤ 0.20
Temperature Dependent Loss (dBp-p)	Main port	≤ 0.10			
	Tap port				
Size	φ0.25mm fiber type	2x2type;φ2.9 x L45mm, 1x2type;φ2.9 x L50mm			
	φ0.9mm loose tube type	2x2type;φ2.9 x L55mm, 1x2type;φ2.9 x L55mm			


Specifications do not include connectors

Available for FC-SPC, SC-SPC connectors for each port.

Dimensions



Ordering Information



Fitel Technologies, Inc. reserves the right to change data contained in this document in the interest of continued product improvement. The publication of this information by Fitel Technologies does not does not imply freedom from patent or any other rights of Fitel Technologies, Inc.



Perryville Corporate Park
Perryville III

Clinton, NJ 08809

T: 908-713-3525

F: 908-713-3515

www.fiteltech.com

sales@fiteltech.com