


<div>LCD Module Specification</div>		First Edition	Approved by	Production Div.
		May 20, 1998	Checked by	Quality Assurance Div.
		Final Revision	Checked by	Design Engineering Div.
		*****	Prepared by	Production Div.
Type No.	DMF – 5 0 2 6 2 N F – F W			
<div>Table of Contents</div> <div>1. General Specifications2</div> <div>2. Electrical Specifications.....3</div> <div>3. Optical Specifications8</div> <div>4. I/O Terminal.....10</div> <div>5. Test.....12</div> <div>6. Appearance Standards.....13</div> <div>7. Code System of Production Lot16</div> <div>8. Type Number16</div> <div>9. Applying Precautions16</div> <div>10. Handling Precautions17</div> <div>Revision History</div>				
Rev.	Date	Page	Comment	
DMF-50262NF-FW (AA) No.98-0082		 OPTREX CORPORATION	Page 1/17	

1. General Specifications

Operating Temp.	: min. 0°C ~ max. 50°C
Storage Temp.	: min. -20°C ~ max. 60°C
Dot Pixels	: 640 (W) × 400 (H) dots
Dot Size	: 0.27 (W) × 0.27 (H) mm
Dot Pitch	: 0.30 (W) × 0.30 (H) mm
Viewing Area	: 200.0 (W) × 128.0 (H) mm
Outline Dimensions	: 255.0* (W) × 147.0 (H) × 7.3 max. (D) mm * Without CFL Cable
Weight	: 310g max.
LCD Type	: NTD-11591 (F-STN / Black & White-mode / Transmissive)
Viewing Angle	: 6:00
Data Transfer	: 4-bit parallel data transfer × 2
Backlight	: Cold Cathode Fluorescent Lamp (CFL) × 1
Drawings	: Dimensional Outline UE-34368D

2. Electrical Specifications

2.1. Absolute Maximum Ratings

$V_{SS}=0V$

Parameter	Symbol	Conditions	Min.	Max.	Units
Supply Voltage (Logic)	$V_{CC}-V_{SS}$	—	-0.3	7.0	V
Supply Voltage (LCD Drive)	$V_{SS}-V_{EE}$	—	0	27.0	V
Input Voltage	V_I	—	-0.3	$V_{CC}+0.3$	V

2.2. DC Characteristics


$T_a=25^{\circ}C$, $V_{SS}=0V$

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Supply Voltage (Logic)	$V_{CC}-V_{SS}$	—	3.5	—	5.5	V
Supply Voltage (LCD Drive)	$V_{SS}-V_{EE}$	Shown in 3.1				V
High Level Input Voltage	V_{IH}	$V_{CC}=3.5\sim 5.5V$	$0.8 \times V_{CC}$	—	V_{CC}	V
Low Level Input Voltage	V_{IL}	$V_{CC}=3.5\sim 5.5V$	0	—	$0.2 \times V_{CC}$	V
Supply Current	I_{CC}	$V_{CC}-V_{SS}= 5.0V$ $V_{SS}-V_{EE}= 18.8V$	—	12.0	25.0	mA
		$V_{CC}-V_{SS}= 3.5V$ $V_{SS}-V_{EE}= 18.8V$	—	12.0	25.0	mA
	I_{EE}	$V_{CC}-V_{SS}= 5.0V$ $V_{SS}-V_{EE}= 18.8V$	—	8.0	20.0	mA


2.3.AC Characteristics

$V_{CC}=3.5\sim 5.5V$


Parameter	Symbol	Min.	Max.	Units
Clock Pulse Cycle Time	t_{WCK}	152	—	ns
Clock Pulse High Level Width	t_{WCKH}	65	—	ns
Clock Pulse Low Level Width	t_{WCKL}	65	—	ns
Latch Pulse High Level Width	t_{WLPH}	65	—	ns
CP→LP Rise Time	t_{LD}	0	—	ns
CP→LP Fall Time	t_{SL}	65	—	ns
LP→CP Rise Time	t_{LS}	65	—	ns
LP→CP Fall Time	t_{LH}	65	—	ns
Clock Pulse Rise/Fall Time	t_r, t_f	—	50	ns
Data Setup Time	t_{DS}	50	—	ns
Data Hold Time	t_{DH}	40	—	ns
$\overline{DISPOFF}$ Low Level Width	t_{WDL}	1.2	—	μs
$\overline{DISPOFF}$ Cancellation Time	t_{SD}	100	—	ns



2.4. Timing Chart




2.5. Comparison of Display and Data




2.6.Power Supply ON/OFF Sequence

2.6.1.ON Sequence



2.6.2.OFF Sequence



Please maintain the above sequence when turning on and off the power supply of the module. If DISPOFF is supplied to the module while internal alternate signal for LCD driving (M) is unstable, DC component will be supplied to the LCD panel. This may cause damage the LCD module.

2.7. Lighting Specifications

Ta=25°C

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units	Notes
Lamp Voltage	V _L	—	—	325	—	Vrms	1
Lamp Current	I _L	—	4.0	5.0	6.0	mA _{rms}	2
Starting Voltage	V _S	—	800	—	—	Vrms	3
Surface Luminance	L	I _L =5.0mA	—	55	—	cd/m ²	4
Average Life	T _{AL}	I _L =5.0mA	—	15000	—	hrs	5


Note 1 : The voltage (r.m.s.) to maintain the electric discharge of the lamp. It is measured after lighting for 3 minutes .

Note 2 : The current (r.m.s.) to flow through the lamp with the electric discharge. It is measured after lighting for 3 minutes.


Note 3 : The voltage at starting the electric discharge when the voltage is increased gradually from 0V.

Note 4 : Surface Luminance is specified by the average of 9 luminance values measured at each point shown above after 20 minutes power on with the all ON pattern adjusted to maximum contrast and the dimming control of 100%. (maximum brightness)

Note 5 : CFL life is defined as the time for which the initial luminance is attenuated by 50% of the luminance value. Average Life represents the time elapsed at the point of time when the residual ratio becomes below 50% when plural lamps are lighted in comparison with the definition of life mentioned above.



CFL Testing Circuit



Measurement Points

3. Optical Specifications

3.1. LCD Driving Voltage

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Recommended LCD Driving Voltage Note 1	$V_{SS}-V_{EE}$	$T_a = 0^{\circ}\text{C}$	—	—	22.3	V
		$T_a = 25^{\circ}\text{C}$	17.5	18.8	20.1	V
		$T_a = 50^{\circ}\text{C}$	15.6	—	—	V

Note 1 : Voltage (Applied actual waveform to LCD Module) for the best contrast. The range of minimum and maximum shows tolerance of the operating voltage. The specified contrast ratio and response time are not guaranteed over the entire range.

3.2. Optical Characteristics

$T_a = 25^{\circ}\text{C}$, 1/200Duty, 1/14Bias, $V_D = 21.8\text{V}$ (Note 4), $\theta = 0^{\circ}$, $\phi = -^{\circ}$

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Contrast Ratio Note 1	CR	$\theta = 0^{\circ}$, $\phi = -^{\circ}$	—	12	—	
Viewing Angle		Shown in 3.3				
Response Time	Rise Note 2	T_{ON}	—	190	290	ms
	Decay Note 3	T_{OFF}	—	230	350	ms

Note 1 : Contrast ratio is defined as follows.

$$CR = L_{ON} / L_{OFF}$$

L_{ON} : Luminance of the ON segments

L_{OFF} : Luminance of the OFF segments


Note 2 : The time that the luminance level reaches 90% of the saturation level from 0% when ON signal is applied.

Note 3 : The time that the luminance level reaches 10% of the saturation level from 100% when OFF signal is applied.

Note 4 : Definition of Driving Voltage V_D


$$V_D = V_{CC} - V_{ADJ} - V_{BE}$$

Assuming that the typical driving waveforms shown below are applied to the LCD Panel at 1/A Duty - 1/B Bias (A : Duty Number, B : Bias Number). Driving voltage V_D is defined as the voltage V_{O-P} when the contrast ratio ($CR = L_{ON} / L_{OFF}$) is at its maximum.




3.3. Definition of Viewing Angle and Optimum Viewing Area

- Point ● shows the point where contrast ratio is measured. : $\theta = 0^\circ$, $\phi = -^\circ$
- Driving condition : 1/200Duty, 1/14Bias, $V_D = 21.8V$, $f_F = 70.0Hz$



3.4. System Block Diagram



4. I/O Terminal

4.1. Pin Assignment

CN1


No.	Symbol	Level	Function
1	FLM	H / L	First Line Marker
2	LP	H / L	Data Latch Signal
3	CP	H / L	Clock Signal for Shifting Data
4	$\overline{\text{DISPOFF}}$	H / L	Display Control Signal H : Display on L : Display off
5	V _{CC}	—	Power Supply for Logic
6	V _{SS}	—	Power Supply (0V, GND)
7	V _{EE}	—	Power Supply for LCD Drive
8	DU0	H / L	Display Upper Data
9	DU1	H / L	Display Upper Data
10	DU2	H / L	Display Upper Data
11	DU3	H / L	Display Upper Data
12	DL0	H / L	Display Lower Data
13	DL1	H / L	Display Lower Data
14	DL2	H / L	Display Lower Data
15	DL3	H / L	Display Lower Data

CN2

No.	Symbol	Level	Function
1	CFLOUT1 (HOT)	—	Power Supply for CFL (HOT)
2	NC	—	Non-connection
3	NC	—	Non-connection
4	CFLOUT1 (GND)	—	Power Supply for CFL (GND)

4.2.Example of Power Supply


It is recommended to apply a potentiometer for the contrast adjust due to the tolerance of the driving voltage and its temperature dependence.



$$R1+R2+VR=10\sim20K\ \Omega$$


$$Tr=2SA1202\text{ or equivalent}$$

4.3.Block Diagram



5. Test

No change on display and in operation under the following test condition.

No.	Parameter	Conditions	Notes
1	High Temperature Operating	50°C ± 2°C, 96hrs (operation state)	
2	Low Temperature Operating	0°C ± 2°C, 96hrs (operation state)	3
3	High Temperature Storage	60°C ± 2°C, 96hrs	4
4	Low Temperature Storage	-20°C ± 2°C, 96hrs	3, 4
5	Damp Proof Test	40°C ± 2°C, 90~95% RH, 96hrs	3, 4
6	Vibration Test	Total fixed amplitude : 1.5mm Vibration Frequency : 10~55Hz One cycle 60 seconds to 3 directions of X, Y, Z for each 15 minutes	5
7	Shock Test	To be measured after dropping from 60cm high on the concrete surface in packing state. 	

Note 1 : Unless otherwise specified, tests will be conducted under the following condition.

Temperature : 20 ± 5°C

Humidity : 65 ± 5%

Note 2 : Unless otherwise specified, tests will be not conducted under functioning state.

Note 3 : No dew condensation to be observed.

Note 4 : The function test shall be conducted after 4 hours storage at the normal temperature and humidity after removed from the test chamber.

Note 5 : Vibration test will be conducted to the product itself without putting it in a container.


6. Appearance Standards

6.1. Inspection conditions


The LCD shall be inspected under 40W white fluorescent light.

The distance between the eyes and the sample shall be more than 30cm.

All directions for inspecting the sample should be within 45° against perpendicular line.



6.2. Definition of applicable Zones



A Zone : Active display area





B Zone : Area from outside of "A Zone" to validity viewing area

C Zone : Rest parts

A Zone + B Zone = Validity viewing area


6.3.Standards

No.	Parameter	Criteria																											
1	Black and White Spots, Foreign Substances	(1) Round Shape																											
		<table><tr><th rowspan="2"><div>Zone</div><div>Dimension (mm)</div></th><th colspan="3">Acceptable Number</th></tr><tr><th>A</th><th>B</th><th>C</th></tr><tr><td>$D \leq 0.1$</td><td>*</td><td>*</td><td>*</td></tr><tr><td>$0.1 < D \leq 0.2$</td><td>3</td><td>5</td><td>*</td></tr><tr><td>$0.2 < D \leq 0.3$</td><td>2</td><td>3</td><td>*</td></tr><tr><td>$0.3 < D \leq 0.35$</td><td>0</td><td>1</td><td>*</td></tr><tr><td>$0.35 < D$</td><td>0</td><td>0</td><td>*</td></tr></table>	<div>Zone</div> <div>Dimension (mm)</div>	Acceptable Number			A	B	C	$D \leq 0.1$	*	*	*	$0.1 < D \leq 0.2$	3	5	*	$0.2 < D \leq 0.3$	2	3	*	$0.3 < D \leq 0.35$	0	1	*	$0.35 < D$	0	0	*
		<div>Zone</div> <div>Dimension (mm)</div>		Acceptable Number																									
			A	B	C																								
		$D \leq 0.1$	*	*	*																								
		$0.1 < D \leq 0.2$	3	5	*																								
		$0.2 < D \leq 0.3$	2	3	*																								
		$0.3 < D \leq 0.35$	0	1	*																								
		$0.35 < D$	0	0	*																								
		$D = (\text{ Long } + \text{ Short }) / 2$ * : Disregard																											
(2) Line Shape																													
<table><tr><th rowspan="2"><div>Zone</div><div>X (mm) Y (mm)</div></th><th colspan="3">Acceptable Number</th></tr><tr><th>A</th><th>B</th><th>C</th></tr><tr><td><div>—</div><div>$0.03 \geq W$</div></td><td>*</td><td>*</td><td>*</td></tr><tr><td><div>$2.0 \geq L$</div><div>$0.05 \geq W$</div></td><td>4</td><td>4</td><td>*</td></tr><tr><td><div>$1.0 \geq L$</div><div>$0.1 \geq W$</div></td><td>4</td><td>4</td><td>*</td></tr><tr><td><div>—</div><div>$0.1 < W$</div></td><td colspan="3">In the same way (1)</td></tr></table>	<div>Zone</div> <div>X (mm) Y (mm)</div>	Acceptable Number			A	B	C	<div>—</div> <div>$0.03 \geq W$</div>	*	*	*	<div>$2.0 \geq L$</div> <div>$0.05 \geq W$</div>	4	4	*	<div>$1.0 \geq L$</div> <div>$0.1 \geq W$</div>	4	4	*	<div>—</div> <div>$0.1 < W$</div>	In the same way (1)								
<div>Zone</div> <div>X (mm) Y (mm)</div>		Acceptable Number																											
	A	B	C																										
<div>—</div> <div>$0.03 \geq W$</div>	*	*	*																										
<div>$2.0 \geq L$</div> <div>$0.05 \geq W$</div>	4	4	*																										
<div>$1.0 \geq L$</div> <div>$0.1 \geq W$</div>	4	4	*																										
<div>—</div> <div>$0.1 < W$</div>	In the same way (1)																												
$X : \text{Length} \quad Y : \text{Width} \quad * : \text{Disregard}$																													
Total defects shall not exceed 7.																													
2	Air Bubbles (between glass & polarizer)	<table><tr><th rowspan="2"><div>Zone</div><div>Dimension (mm)</div></th><th colspan="3">Acceptable Number</th></tr><tr><th>A</th><th>B</th><th>C</th></tr><tr><td>$D1, D2 \leq 0.3$</td><td>*</td><td>*</td><td>*</td></tr><tr><td>$0.3 < D1, D2 \leq 0.5$</td><td>3</td><td>*</td><td>*</td></tr><tr><td>$0.5 < D1 \leq 0.7$</td><td>2</td><td>3</td><td>*</td></tr><tr><td>$0.5 < D2 \leq 0.6$</td><td>2</td><td>3</td><td>*</td></tr><tr><td>$0.7 < D1, 0.6 < D2$</td><td>0</td><td>0</td><td>*</td></tr></table>	<div>Zone</div> <div>Dimension (mm)</div>	Acceptable Number			A	B	C	$D1, D2 \leq 0.3$	*	*	*	$0.3 < D1, D2 \leq 0.5$	3	*	*	$0.5 < D1 \leq 0.7$	2	3	*	$0.5 < D2 \leq 0.6$	2	3	*	$0.7 < D1, 0.6 < D2$	0	0	*
		<div>Zone</div> <div>Dimension (mm)</div>		Acceptable Number																									
			A	B	C																								
		$D1, D2 \leq 0.3$	*	*	*																								
		$0.3 < D1, D2 \leq 0.5$	3	*	*																								
		$0.5 < D1 \leq 0.7$	2	3	*																								
		$0.5 < D2 \leq 0.6$	2	3	*																								
		$0.7 < D1, 0.6 < D2$	0	0	*																								
		$D1 : \text{Small foam a gathering} \quad D2 : \text{Single foam} \quad * : \text{Disregard}$																											
		Total defects shall not exceed 5.																											

No.	Parameter	Criteria
3	The Shape of Dot	<p>(1) Dot Shape (with Dent)</p>  <p>As per the sketch of left hand.</p>
		<p>(2) Dot Shape (with Projection)</p>  <p>Should not be connected to next dot.</p>
		<p>(3) Pin Hole</p>  <p> $(X+Y) / 2 \leq 0.2\text{mm}$ (Less than 0.1mm is no counted.) </p>
		<p>(4) Deformation</p>  <p> $(X+Y) / 2 \leq 0.2\text{mm}$ </p>
		<p>Total acceptable number : 1/dot, 5/cell (Defect number of (4) : 1pc.)</p>
4	Polarizer Scratches	Not to be conspicuous defects.
5	Polarizer Dirts	If the stains are removed easily from LCDP surface, the module is not defective.
6	Complex Foreign Substance Defects	Black spots, line shaped foreign substances or air bubbles between glass & polarizer should be 7pcs maximum in total.
7	Distance between Different Foreign Substance Defects	$D \leq 0.2$: 20mm or more $0.2 < D$: 40mm or more


7. Code System of Production Lot

The production lot of module is specified as follows.



8. Type Number

The type number of module is specified on the back of module as follows.



9. Applying Precautions

Please contact us when questions and/or new problems not specified in this specifications arise.

10. Handling Precautions

Optrex Products are designed for use in ordinary electronic devices such as business machines, telecommunications equipment, measurement devices and etc..

Optrex Products are not designed, intended, or authorized for use in any application in which the failure of the product could result in a situation where personal injury or death may occur. These applications include, but are not limited to, life-sustaining equipment, nuclear control devices, aerospace equipment, devices related to hazardous or flammable materials, etc. (If Buyer intends to purchase or use the Optrex Products for such unintended or unauthorized applications, Buyer must secure prior written consent to such use by a responsible officer of Optrex Corporation.) Should Buyer purchase or use Optrex Products for any such unintended or unauthorized application (without such consent), Buyer shall indemnify and hold Optrex and its officers, employees, subsidiaries, affiliates and distributors harmless against all claims, costs, damages and expenses, and reasonable attorney's fees, arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Optrex was negligent regarding the design or manufacture of the part.

- 1) LCD may be broken because it is made of glass.
- 2) Polarizer is a soft material and can easily be scratched.
- 3) Please avoid static electricity.
 - ① Please be sure to ground human body and electric appliances during work.
 - ② It is preferable to use conductive mat on table and wear cotton clothes or conduction processed fiber. Synthetic fiber is not recommended.
 - ③ Please slowly peel off protective film, because static electricity may be charged.
- 4) If it is necessary to store LCD modules for a long time, please comply with the following procedures. If storage condition is not satisfactory, display (especially polarizer) may be deteriorated or soldering I/O terminals may become difficult (some oxide is generated at I/O terminals plating).
 - ① Store as delivered by Optrex
 - ② If you store as unpacked, put in anti-static bag, seal its opening and store where it is not subjected to direct sunshine nor fluorescent lamp.
 - ③ Store at temperature 0 to +35°C and at low humidity. Please refer to our specification sheets for storage temperature range and humidity condition.
- 5) The module does not contain excess current limiter.
Please design the limiter to cut excess current in your power supply circuit.
- 6) Liquid crystal may be leaked when display is broken. Never taste it. If your hands or clothes touch it, please immediately wash using soap.
- 7) The connection between the bezel and Vss (GND) is not specified in the module.
(Some module do not maintain connection between them.)
Please consult OPTREX to specify the connection.
- 8) A high voltage over 1000V is applied at the connector of CFL cable when the CFL inverter is connected and energized. Please do not touch there incidentally or accidentally to avoid a skin burn.
And please set the cable properly in the housing to avoid a worn-out of isolated cover of cable wire.

Optrex shall not be responsible for any infringement of industrial property rights of third parties in any country arising out of the application or use of Optrex Products, except which directly concern the structure or production of such products.