



160 School House Road, Souderton, PA 18964-9990 USA
Phone 215-723-8181 • FAX 215-723-5688

MODEL DC7620
DUAL DIRECTIONAL COUPLER
200 WATTS CW
26.5 - 40 GHz

The Model DC7620 is a dual directional coupler with excellent frequency range and power handling capability. The wide range assures flexibility in coupling medium power amplifiers to oscilloscopes, voltmeters, power meters, spectrum analyzers and other measuring instruments. The dual directional design allows the user to monitor both forward and reflected power, a much needed characteristic in RF susceptibility testing for amplifier overdrive protection, field control and load protection. Low insertion loss allows efficient coupling to the load. The DC7620 is intended for use with the 25T26G40, 40T26G40 and other "T" series microwave TWT amplifiers.

SPECIFICATIONS
Model DC7620

<i>FREQUENCY RANGE</i>	26.5-40GHz
<i>POWER (maximum)</i>	200 Watts CW 30K Watts Peak
<i>COUPLING FACTOR</i>	40 dB \pm 2.0 dB (includes flatness)
<i>COUPLING LFATENSS</i>	\pm 1.0dB
<i>DIRECTIVITY</i>	
<i>Typical</i>	28 dB
<i>Minimum</i>	23 dB
<i>INSERTION LOSS</i>	0.26 dB maximum
<i>VSWR (Main Line)</i>	VSWR 1.15:1 maximum
<i>CONNECTORS</i>	
<i>Main Line</i>	EIA WR28
<i>Coupled</i>	K female
<i>WEIGHT</i>	113 g (4 oz.)
<i>SIZE (WxHxD)</i>	3.5 x 1.9 x 14 cm 1.4 x 0.75 x 5.50 in

REV072298

