







Telecommunication MODEM Transformer Transformers

DT43-7023



XXXX : DATE CODE
BLACK DOT ON PIN 1



DIMENSIONS IN mm

A	B	C	D	E	F	G
12.0 MAX.	2.8±0.5	7.62±0.15	12.7±0.20	16.5 MAX.	16.5 MAX.	

ELECTRICAL CHARACTERISTICS	
URNS RATIO	1:1±1% @1KHz, 1V
INDUCTANCE	28H Min. @250Hz, 1V PARALLEL
IMPEDANCE	600 Ω ±10% @1KHz, 1V
PHASE	±10 deg. @70Hz~4.0KHz
D.C. RESISTANCE	PRI: 135 Ω ±10% SEC: 145 Ω ±10%
INSERTION LOSS	2.7 dB Max. @1KHz, 0 dBm
FREQUENCY RESPONSE	± 0.1 dB @70Hz~4.0KHz
RETURN LOSS	20 dB Min. @200Hz~4KHz
LONGITUDINAL BALANCE	60 dB Min. @200Hz~4KHz
TOTAL HARMONIC	-84 dB Max. @150Hz, -10 dBm
DIELECTRIC STRENGTH	1500 VAC, 2 SEC @PRI TO SEC

DELTA ELECTRONICS, INC.

(TAOYUAN PLANT CPBG) 31-1, SHIEN PAN ROAD, KUEI SAN INDUSTRIAL ZONE, TAOYUAN SHIEN, TAIWAN, R.O.C.

TEL: 886-3-3626301 FAX: 886-3-3618901

http://www.deltaww.com