




Telecommunication MODEM Transformer Transformers

DT43-7034



DIMENSIONS IN mm

A	B	C	D	E	F	G
12.8 TYP.	3.0 MIN.	7.62 $\pm$ 0.15	12.7 $\pm$ 0.20	18.1 MAX.	18.1 MAX.	

ELECTRICAL CHARACTERISTICS	
URNS RATIO	1:1 $\pm$ 1% @1KHz, 1V
INDUCTANCE	28H Min. @250Hz, 1V PARALLEL
IMPEDANCE	600 Ω $\pm$ 10% @1KHz, 1V
PHASE	$\pm$ 10 deg. @70Hz~4.0KHz
D.C. RESISTANCE	PRI: 135 Ω $\pm$ 10% SEC: 145 Ω $\pm$ 10%
INSERTION LOSS	2.7 dB @1KHz, 0 dBm
FREQUENCY RESPONSE	$\pm$ 0.1 dB @70Hz~4.0KHz
RETURN LOSS	20 dB Min. @200Hz~4KHz
LONGITUDINAL BALANCE	60 dB Min. @200Hz~4KHz
TOTAL HARMONIC	-84 dB Max. @150Hz, -10 dBm
DIELECTRIC STRENGTH	1500 VAC, 2 SEC @PRI TO SEC

DELTA ELECTRONICS, INC.

(TAOYUAN PLANT CPBG) 31-1, SHIEN PAN ROAD, KUEI SAN INDUSTRIAL ZONE, TAOYUAN SHIEN, TAIWAN, R.O.C.

TEL: 886-3-3626301 FAX: 886-3-3618901

<http://www.deltaww.com>