




Telecommunication COMMON MODE CHOKE Transformers

DT35-1301AT
DT35-1302AT
DT35-1303AT
DT35-1304AT



DIMENSIONS IN mm

A	B	C	D	E	F	G
17.0 MAX.	16.5 MAX.	13.45 MAX.	11.2 MAX.	2.54~4.3		

ELECTRICAL CHARACTERISTICS

	DT35-1301AT	DT35-1302AT	DT35-1303AT	DT35-1304AT
T.R	(N1:N2): 1:1±5% @10KHz 0.1V	(N1:N2): 1:1±5% @10KHz 0.1V	(N1:N2): 1:1±5% @10KHz 0.1V	(N1:N2): 1:1±5% @10KHz 0.1V
L	N1: 93uH ± 5% @10KHz 0.1V 100mA	N1: 308uH ± 5% @10KHz 0.1V 100mA	N1: 403uH ± 5% @10KHz 0.1V 100mA	N1: 70uH ± 5% @10KHz 0.1V 100mA
L.K	8.0uH Max. @100KHz 1V	9.24uH Max. @100KHz 1V	12.1uH Max. @100KHz 1V	6.3uH Max. @100KHz 1V
C	40pF Max. @100KHz 1V	40pF Max. @100KHz 1V	40pF Max. @100KHz 1V	60pF Max. @100KHz 1V
D.C.R	N1: 0.4Ω Max. N2: 0.4Ω Max.	N1: 1.0Ω Max. N2: 1.0Ω Max.	N1: 1.2Ω Max. N2: 1.2Ω Max.	N1: 0.15Ω Max. N2: 0.35Ω Max.
HI-POT	1500 VAC 2 SEC	1500 VAC 2 SEC	1500 VAC 2 SEC	1500 VAC 2 SEC
SCHEMATIC	1	1	1	1

DELTA ELECTRONICS, INC.

(TAOYUAN PLANT CPBG) 31-1, SHIEN PAN ROAD, KUEI SAN INDUSTRIAL ZONE, TAOYUAN SHIEN, TAIWAN, R.O.C.

TEL: 886-3-3626301 FAX: 886-3-3618901

http://www.deltaww.com