




Telecommunication

COMMON MODE CHOKE

Transformers

DT35-2009T
DT35-2013T
DT35-2018T



DIMENSIONS IN mm

A	B	C	D	E	F	G
12.7 MAX.	2.79 MIN.	14.0 MAX.	14.0 MAX.	10.16±0.3	2.54±0.3	

ELECTRICAL CHARACTERISTICS

	DT35-2009T	DT35-2013T	DT35-2018AT
T.R	(N1:N2): 1:1±4% @100KHz 0.1V	(N1:N2): 1:1±1% @10KHz 0.1V	(N1:N2): 1:1±1% @10KHz 0.1V
L	PRI: 6.0mH ±5% @10KHz 0.1V	PRI: 5.5mH ±10% @10KHz 1V Idc=160mA	PRI: 5.5mH ±5% @10KHz 1V
L.K	-----	-----	-----
C	-----	-----	-----
D.C.R	N1: 3.5Ω Max. N2: 3.5Ω Max.	N1: 4.75Ω Max. N2: 4.75Ω Max.	N1: 6.25Ω Max. N2: 6.25Ω Max.
HI-POT	1200 VAC 2 SEC	850 VAC 1 SEC	500uA Max. 1000 VAC 1 SEC
SCHEMATIC	1	2	2

DELTA ELECTRONICS, INC.

(TAOYUAN PLANT CPBG) 31-1, SHIEN PAN ROAD, KUEI SAN INDUSTRIAL ZONE, TAOYUAN SHIEN, TAIWAN, R.O.C.

TEL: 886-3-3626301 FAX: 886-3-3618901

http://www.deltaww.com