




Telecommunication COMMON MODE CHOKE Transformers

DT35-8005
DT35-8006
DT35-8007



DIMENSIONS IN mm

A	B	C	D	E	F	G
15.0 MAX.	4.0± 0.3	8.8± 0.2	2.54± 0.2	11.0 MAX.	30.0 MAX.	

ELECTRICAL CHARACTERISTICS

	DT35-8005	DT35-8006	DT35-8007
T.R	(PRI:SEC): 1:1± 1% @10KHz 0.1V	(PRI:SEC): 1:1± 1% @10KHz 0.1V	(PRI:SEC): 1:1± 1% @10KHz 0.1V
L	N1: 185uH±10% N2: 620uH±10% @10KHz 0.1V 160mA	N1: 210uH±10% N2: 730uH±10% @10KHz 0.1V 160mA	N1: 110uH±10% N2: 380uH±10% @10KHz 0.1V 160mA
L.K	N1: 250nH Max. N2: 500nH Max. @100KHz 0.1V	N1: 350nH Max. N2: 650nH Max. @100KHz 0.1V	N1: 400nH Max. N2: 400nH Max. @100KHz 0.1V
C	N1: 40pF Max. N2: 80pF Max. @300KHz 0.1V	N1: 40pF Max. N2: 80pF Max. @300KHz 0.1V	N1: 50pF Max. N2: 70pF Max. @300KHz 0.1V
D.C.R	N1:N3: 0.36Ω Max. N2:N4: 0.65Ω Max.	N1:N3: 0.4Ω Max. N2:N4: 0.6Ω Max.	N1:N3: 0.35Ω Max. N2:N4: 0.6Ω Max.
HI-POT	500 VAC 60 SEC	500 VAC 60 SEC	500 VAC 60 SEC
SCHEMATIC	1	1	1

DELTA ELECTRONICS, INC.

(TAOYUAN PLANT CPBG) 31-1, SHIEN PAN ROAD, KUEI SAN INDUSTRIAL ZONE, TAOYUAN SHIEN, TAIWAN, R.O.C.

TEL: 886-3-3626301 FAX: 886-3-3618901

<http://www.deltaww.com>