






Telecommunication COMMON MODE CHOKE Transformers

DT35-8606AT
DT35-8607AT
DT35-8608AT
DT35-8609AT



DIMENSIONS IN mm

A	B	C	D	E	F	G
7.5 MAX.	6 Typ.	4.0 MAX.				

ELECTRICAL CHARACTERISTICS

	DT35-8606AT	DT35-8607AT	DT35-8608AT	DT35-8609AT
T.R	(PRI:SEC): 1:1 ±1% @100KHz 0.1V	(PRI:SEC): 1:1 ±1% @100KHz 0.1V	(PRI:SEC): 1:1 ±1% @100KHz 0.1V	(PRI:SEC): 1:1 ±1% @100KHz 0.1V
L	4.8~5.6uH @100KHz 0.1V	9.8~10.8uH @100KHz 0.1V	10.9~12uH @100KHz 0.1V	2.7~3.0uH @100KHz 0.1V
D.C.R	PRI: 0.4Ω Max. SEC: 0.4Ω Max.	PRI: 0.4Ω Max. SEC: 0.4Ω Max.	PRI: 0.4Ω Max. SEC: 0.4Ω Max.	PRI: 0.3Ω Max. SEC: 0.3Ω Max.
HI-POT	500 VAC 60 SEC	500 VAC 60 SEC	500 VAC 60 SEC	500 VAC 60 SEC
SCHEMATIC	1	1	1	1

DELTA ELECTRONICS, INC.

(TAOYUAN PLANT CPBG) 31-1, SHIEN PAN ROAD, KUEI SAN INDUSTRIAL ZONE, TAOYUAN SHIEN, TAIWAN, R.O.C.

TEL: 886-3-3626301 FAX: 886-3-3618901

http://www.deltaww.com