




Telecommunication

ISDN U_{KO} Transformer





Transformers

DT23-1307

DT23-1307
MARKING: • DELTAXXXX



XXXX: DATE CODE
WHITE DOT ON PIN1



DIMENSIONS IN mm

A	B	C	D	E	F	
12.8 MAX.	20 MAX.	22.0 MAX.	4.9± 0.2	3.7± 0.2	18.0±0.2.	

ELECTRICAL CHARACTERISTICS

URNS RATIO (PRI:SEC)	1.6 : 1 ± 2% @10KHz, 1V
INDUCTANCE	PRI: 13.3 mH ± 10% @10KHz, 1V Idc=60mA
LEAKAGE INDUCTANCE	70 uH Max. @100KHz, 0.1V
D.C. RESISTANCE	PRI: 4.9 Ω Max. SEC: 4.8 Ω Max.
INTERWINDING CAPACITANCE	90 pF Max. @10KHz, 0.1V
DIELECTRIC STRENGTH	2000 VAC, 2 SEC @PRI TO SEC 500 VAC, 2 SEC @WDG TO CORE

DELTA ELECTRONICS, INC.

(TAOYUAN PLANT CPBG) 31-1, SHIEN PAN ROAD, KUEI SAN INDUSTRIAL ZONE, TAOYUAN SHIEN, TAIWAN, R.O.C.

TEL: 886-3-3626301 FAX: 886-3-3618901

<http://www.deltaww.com>