



Endicott Research Group, Inc.

2601 Wayne St., Endicott NY 13760

607-754-9187 Fax 607-754-9255

<http://www.ergpower.com>

DMC42632

Specifications and Applications Information


05/09/02

Preliminary

Four Tube DC to AC Inverter

The ERG DMC42632 (DMC4 Series) DC to AC inverter features onboard connectors and can be easily dimmed using an external pulse-width modulated control signal. This unit is less than 13mm in height and the two mounting holes makes installation very straight forward.

Powered by a regulated 12 volt DC source the DMC42632 is specially designed to power the Toshiba LTM12C285 backlights.



DMC4 Package


Product Features

- ✓ Small Package Size, less than 13mm in height.
- ✓ High Efficiency
- ✓ Made in U.S.A.

Connectors

J1 - (Input) MOLEX 532-61-0890	J2a,J3a - (Outputs) N/A	
	J2a,J3a-1 J2a,J3a-2	N/A N/A
J1-1 V_{in} J1-2 V_{in} J1-3 GND J1-4 GND J1-5 Enable J1-6 N/C J1-7 N/C J1-8 N/C	J2b,J3b - (Outputs) JST SM04(4.0)B-BHS-1-TB	
	J2b, J3b-1	AC_{out}
	J2b, J3b-2	AC_{out}
	J2b, J3b-3	N/C
	J2b, J3b-4	AC_{com}

Package Configuration





Absolute Maximum Ratings ^(Note 1)

Rating	Symbol	Value	Units
Input Voltage	V_{in}	-0.3 to +13.2	Vdc
Enable	V_{Enable}	-0.3 to +0.3	Vdc
Operating Temperature	T_a	-0 to +85	°C
Storage Temperature	T_s	-40 to +85	°C

Recommended Operating Conditions

Rating	Symbol	Value	Units
Input Voltage	V_{in}	+6 to 13.2	Vdc
Operating Temperature ^(Note 2)	T_a	0 to +50	°C

Electrical Characteristics

Unless otherwise noted $V_{in} = 12.00$ Volts dc and $T_a = 25^{\circ}\text{C}$

Characteristic	Symbol	Min	Typ	Max	Units
Input Current	I_{in}	-	1.7	2.0	A_{DC}
Input Ripple Current	I_{rip}	-	-	-	mA_{pk-pk}
Operating Frequency	F_o	35	40	45	KHz
Efficiency	η	-	83	-	%
Output Voltage (no load) ^(Note 3)	V_{start}	1500	-	-	V
Output Voltage (with lamp)	V_{out}	-	690	-	V
Output Current (per tube)	I_{out}	-	6.1	-	mArms
Enable (pin J1-5)					
Turn-off Threshold	V_{thoff}	-	-	.7	V
Turn-On Threshold	V_{thon}	2	-	-	V

(Note 1) Reliable and predictable operation of the device are not guaranteed with applied stresses at or beyond those listed in "Absolute Maximum Ratings". Operation at these limits may reduce device reliability and is therefore not recommended. Please refer to "Recommended Operating Conditions" for reliable operation of the device.

(Note 2) Operation above 50°C is possible if airflow is provided.

(Note 3) Provided data is not tested but guaranteed by design.