




- 1 Series name
- 2 Single output
- 3 Output wattage
- 4 Universal input
- 5 Output voltage


TRC Electronics, Inc.
 Authorized Stocking Distributor
 Tel: 973.779.8282
 Fax: 973.779.1490
 Contact TRC for pricing,
 stock, and technical assistance.
www.trcelectronics.com

MODEL	DPA500F-360	
AC INPUT[V]	AC85 - 264	AC170 - 264
MAX OUTPUT WATTAGE[W]	500	750
DC OUTPUT VOLTAGE[V]	DC300 - 360	

SPECIFICATIONS


	MODEL	DPA500F-360	
INPUT	VOLTAGE[V]	AC100/120	AC200/240
	VOLTAGE RANGE[V]	AC85 - 170	AC170 - 264
	POWER FACTOR CORRECTION RANGE[V]	AC85 - 255	
	CURRENT[A]	5.6typ (ACIN 100V)	4.0typ (ACIN 200V)
	FREQUENCY[Hz]	47 - 63	
	APPARENT POWER[VA]	560typ (ACIN 100V)	800typ (ACIN 200V)
	INRUSH CURRENT[A]	15typ (ACIN 100V)	30typ (ACIN 200V)
	EFFICIENCY[%]	90typ (ACIN 100V)	95typ (ACIN 200V)
	POWER FACTOR	0.98typ (Complies with IEC61000-3-2)	
	LEAKAGE CURRENT[ma]	Less than 0.3	
OUTPUT	WATTAGE[W]	500	750
	VOLTAGE[V]	DC300 - 360 (Automatically changes according to input voltage)	
PROTECTION CIRCUIT AND OTHERS	OVERVOLTAGE PROTECTION[V]	DC390 - 440	
	IOG	Inverter operation monitoring, Open-collector output, Maximum sink current 5mA, Maximum allowance voltage 35V	
	PR	Power-ready signal, Open-collector output, Maximum sink current 5mA, Maximum allowance voltage 35V	
	AUX	Auxiliary power supply for external signal, Output voltage:10 - 20V maximum, Output current:10mA	
	OTHERS	Inrush current protection, Parallel operation possible (Current balancing function), Thermal protection	
ISOLATION	INPUT-OUTPUT	Non isolated	
	INPUT-FG	AC3.000V 1minute, Cutoff current = 10mA, DC500V 50MW min (At Room Temperature)	
	OUTPUT-FG	AC3.000V 1minute, Cutoff current = 10mA, DC500V 50MW min (At Room Temperature)	
ENVIRONMENT	OPERATING TEMP., HUMID. AND ALTITUDE	-20 to +85°C (Aluminum base plate), 20 - 95%RH (Non condensing) (Refer to DERATING CURVE), 3,000m (10,000feet) max	
	STORAGE TEMP., HUMID. AND ALTITUDE	-40 to +85°C, 20 - 95%RH (Non condensing), 9,000m (30,000feet) max	
	VIBRATION	10 - 55Hz, 49.0m/s ² (5G), 3minutes period, 60minutes each along X, Y and Z axis	
	IMPACT	196.1m/s ² (20G), 11ms, once each X, Y and Z axis	
SAFETY	AGENCY APPROVALS	UL1950, CSA C22.2 No.234, EN60950, VDE0160 Complies with DEN-AN and IEC60950	
OTHERS	CASE SIZE/WEIGHT	58 x 12.7 x 130mm (W x H x D) / 150g max	
	COOLING METHOD	Conduction cooling (e.g. heat radiation from the aluminum base plate to the attached heat sink)	

External view




Performance data


■ STATIC CHARACTERISTICS



■ OUTPUT VOLTAGE FOR INPUT



■ HARMONIC CURRENT (AC100V)



■ HARMONIC CURRENT (AC200V)

