

Product Information

Model Number: *DWDM 200G Series*
 Description: *16 Channel 200GHz Wavelength
 Division Multiplexer / DeMultiplexer*


Selected Features

- 200GHz Channel Spacing
- High Channel Isolation
- Low Polarization Dependent Loss
- Low Insertion Loss
- High Reliability
- Compact Size



Selected Applications

- Dense WDM Systems
- Multiplexing and De-multiplexing
- Fiber Amplifier System
- CATV Fiberoptic Links
- EDFA System
- Sensors



Functional Diagram

Performance Specifications

Channel Center Frequency	ITU grids
Number of Channel	16
1 dB Band Width	>0.35nm
Insertion Loss	<6 dB (without connector loss)
Pass Band Ripple	0.5dB
Uniformity	1dB
PDL	<0.3dB

DWDM 200G 16CH

PMD	<0.3ps
Directivity	>50dB
Return Loss	>50dB
Adjacent Channel Isolation	>25dB
Nonadjacent Channel Isolation	>35dB
Total Cross Talk	>25dB
Within Band Chromatic Dispersion	<5ps


Environmental Specifications

Operation Temp.	-5~65°C
Humidity	0~85% RH
Storage Temperature	-40~85°C


Mechanical & Packaging Specifications

Package Dimension	120 x 90 x 15mm ³
Fiber Type	900um
Pigtail Length	100±5cm
Optional Connector	To Be Specified


Packaging Dimensions



Typical Response



DWDM Ordering Part Number System



The content of this document is the proprietary and confidential information to Primanex Corporation. No part of this document may be disclosed to or used by, in digital or print format, any third party without the prior written consent from Primanex Corporation. All rights reserved.

41946 Christy Street, Fremont, CA 94538 Tel (510) 226-7252 Fax (510) 226-7258 Sales@primanex.com