

D5SB60

600V 6A


FEATURES

- Thin Single In-Line Package
- High IFSM
- Applicable to Automatic Insertion

APPLICATION

- Switching power supply
- Home Appliances, Office Equipment
- Telecommunication, Factory Automation

OUTLINE DIMENSIONS



RATINGS

●Absolute Maximum Ratingss (If not specified Tc=25°C)


Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	Tstg		-40~150	°C
Operating Junction Temperature	Tj		150	°C
Maximum Reverse Voltage	V _{RM}		600	V
Average Rectified Forward Current	I _O	50Hz sine wave, R-load With heatsink Tc=111°C	6	A
		50Hz sine wave, R-load Without heatsink Ta=25°C	2.8	
Peak Surge Forward Current	I _{FSM}	50Hz sine wave, Non-repetitive 1cycle peak value, Tj=25°C	170	A
Current Squared Time	I ² t	2ms≤t<10ms Tj=25°C	140	A ² s
Dielectric Strength	V _{dis}	Terminals to case, AC 1 minute	2	kV
Mounting Torque	TOR	(Recommended torque:0.5N·m)	0.8	N·m

●Electrical Characteristics (If not specified Tc=25°C)

Item	Symbol	Condi ti ons	Rat ings	Uni t
Forward Voltage	V _F	IF=3A, Pulse measurement, Rating of per diode	Max.1.05	V
Reverse Current	I _R	V _R =V _{RM} , Pulse measurement, Rating of per diode	Max.10	μ A
Thermal Resistance	θ ic	junction to case With heatsink	Max.3.4	°C/W
	θ jl	junction to lead Without heatsink	Max.5	
	θ ja	junction to ambient Without heatsink	Max.26	


D5SBx

Forward Voltage



D5SBx

Forward Power Dissipation




$T_j = 150^{\circ}\text{C}$

Sine wave

D5SBx


Derating Curve



Sine wave
R-load
with heatsink

D5SBx

Derating Curve



Sine wave
R-load
Free in air

D5SBx

Peak Surge Forward Capability

