

S10VT60

600V 10A


FEATURES

- Dual In-Line Package
- Compact 3 phase bridge
- High IFSM
- Applicable to mount on glass-epoxy substrate (VTA type)

APPLICATION

- Big power supply
- Air conditioner
- Factory automation, Inverter

OUTLINE DIMENSIONS



RATINGS

● Absolute Maximum Ratings (If not specified Tc=25°C)


| Item                              | Symbol           | Conditions                                                                   | Ratings | Unit             |
|-----------------------------------|------------------|------------------------------------------------------------------------------|---------|------------------|
| Storage Temperature               | Tstg             |                                                                              | -40~150 | °C               |
| Operating Junction Temperature    | Tj               |                                                                              | 150     | °C               |
| Maximum Reverse Voltage           | V <sub>RM</sub>  |                                                                              | 600     | V                |
| Average Rectified Forward Current | I <sub>O</sub>   | 50Hz sine wave, R-load, With heatsink, Tc=137°C                              | 10      | A                |
| Peak Surge Forward Current        | I <sub>FSM</sub> | 50Hz sine wave, Non-repetitive 1cycle peak value, Rating of per arm, Tj=25°C | 170     | A                |
| Current Squared Time              | I <sup>2</sup> t | 1ms ≤ t < 10ms Tj=25°C                                                       | 110     | A <sup>2</sup> s |
| Dielectric Strength               | Vdis             | Terminals to case, AC 1 minute                                               | 2       | kV               |
| Mounting Torque                   | TOR              | ( Recommended torque : 0.6N·m)                                               | 0.8     | N·m              |

● Electrical Characteristics (If not specified Tc=25°C)

| Item               | Symbol          | Conditions                                                             | Ratings  | Unit |
|--------------------|-----------------|------------------------------------------------------------------------|----------|------|
| Forward Voltage    | V <sub>F</sub>  | IF=3.5A, Pulse measurement, Rating of per arm                          | Max.1.05 | V    |
| Reverse Current    | I <sub>R</sub>  | V <sub>R</sub> =V <sub>RM</sub> , Pulse measurement, Rating of per arm | Max.10   | μA   |
| Thermal Resistance | θ <sub>jc</sub> | junction to case                                                       | Max.0.65 | °C/W |


S10VTx

Forward Voltage



S10VTx

Forward Power Dissipation




$T_j = 150^{\circ}\text{C}$

Sine wave


# S10VTx

## Peak Surge Forward Capability



S10VTx

Derating Curve



$V_R = V_{RM}$   
Sine wave  
R-load  
with heatsink