






Telecommunication COMMON MODE CHOKE Transformers

DT35-8602AT
DT35-8603AT
DT35-8604AT
DT35-8605AT



DIMENSIONS IN mm

A	B	C	D	E	F	G
7.5 MAX.	6 Typ.	4.0 MAX.				

ELECTRICAL CHARACTERISTICS

	DT35-8602AT	DT35-8603AT	DT35-8604AT	DT35-8605AT
T.R	(PRI:SEC): 1:1±1% @100KHz 0.1V	(PRI:SEC): 1:1±1% @100KHz 0.1V	(PRI:SEC): 1:1±1% @100KHz 0.1V	(PRI:SEC): 1:1±1% @100KHz 0.1V
L	3mH Min. @100KHz 0.1V	20uH±5% @100KHz 0.1V 100mA	42uH±5% @100KHz 0.1V 100mA	33.8uH±5% @100KHz 0.1V 100mA
D.C.R	PRI: 0.8ΩMax. SEC: 0.8ΩMax.	PRI: 0.4ΩMax. SEC: 0.4ΩMax.	PRI: 0.4ΩMax. SEC: 0.4ΩMax.	PRI: 0.4ΩMax. SEC: 0.4ΩMax.
C.M ATTENUATION	42dB Typ. @900KHz 46dB Typ. @2.5MHz 38dB Typ. @8MHz	-----	-----	-----
HI-POT	500 VAC 60 SEC	500 VAC 60 SEC	500 VAC 60 SEC	500 VAC 60 SEC
SCHEMATIC	1	1	1	1

DELTA ELECTRONICS, INC.

(TAOYUAN PLANT CPBG) 31-1, SHIEN PAN ROAD, KUEI SAN INDUSTRIAL ZONE, TAOYUAN SHIEN, TAIWAN, R.O.C.

TEL: 886-3-3626301 FAX: 886-3-3618901

http://www.deltaww.com