


ELECTRICAL SPECIFICATIONS

FREQUENCY RANGE (GHz): 0.800-2.200
 IMPEDANCE (NOMINAL): 50 OHMS
 VSWR: INPUT: 1.15:1 TYP/1.25:1 MAX
 OUTPUT: 1.10:1 TYP/1.20:1 MAX
 INSERTION LOSS (dB): 0.3 TYP/0.4 MAX
 AMPLITUDE BALANCE (MAX): 0.1 dB
 PHASE BALANCE (MAX): 2 DEGREES
 ISOLATION (dB): 27 TYP/22 MIN
 RF POWER (TOTAL MAX): 20 WATTS INPUT WITH LOAD
 VSWR 1.2:1 OR BETTER
 DC VOLTAGE (MAX): 5 V

MECHANICAL SPECIFICATIONS

CONNECTORS: N-FEMALE, BRASS, NICKEL PLATE
 CONNECTOR PINS: BERYLLIUM COPPER, GOLD PLATE
 HOUSING: ALUMINUM, YELLOW IRIDITE
 INSULATORS: TEFLON®, VIRGIN ELECTRICAL GRADE
 TEMPERATURE: -55°C TO +85°C



LTR	DESCRIPTION	DATE	APP	MATERIAL: SEE ABOVE		UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES		 ELECTRONICS, INC. DENVILLE, NEW JERSEY e-meca.com	
				FINISH: SEE ABOVE		TOLERANCES 2 PLACES: ± .02 3 PLACES: ± .010 ANGLES: ± ----			
				DRAWN: RWA	DATE: 06/11/02	TIR:		TITLE 2-WAY, IN PHASE (0 DEGREE), POWER DIVIDER/COMBINER, N-FEMALE, WITH DC BLOCK	
				APPROVED: MJD	DATE: 06/11/02	SCALE: NTS	SIZE A		
				SHEET:		CODE IDENT. NO. 22424		DRAWING NO. DC802-4-1.500V	