

D1NL20U

200V 1A


FEATURES

- Low noise
- trr35ns
- 5 mm pitch mounting applicable

APPLICATION

- Switching power supply
- Free Wheel
- Home Appliances, Office Equipment
- Telecommunication, Factory Automation

OUTLINE DIMENSIONS



RATINGS

● Absolute Maximum Ratings (If not specified TI=25°C)


Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	T _{stg}		-55~150	°C
Operating Junction Temperature	T _j		150	°C
Maximum Reverse Voltage	V _{RM}		200	V
Average Rectified Forward Current	I _O	50Hz sine wave, R-load, Ta=25°C	1	A
Peak Surge Forward Current	I _{FSM}	50Hz sine wave, Non-repetitive 1 cycle peak value, Tj=25°C	25	A

● Electrical Characteristics (If not specified TI=25°C)


Item	Symbol	Conditions	Ratings	Unit
Forward Voltage	V _F	I _F =1A, Pulse measurement	Max.0.98	V
Reverse Current	I _R	V _R =V _{RM} , Pulse measurement	Max.10	μA
Reverse Recovery Time	trr	I _F =0.5A, I _R =1A	Max.35	ns
Thermal Resistance	θ _{jl}	junction to lead	Max.10	°C/W
	θ _{ja}	junction to ambient, On P.C.B. Lead length=5mm	Max.113	

D1NL20U


Forward Voltage



D1NL20U Forward Power Dissipation




$T_j = 150^\circ\text{C}$




D1NL20U

Derating Curve




$V_R = 200\text{V}$



D1NL20U

Peak Surge Forward Capability



D1NL20U Junction Capacitance

