



DB3826-WP

Dual 4 MHz Window Filter

456-460 MHz
466-470 MHz

- 456-460, 466-470 MHz
- Pass Band - Dual 4 MHz
- High Selectivity
- Attenuation > 35 dB (Min.)
- 19" Rack Mountable
- N Female Terminations
- RX Filter

Filter



Electrical		Mechanical	
VSWR:	1.5:1	Temperature Range:	-22°F to +140°F -30°C to +60°C
Frequency Range:	456-460 MHz, 466-470 MHz	Weight:	34 lbs (15.4 kg)
Pass Band:	Dual 4 MHz or 2 MHz	Dimensions:	3.5" x 19" x 31.5"
Insertion Loss:	2 dB @ 2 MHz passband 3.2 dB @ 4 MHz passband	Connectors:	N-Female
Attenuation:	> 35 dB (See curve $\pm$ 1 MHz from each @ band edge)	(Input/Output)	
Input Power Rating:	300 Watts (Maximum)	Finish:	DB Tek Black
Features:	> 30 dB Isolation at UHF Transmit Frequencies	Mounting:	19" Rack Mount
Mounting Options		Shipping Information	
Standard:	Panel mount for ARS & 19" rack mounting	Packing Size:	6" x 20" x 36"
		Shipping Weight:	42 lbs (19 kg)

8635 Stemmons Freeway • Dallas, Texas U.S.A. 75247-3701

Dallas/Ft.Worth Area Tel: 214.631.0310 • Fax: 214.631.4706

Toll Free Tel: 1.800.676.5342 • Fax: 1.800.229.4706

www.decibelproducts.com

customerservice@decibelproducts.com



DB3826-WP

Dual 4 MHz Window Filter

456-460 MHz
466-470 MHz

- 456-460, 466-470 MHz
- Pass Band - Dual 4 MHz
- High Selectivity
- Attenuation > 35 dB (Min.)
- 19" Rack Mountable
- N Female Terminations
- RX Filter

Filter

