

## NPN PRE-BIASED SMALL SIGNAL SOT-363 DUAL SURFACE MOUNT TRANSISTOR


### Features

- Epitaxial Planar Die Construction
- Complementary PNP Types Available (DDA)
- Built-In Biasing Resistors
- Lead-Free Device


### Mechanical Data

- Case: SOT-363, Molded Plastic
- Moisture sensitivity: Level 1 per J-STD-020A
- Case material - UL Flammability Rating 94V-0
- Terminals: Finish - Matte Tin Solderable per MIL-STD-202, Method 208
- Terminal Connections: See Diagram
- Marking: Date Code and Marking Code (See Diagrams & Page 2)
- Weight: 0.006 grams (approx.)
- Ordering Information (See Page 2)

| P/N      | R1 (NOM) | R2 (NOM) | MARKING |
|----------|----------|----------|---------|
| DDC122LU | 0.22K    | 10K      | N81     |
| DDC142JU | 0.47K    | 10K      | N82     |
| DDC122TU | 0.22K    | OPEN     | N83     |
| DDC142TU | 0.47K    | OPEN     | N84     |



| SOT-363              |              |      |
|----------------------|--------------|------|
| Dim                  | Min          | Max  |
| A                    | 0.10         | 0.30 |
| B                    | 1.15         | 1.35 |
| C                    | 2.00         | 2.20 |
| D                    | 0.65 Nominal |      |
| F                    | 0.30         | 0.40 |
| H                    | 1.80         | 2.20 |
| J                    | —            | 0.10 |
| K                    | 0.90         | 1.00 |
| L                    | 0.25         | 0.40 |
| M                    | 0.10         | 0.25 |
| α                    | 0°           | 8°   |
| All Dimensions in mm |              |      |



SCHEMATIC DIAGRAM

### Maximum Ratings @ T<sub>A</sub> = 25°C unless otherwise specified

| Characteristic                                       | Symbol                            | Value       | Unit |
|------------------------------------------------------|-----------------------------------|-------------|------|
| Supply Voltage                                       | V <sub>CC</sub>                   | 50          | V    |
| Input Voltage                                        | V <sub>IN</sub>                   | -5 to +6    | V    |
| Input Voltage                                        | V <sub>EBO</sub> (MAX)            | 5           | V    |
| Output Current                                       | I <sub>C</sub>                    | 100         | mA   |
| Power Dissipation (Note 3)                           | P <sub>d</sub>                    | 200         | mW   |
| Thermal Resistance, Junction to Ambient Air (Note 3) | R <sub>θJA</sub>                  | 625         | °C/W |
| Operating and Storage and Temperature Range          | T <sub>j</sub> , T <sub>STG</sub> | -55 to +150 | °C   |

- Note:
1. If lead-bearing terminal plating is required, please contact your Diodes Inc. sales representative for availability and minimum order details.
  2. Mounted on FR4 PC Board with recommended pad layout at <http://www.diodes.com/datasheets/ap02001.pdf>.
  3. 150mW per element must not be exceeded.

**Electrical Characteristics** @  $T_A = 25^\circ\text{C}$  unless otherwise specified **R1, R2 Types**

| Characteristic          |                      | Symbol       | Min        | Typ | Max        | Unit    | Test Condition                                       |
|-------------------------|----------------------|--------------|------------|-----|------------|---------|------------------------------------------------------|
| Input Voltage           | DDC122LU<br>DDC142JU | $V_{I(off)}$ | 0.3<br>0.3 | —   | —          | V       | $V_{CC} = 5V, I_O = 100\mu A$                        |
|                         | DDC122LU<br>DDC142JU | $V_{I(on)}$  | —          | —   | 2.0<br>2.0 | V       | $V_O = 0.3V, I_O = 20mA$<br>$V_O = 0.3V, I_O = 20mA$ |
| Output Voltage          |                      | $V_{O(on)}$  | —          | —   | 0.3V       | V       | $I_O/I_I = 5mA/0.25mA$                               |
| Input Current           | DDC122LU<br>DDC142JU | $I_I$        | —          | —   | 28<br>13   | mA      | $V_I = 5V$                                           |
| Output Current          |                      | $I_{O(off)}$ | —          | —   | 0.5        | $\mu A$ | $V_{CC} = 50V, V_I = 0V$                             |
| DC Current Gain         | DDC122LU<br>DDC142JU | $G_I$        | 56<br>56   | —   | —          | —       | $V_O = 5V, I_O = 10mA$                               |
| Gain-Bandwidth Product* |                      | $f_T$        | —          | 200 | —          | MHz     | $V_{CE} = 10V, I_E = 5mA,$<br>$f = 100MHz$           |

\* Transistor - For Reference Only

**Electrical Characteristics** @  $T_A = 25^\circ\text{C}$  unless otherwise specified **R1-Only**


| Characteristic                       |                      | Symbol        | Min        | Typ        | Max        | Unit    | Test Condition                              |
|--------------------------------------|----------------------|---------------|------------|------------|------------|---------|---------------------------------------------|
| Collector-Base Breakdown Voltage     |                      | $BV_{CBO}$    | 50         | —          | —          | V       | $I_C = 50\mu A$                             |
| Collector-Emitter Breakdown Voltage  |                      | $BV_{CEO}$    | 40         | —          | —          | V       | $I_C = 1mA$                                 |
| Emitter-Base Breakdown Voltage       | DDC122TU<br>DDC142TU | $BV_{EBO}$    | 5          | —          | —          | V       | $I_E = 50\mu A$<br>$I_E = 50\mu A$          |
| Collector Cutoff Current             |                      | $I_{CBO}$     | —          | —          | 0.5        | $\mu A$ | $V_{CB} = 50V$                              |
| Emitter Cutoff Current               | DDC122TU<br>DDC142TU | $I_{EBO}$     | —<br>—     | —          | 0.5<br>0.5 | $\mu A$ | $V_{EB} = 4V$                               |
| Collector-Emitter Saturation Voltage |                      | $V_{CE(sat)}$ | —          | —          | 0.3        | V       | $I_C = 5mA, I_B = 0.25mA$                   |
| DC Current Transfer Ratio            | DDC122TU<br>DDC142TU | $h_{FE}$      | 100<br>100 | 250<br>250 | 600<br>600 | —       | $I_C = 1mA, V_{CE} = 5V$                    |
| Gain-Bandwidth Product*              |                      | $f_T$         | —          | 200        | —          | MHz     | $V_{CE} = 10V, I_E = -5mA,$<br>$f = 100MHz$ |

\* Transistor - For Reference Only

**Ordering Information** (Note 4)

| Device     | Packaging | Shipping         |
|------------|-----------|------------------|
| DDC122LU-7 | SOT-363   | 3000/Tape & Reel |
| DDC142JU-7 | SOT-363   | 3000/Tape & Reel |
| DDC122TU-7 | SOT-363   | 3000/Tape & Reel |
| DDC142TU-7 | SOT-363   | 3000/Tape & Reel |

Notes: 1. If lead-bearing terminal plating is required, please contact your Diodes Inc. sales representative for availability and minimum order details.  
 4. For Packaging Details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

**Marking Information**


NXX = Product Type Marking Code  
 See Sheet 1 Diagrams  
 YM = Date Code Marking  
 Y = Year ex: N = 2002  
 M = Month ex: 9 = September

Date Code Key

| Year | 2002 | 2003 | 2004 | 2005 | 2006 | 2007 | 2008 | 2009 |
|------|------|------|------|------|------|------|------|------|
| Code | N    | P    | R    | S    | T    | U    | V    | W    |

| Month | Jan | Feb | March | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-------|-----|-----|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Code  | 1   | 2   | 3     | 4   | 5   | 6   | 7   | 8   | 9   | O   | N   | D   |




Fig. 1 Power Derating Curve

(150mW per element must not be exceeded).