


Power Schottky Rectifier with common cathode


Preliminary Data

$$\begin{aligned} I_{FAV} &= 2 \times 8 \text{ A} \\ V_{RRM} &= 100 \text{ V} \\ V_F &= 0.62 \text{ V} \end{aligned}$$

V_{RSM} V	V_{RRM} V	Type
100	100	DSSK 16-01C



TO-220 AB



A = Anode, C = Cathode, TAB = Cathode

Symbol	Test Conditions	Maximum Ratings	
I_{FRMS}		35	A
I_{FAV}	$T_C = 165^\circ\text{C}$; rectangular, $d = 0.5$	8	A
I_{FAV}	$T_C = 165^\circ\text{C}$; rectangular, $d = 0.5$; per device	16	A
I_{FSM}	$T_{VJ} = 45^\circ\text{C}$; $t_p = 10 \text{ ms}$ (50 Hz), sine	120	A
E_{AS}	$I_{AS} = 8 \text{ A}$; $L = 180 \mu\text{H}$; $T_{VJ} = 25^\circ\text{C}$; non repetitive	tbd	mJ
I_{AR}	$V_A = 1.5 \cdot V_{RRM}$ typ.; $f = 10 \text{ kHz}$; repetitive	tbd	A
$(dv/dt)_{cr}$		5000	V/ μs
T_{VJ}		-55...+175	$^\circ\text{C}$
T_{VJM}		175	$^\circ\text{C}$
T_{stg}		-55...+150	$^\circ\text{C}$
P_{tot}	$T_C = 25^\circ\text{C}$	90	W
M_d	mounting torque	0.4...0.6	Nm
Weight	typical	2	g

Features

- International standard package
- Very low V_F
- Extremely low switching losses
- Low I_{RM} -values
- Epoxy meets UL 94V-0

Applications

- Rectifiers in switch mode power supplies (SMPS)
- Free wheeling diode in low voltage converters

Advantages

- High reliability circuit operation
- Low voltage peaks for reduced protection circuits
- Low noise switching
- Low losses

Symbol	Test Conditions	Characteristic Values	
		typ.	max.
I_R ①	$T_{VJ} = 25^\circ\text{C}$; $V_R = V_{RRM}$ $T_{VJ} = 125^\circ\text{C}$; $V_R = V_{RRM}$		0.3 mA 20 mA
V_F	$I_F = 8 \text{ A}$; $T_{VJ} = 125^\circ\text{C}$ $I_F = 8 \text{ A}$; $T_{VJ} = 25^\circ\text{C}$ $I_F = 16 \text{ A}$; $T_{VJ} = 125^\circ\text{C}$		0.62 V 0.79 V 0.73 V
R_{thJC} R_{thCH}	0.5		1.7 K/W K/W

Pulse test: ① Pulse Width = 5 ms, Duty Cycle < 2.0 %
Data according to IEC 60747 and per diode unless otherwise specified

Dimensions see IXYS Databook 2001