


ECX-TXO-10C2 SERIES

SMD TEMPERATURE COMPENSATED OSCILLATOR



The ECS-TXO-10C2 is a TCXO (Temperature Compensated Crystal Oscillator) featuring very tight stability over a wide temperature range. An internal trimmer is a standard feature to tune the TCXO to its nominal frequency. The standard DIP 14 pin pitch TCXO is ideal for wireless communication applications.

OPTIONS:

- 3V operation
- 2 TTL / CMOS I5 pF load
- voltage control function

FEATURES

- Highly stable output over wide temperature range
- 4.7mm H max. low profile TCXO
- Industry standard DIP 14 pin lead spacing

PART NUMBERING GUIDE "EXAMPLE"

PART NUMBER*	WAVEFORM	CONTROL OPTION
ECX-TXO-10C2	CLIPPED SINE WAVE	NO VOLTAGE CONTROL
ECX-TXO-10D2	2 TTL/15pF CMOS	NO VOLTAGE CONTROL
ECX-VTXO-10C2	CLIPPED SINE WAVE	VOLTAGE CONTROL
ECX-VTXO-10D2	2 TTL/15pF CMOS	VOLTAGE CONTROL

* Complete part number to include frequency. i.e. ECX-TXO-10C2-100 (100 = 10 MHz)


STANDARD FREQUENCIES

11.300, 12.800, 15.360, 19.200
and 21.250 MHz

OPERATING CONDITIONS/ELECTRICAL CHARACTERISTICS

PARAMETERS	CONDITIONS	SPECIFICATIONS				UNITS
TYPE		ECX-TXO-10C2	ECX-TXO-10D2	ECX-VTXO-10C2	ECX-VTXO-10D2	
FREQUENCY RANGE	f_0	9.600 ~ 26.000		9.600 ~ 26.000		MHz
FREQUENCY TOLERANCE	@ 25°C	±0.5		±0.5		PPM
FREQUENCY STABILITY	-30°C ~ +75°C	±2.5		±2.5		PPM
SUPPLY VOLTAGE		+5±5%		+5±5%		V
SUPPLY CURRENT		2.0 Max.		2.0 Max.		mA
OUTPUT LEVEL		1Vp-p Min. (Clipped Sine)	HCMOS/TTL	1Vp-p Min. (Clipped Sine)	HCMOS/TTL	
OUTPUT LOAD		10K ohm 15pF	2 TTL 15pF CMOS	10K ohm 15pF	2 TTL 15pF CMOS	
AGING	per year @25°C	±1.0		±1.0		PPM
FREQUENCY ADJUSTMENT	Internal Trimmer	±3.0 Min.		±3.0 Min.		PPM
VOLTAGE CONTROL RANGE	@ 2.5 ±2.0V	N/A		±8.0 Min.		PPM
STORAGE TEMPERATURE	-40 +85°C					°C

PACKAGE DIMENSIONS (mm)



ECX-TXO-10C2 SERIES – Top, Side and Bottom views

PIN CONNECTIONS	
#1	N.C. or Vcont
#7	GND/CASE
#8	OUTPUT
#14	+Vcc