

ESA2UN3282B-60JS-S

8MByte (2M x 32) CMOS EDO DRAM Module

General Description

The ESA2UN3282B-60JS-S is a high performance, EDO (Extended Data Out) 8-megabyte dynamic RAM module organized as 2M words by 32bits, in a 72-pin, leadless, single-in-line memory module (SIMM) package. ESA2UN3282B supports 2K refresh.

The module utilizes eight, Fujitsu MB8117805B-60PJ CMOS 2Mx8 EDO dynamic RAM in a surface mount package on an epoxy laminate substrate. Each device is accompanied by a decoupling capacitor for improved noise immunity.

Control lines provided are such that byte control is possible.

Features

- High Density: 8MByte
- Fast Access Time of 60 ns (max.)
- Low Power: Active (60ns)
2.4 W (max.)
44mW (max.) - Standby (TTL)
22mW (max.) - Standby (CMOS)
- TTL-compatible inputs and outputs
- Separate power and ground planes
- Single power supply of 5V±10%
- Height: 0.900 inch

ABSOLUTE MAXIMUM RATINGS


Item	Symbol	Ratings	Unit
Voltage on any pin relative to V _{SS}	V _T	-1 to +7.0	V
Power Dissipation	P _T	4	W
Operating Temperature	T _{opr}	0 to +70	°C
Storage Temperature	T _{stg}	-55 to +125	°C
Short Circuit Output Current	I _{OS}	-50 to +50	mA

RECOMMENDED DC OPERATING CONDITIONS

(T_A = 0 to +70 °C)

Symbol	Parameter	Min	Typ	Max	Unit
V _{CC}	Supply Voltage	4.5	5.0	5.5	V
V _{SS}	Ground	0	0	0	V
V _{IH}	Input High voltage	2.4	-	V _{CC} +1	V
V _{IL}	Input Low voltage	-1	-	0.8	V

Functional Diagram



- Notes:
1. A0 ~ A10 to all devices.
 2. WE* to all devices.
 3. OE* of all devices are grounded.

ESA2UN3282B-60JS-S

Pin Name

A0-A10	Row Addresses	WE*	Write Enable
A0~A9	Column Addresses	PD1~PD4	Presence Detects
DQ0~DQ31	Data Inputs/Outputs	V _{CC}	Power Supply
CAS0*~CAS3*	Column Address Strokes	V _{SS}	Ground
RAS0*, RAS2*	Row Address Strokes	NC	No Connection

Presence Detect Pins

Pin	-60
PD1	NC
PD2	NC
PD3	NC
PD4	NC

Pin No.	Pin Designation	Pin No.	Pin Designation	Pin No.	Pin Designation	Pin No.	Pin Designation
1	V _{SS}	19	A10	37	NC	55	DQ11
2	DQ0	20	DQ4	38	NC	56	DQ27
3	DQ16	21	DQ20	39	V _{SS}	57	DQ12
4	DQ1	22	DQ5	40	CAS0*	58	DQ28
5	DQ17	23	DQ21	41	CAS2*	59	V _{CC}
6	DQ2	24	DQ6	42	CAS3*	60	DQ29
7	DQ18	25	DQ22	43	CAS1*	61	DQ13
8	DQ3	26	DQ7	44	RAS0*	62	DQ30
9	DQ19	27	DQ23	45	NC	63	DQ14
10	V _{CC}	28	A7	46	NC	64	DQ31
11	NC	29	NC	47	WE*	65	DQ15
12	A0	30	V _{CC}	48	NC	66	NC
13	A1	31	A8	49	DQ8	67	PD1
14	A2	32	A9	50	DQ24	68	PD2
15	A3	33	NC	51	DQ9	69	PD3
16	A4	34	RAS2*	52	DQ25	70	PD4
17	A5	35	NC	53	DQ10	71	NC
18	A6	36	NC	54	DQ26	72	V _{SS}

DC CHARACTERISTICS

($V_{CC} = 5.0V \pm 10\%$, $V_{SS} = 0V$, $T_A = 0$ to $+70^\circ C$)

Parameter	Symbol	Test Condition	60		Unit	Note
			Min.	Max.		
Operating Current	I_{CC1}	RAS*, CAS* cycling; $t_{RC} = \min.$	-	440	mA	1, 2
Standby current	I_{CC2}	TTL Interface RAS*, CAS* = V_{IH} $D_{out} = \text{High-Z}$	-	8	mA	
		CMOS Interface RAS*, CAS* $\geq V_{CC} - 0.2V$ $D_{out} = \text{High-Z}$	-	4	mA	
RAS* -only Refresh Current	I_{CC3}	CAS* = V_{IH} ; RAS*, Address cycling @ $t_{RC} = \min$	-	440	mA	2
CAS*-before-RAS* Refresh Current	I_{CC4}	RAS*, CAS* cycling @ $t_{RC} = \min.$	-	440	mA	
Hyper Page Mode Current	I_{CC5}	RAS* = V_{IL} ; CAS*, Address cycling @ $t_{HPC} = \min$	-	360	mA	1, 3
Input Leakage Current	I_{LI}	$0V \leq V_{in} \leq V_{CC} + 0.5V$	-40	40	μA	
Output Leakage Current	I_{LO}	$0V \leq V_{out} \leq V_{CC}$ $D_{out} = \text{Disable}$	-10	10	μA	
Output High Voltage	V_{OH}	High $I_{out} = -5$ mA	2.4	-	V	
Output Low Voltage	V_{OL}	Low $I_{out} = 4.5$ mA	-	0.4	V	

- Notes:
1. Values depend on load condition when the device is selected. Maximum Values are specified at the output open condition.
 2. Address can be changed once or less while RAS* = V_{IL} .
 3. Address can be changed once or less while CAS* = V_{IH} .

CAPACITANCE

($T_A = +25^\circ C$, $V_{CC} = 5.0V \pm 10\% = 10V$)

Parameter	Symbol	Max.	Unit	Note
Input Capacitance (Address)	C_{I1}	25	pF	1
Input Capacitance (RAS0*, RAS2*)	C_{I2}	17	pF	1
Input Capacitance (CAS0*~CAS3*)	C_{I3}	10	pF	1
Input Capacitance (WE*)	C_{I4}	30	pF	1
Input/Output Capacitance (DQ0~DQ31)	$C_{I/O}$	12	pF	1, 2

- Notes:
1. Capacitance is measured with Boonton Meter or effective capacitance method.
 2. CAS* = V_{IH} to disable D_{out} .

ESA2UN3282B-60JS-S

AC CHARACTERISTICS


(TA = 0 to +70°C, V_{CC} = 5.0V±10%V, V_{SS} = 0V)

Parameter	Symbol	60		Unit	Notes
		Min	Max		
Random read/write cycle time	t _{RC}	110	-	ns	
Access time from RAS*	t _{RAC}	-	60	ns	3, 4
Access time from CAS*	t _{CAC}	-	17	ns	3, 4, 5
Access time from column address	t _{AA}	-	30	ns	3, 10
Output buffer turn-off time	t _{OFF}	3	15	ns	6
Transition time (rise and fall)	t _T	2	50	ns	2
RAS* precharge time	t _{RP}	40	-	ns	
RAS* pulse width	t _{RAS}	60	10000	ns	
RAS* hold time	t _{RSH}	17	-	ns	
CAS* hold time	t _{CSH}	50	-	ns	
CAS* pulse width	t _{CAS}	10	10000	ns	
RAS* to CAS* delay time	t _{RCD}	20	45	ns	4
RAS* to column address delay time	t _{RAD}	15	30	ns	10
CAS* to RAS* precharge time	t _{CRP}	5	-	ns	
Row address set-up time	t _{ASR}	0	-	ns	
Row address hold time	t _{RAH}	10	-	ns	
Column address set-up time	t _{ASC}	0	-	ns	
Column address hold time	t _{CAH}	10	-	ns	
Column address to RAS* lead time	t _{RAL}	30	-	ns	
Read command set-up time	t _{RCS}	0	-	ns	
Read command hold time to CAS*	t _{RCH}	0	-	ns	8
Read command hold time to RAS*	t _{RRH}	0	-	ns	
Write command hold time	t _{WCH}	10	-	ns	
Write command pulse width	t _{WP}	10	-	ns	
Write command to RAS* lead time	t _{RWL}	15	-	ns	
Write command to CAS* lead time	t _{CWL}	10	-	ns	
Data-in set-up time	t _{DS}	0	-	ns	9
Data-in hold time	t _{DH}	10	-	ns	9
Refresh period	t _{REF}	-	32	ms	
Write command set-up time	t _{WCS}	0	-	ns	7
CAS* set-up time (CBR refresh)	t _{CSR}	10	-	ns	1
CAS* hold time (CBR refresh)	t _{CHR}	10	-	ns	1
RAS* precharge to CAS* hold time	t _{RPC}	5	-	ns	
Access time from CAS* precharge	t _{CPA}	-	35	ns	3, 11
Hyper Page mode cycle time	t _{HPC}	25	-	ns	
CAS* precharge time (Hyper Page)	t _{CP}	10	-	ns	
RAS* pulse width (Hyper Page)	t _{RASP}	60	100000	ns	12

- Notes:
1. An initial pulse of at least 200 μ s is required after power-up followed by a minimum of eight RAS* cycles before device operation is achieved.
 2. V_{IH} (min.) and V_{IL} (max.) are reference levels for measuring timing of input signals. Transition times are measured between V_{IH} (min.) and V_{IL} (max.) and are assumed to be 5 ns for all inputs.
 3. Measure with a load equivalent of 2 TTL loads and 100pF.
 4. Operation within the t_{RCD} (max.) limit ensures that t_{RAC} (max.) limit can be met; t_{RCD} (max.) is specified as a reference point only. If t_{RCD} is greater than the specified t_{RCD} (max) limit, then access time is controlled exclusively by t_{CAC} .
 5. Assumes that $t_{RCD} \geq t_{RCD}$ (max.).
 6. This parameter defines the time at which the output achieves open circuit condition and is not referenced to V_{OH} or V_{OL} .
 7. t_{WCS} is a non restrictive operating parameter. It is included in the data sheet as an electrical characteristic only. If $t_{WCS} \geq t_{WCS}$ (min.) the cycle is an early write cycle and the data-out pin will remain at high impedance for the duration of the cycle.
 8. Either t_{RCH} or t_{RRH} must be satisfied for a read cycle.
 9. These parameters are referenced to the CAS* leading edge in early write cycles.
 10. Operation within the t_{RAD} (max.) limit ensures that t_{RAC} (max.) can be met. t_{RAD} (max.) is specified as a reference point only. If t_{RAD} is greater than the specified t_{RAD} (max.) limit, then access time is controlled by t_{AA} .
 11. Access time is determined by the longer of t_{AA} , t_{CAC} , or t_{ACP} .
 12. t_{RASC} defines RAS* pulse width in fast page mode cycles.

Physical Dimensions

72-pin SIMM



(All dimensions are in inches with ± 0.005 " tolerance unless otherwise specified. Do not scale drawing)

ESA2UN3282B-60JS-S

Ordering Information

E S A 2 U N 32 82 B _ - 60 J S - _ S
(1) (2) (3) (4) (5) (6) (7) (8) (9) (10) (11) (12) (13) (14) (15)

(1) **Memory Type**

F : Fast Page Mode (FPM)
E : Extended Data Out (EDO)

(2) **Module Shape**

S : SIMM
D : DIMM
O : Small Outline DIMM

(3) **Module Pin Count**

A : 72-pin
B : 144-pin
C : 168-pin
D : 200-pin

(4) **Word Depth**

1 : 1M
2 : 2M
4 : 4M, etc.

(5) **Buffer Type**

B : Buffered
U : Unbuffered
R : Registered

(6) **Operating Voltage**

N : 5V
V : 3,3V

(7) **Data Width**

(ex. 8=x8, 32=x32, 72=x72 etc.)

(8) **Device Configuration / Refresh**

41 : 1Mx4, 1K Refresh Cycle
42 : 4Mx4, 2K Refresh Cycle
44 : 4Mx4, 4K Refresh Cycle
82 : 2Mx8, 2K Refresh Cycle
14 : 1Mx16, 4K Refresh Cycle
11 : 1Mx16, 1K Refresh Cycle

(9) **Module Revision *1**

Blank : Rev. 0
A : Rev. 1
B : Rev. 2 (etc.)

*1 When DRAM device or PCB is revised, the revision is changed

(10) **Power consumption**

Blank : Standard
L : Low Power

(11) **Speed**

50 : 50ns
60 : 60ns
70 : 70ns

(12) **Package of Component**

J : SOJ
T : TSOP

(13) **Module Lead Finish**

S : Solder Plate
G : Gold Plate

(14) **Private Brand Name *2**

Blank : Common Products
G : FMG Brand

*2 This column is applicable to custom modules, NOT applicable to JEDEC standard commodity products

(15) **Assembly & Test Site**

S : Smart Modular Technologies

FUJITSU LIMITED

For further information please contact:

Japan

FUJITSU LIMITED
Memory Marketing Dept.
4-1-1, Kamikodanaka Nakahara-ku,
Kawasaki 211-88, Japan
Tel: +81-44-754-3767
Fax: +81-44-754-3343
Internet: <http://www.fujitsu.co.jp/>

North and South America

FUJITSU MICROELECTRONICS, INC.
3545 North First Street
San Jose, CA 95134-1804, USA.
Tel: +1-408-922-9000
Fax: +1-408-922-9179

Customer Response Center (Mon-Fri: 7am-5pm (PST))
Tel: +1-800-866-8608
Fax: +1-408-922-9179

Internet: <http://www.fujitsumicro.com/>

Europe

FUJITSU MIKROELEKTRONIK GmbH
Am Siebenstein 6-10
63303 Dreieich-Buchsschlag
Germany
Tel: +49-6103-690-0
Fax: +49-6103-690-122

Internet: <http://www.fujitsu-edc.com/>

Asia

FUJITSU MICROELECTRONICS ASIA PTE LIMITED
#05-08, 151 Lorong Chuan
NewTechPark
Singapore 556741
Tel: +65-281-0770
Fax: +65-281-0220
Internet: <http://www.fsl.com.sg/>

All Rights Reserved.

Circuit diagrams utilizing Fujitsu products are included as a means of illustrating typical semiconductor applications. Complete information sufficient for construction purposes is not necessarily given.

The information given in this document have been carefully checked and is believed to be reliable. However, Fujitsu assumes no responsibility for inaccuracies.

The information contained in this document does not convey any licence under the copyrights, patent rights or trademarks claimed and owned by Fujitsu.

Fujitsu reserves the right to change products or specifications without notice.

No part of this publication may be copied or reproduced in any form or by any means, or transferred to any third party without prior written consent of Fujitsu.

The information contained in this document are not intended for use with equipments which require extremely high reliability such as aerospace equipments, undersea repeaters, nuclear control systems or medical equipments for life support.