



ETC705/706/707/708 μP Supervisory Circuits

Description

The ETC705/ETC706/ETC707/ETC708 are inexpensive microprocessor supervisory circuits that monitor power supplies in microprocessor based systems. The circuit functions include a watchdog timer, microprocessor reset, power failure warning and a debounced manual reset input.

The ETC705 and ETC706 offer a watchdog timer function while the ETC707 and ETC708 have an active high reset output in addition to the active low reset output.

Supply voltage monitor levels of 4.65V and 4.4V are available. The ETC705/ETC707 have a nominal reset threshold level of 4.65V while the ETC706 and ETC708 have a 4.4V nominal reset threshold level. When the supply voltage drops below the respective reset threshold level, RESET is asserted.


Typical Applications

- Automotive Systems
- Intelligent Instruments
- Critical Microprocessor Power Monitoring
- Printers
- Computers
- Controllers


Ordering Information

Part	Package	Temp. Range
ETC70_N	8-Lead PDIP	-40°C to +85°C
ETC70_M	8-Lead SOIC	-40°C to +85°C
ETC70_D	Tested Die	0°C to +70°C

Pin Configuration




N Package - 8 Lead Plastic DIP Package
M Package - 8 Lead Plastic SOIC Package



Features

- Debounced Manual Reset Input is TTL/CMOS Compatible
- Reset Pulse Width, 200ms
- Watchdog Timer, 1.6s (ETC705/ETC706)
- 4.4V or 4.65V Precision Voltage Monitor
- Early Power Fail Warning or Low Battery Detect

Typical Operating Circuit



ETC705/ETC706/ETC707/ETC708

µP Supervisory Circuits

Absolute Maximum Ratings

Terminal Voltage	
VCC	-0.3V to 6.0V
All Other Inputs	-0.3V to (VCC + 0.3V)
Input Current	
VCC, Gnd	25mA
Output Current (all outputs)	20mA

Operating Temperature Range	
ETC70_N, ETC70_M	-40°C to 85°C
Storage Temperature Range	-65°C to 150°C
Lead Temperature (Soldering - 10 sec.)	300°C
Power Dissipation (PDIP)	475mW
Power Dissipation (SOIC)	400mW

Stresses above those listed under ABSOLUTE MAXIMUM RATINGS may cause permanent device failure. Functionality at or above these limits is not implied. Exposure to absolute maximum ratings for extended periods may affect device reliability. Operating ranges define those limits between which the functionality of the device is guaranteed.

Electrical Characteristics

VCC = 4.75V to 5.5V for ETC705/ETC707, VCC = 4.5V to 5.5V for ETC706/ETC708, T_A = -40°C to 85°C unless otherwise noted.

Parameter	Conditions	Min	Typ	Max	Units
Operating Voltage Range, VCC	ETC70__	1.4		5.5	V
Supply Current	ETC70__			60	µA
Reset Voltage Threshold	ETC705, ETC707 ETC706, ETC708	4.50 4.25	4.65 4.4	4.75 4.5	V
Reset Threshold Hysteresis			40		mV
Reset Pulse Width, t _{RS}		140	200	280	ms
RESET Output Voltage	I _{Source} = 800µA I _{Sink} = 3.2mA ETC70__C, I _{Sink} = 50µA, VCC = 1.4V	VCC - 1.5V		0.4 0.3	V
RESET Output Voltage	I _{Source} = 800µA I _{Sink} = 1.2mA	VCC - 1.5V		0.4	V
Watchdog Timeout Period, t _{WD}		1.0	1.6	2.25	sec
WDI Minimum Input Pulse, t _{WP}	V _{IL} = 0.4V, V _{IH} = 80% of VCC	50			ns
WDI Threshold Voltage	V _{IH} , VCC = 5V V _{IL} , VCC = 5V	3.5		0.8	V
WDI Input Current	WDI = 0V WDI = VCC	-150	-50 50	150	µA
WDO Output Voltage	I _{Source} = 800µA I _{Sink} = 1.2mA	VCC - 1.5V		0.4	V

ETC705/ETC706/ETC707/ETC708 μP Supervisory Circuits

Electrical Characteristics

$V_{CC} = 4.75V$ to $5.5V$ for ETC705/ETC707, $V_{CC} = 4.5V$ to $5.5V$ for ETC706/ETC708, $T_A = -40^{\circ}C$ to $85^{\circ}C$ unless otherwise noted.

Parameter	Conditions	Min	Typ	Max	Units
\overline{MR} Pull-Up Current	$\overline{MR} = 0V$	100	250	600	μA
\overline{MR} Pulse Width, t_{MR}		150			nS
\overline{MR} Input Threshold	V_{IL} V_{IH}	2.0		0.8	V
\overline{MR} to Reset Output Delay, t_{MD}				250	nS
PFI Input Threshold	$V_{CC} = 5V$	1.2	1.25	1.3	V
PFI Input Current		-25	0.01	+25	nA
\overline{PFO} Output Voltage	$I_{Sink} = 3.2mA$ $V_{CC} = 5V, I_{Source} = 800\mu A$	$V_{CC} - 1.5V$		0.4	V

ETC705/ETC706/ETC707/ETC708

µP Supervisory Circuits

Pin Functions

Pin Name	Pin No.		
	ETC705 ETC706	ETC707 ETC708	
$\overline{\text{MR}}$	1	1	Manual Reset Input forces $\overline{\text{RESET}}$ to assert when pulled below 0.8V. An internal pull-up current of 250µA on this input forces it high when left floating. This input can also be driven from TTL or CMOS logic.
VCC	2	2	Primary supply input, +5V.
GND	3	3	IC ground pin, 0V reference.
PFI	4	4	Power fail input. Internally connected to the power fail comparator which is referenced to 1.25V. The power fail output (PFO) remains high if PFI is above 1.25V. PFI should be connected to GND or V _{OUT} if the power fail comparator is not used.
$\overline{\text{PFO}}$	5	5	Power fail output. The power fail comparator is independent of all other functions on this device.
WDI	6	N/A	Watchdog input. The WDI input monitors microprocessor activity, an internal watchdog timer resets itself with each transition on the watchdog input. If the WDI pin is held high or low for longer than the watchdog timeout period, $\overline{\text{WDO}}$ is forced to active low. The watchdog function can be disabled by floating the WDI pin.
N/C	N/A	6	No Connect
$\overline{\text{RESET}}$	7	7	$\overline{\text{RESET}}$ is asserted if either V _{CC} goes below the reset threshold or by a low signal on the manual reset input ($\overline{\text{MR}}$). $\overline{\text{RESET}}$ remains asserted for one reset timeout period (200ms) after V _{CC} exceeds the reset threshold or after the manual reset pin transitions from low to high. The watchdog timer will not assert $\overline{\text{RESET}}$ unless $\overline{\text{WDO}}$ is connected to $\overline{\text{MR}}$.
$\overline{\text{WDO}}$	8	N/A	Output for the watchdog timer. The watchdog timer resets itself with each transition on the watchdog input. If the WDI pin is held high or low for longer than the watchdog timeout period, $\overline{\text{WDO}}$ is forced low. $\overline{\text{WDO}}$ will also be forced low if V _{CC} is below the reset threshold and will remain low until V _{CC} returns to a valid level.
RESET	N/A	8	RESET is the compliment of $\overline{\text{RESET}}$ and is asserted if either V _{CC} goes below the reset threshold or by a low signal on the manual reset input ($\overline{\text{MR}}$). RESET is suitable for microprocessors systems that use an active high reset.

ETC705/ETC706/ETC707/ETC708 μP Supervisory Circuits

Block Diagram




Figure 1. ETC705/ETC706 Block Diagram




Figure 2. ETC707/ETC708 Block Diagram

ETC705/ETC706/ETC707/ETC708 μP Supervisory Circuits

Circuit Description

Power Fail Warning

An additional comparator which is independent of other functions on the ETC705/706/707/708 is provided for early warning of power failure. An external voltage




Figure 3. Power Fail Comparator

divider can be used to compare unregulated DC to an internal 1.25V reference. The voltage divider ratio on the input of the power fail comparator (PFI) can be chosen so as to trip the power fail comparator a few milliseconds before VCC falls below the maximum reset threshold voltage. The output of the power fail comparator (PFO) can be used to interrupt the microprocessor when used in this mode and execute shut-down procedures prior to power loss.

Watchdog Timer

The microprocessor can be monitored by connecting the WDI pin (watchdog input) to a bus line or I/O line. If a transition doesn't occur on the WDI pin within the watchdog timeout period, then \overline{WDO} will go low. A minimum pulse of 50ns or any transition low-to-high or high-to-low on the WDI pin will reset the watchdog timer.

The output of the watchdog timer (\overline{WDO}) will remain high if WDI sees a valid transition within the watchdog timeout period or if WDI is left floating. If VCC falls below the reset threshold voltage then \overline{WDO} goes low immediately regardless of WDI. Thus, if WDI is left floating, then \overline{WDO} can be used as a low line indicator.

Microprocessor Reset

The \overline{RESET} pin is asserted whenever VCC falls below the reset threshold voltage or when \overline{MR} goes low. The reset pin remains asserted for a period of 200ms after VCC has risen above the reset threshold voltage and \overline{MR} goes high. The reset function ensures the




Figure 4. Reset Timing Diagram

microprocessor is properly reset and powers up into a known condition after a power failure. \overline{RESET} will remain valid with VCC as low as 1.4V.

ETC705/ETC706/ETC707/ETC708 μP Supervisory Circuits


Alternate Source Cross Reference Guide

<u>Industry P/N</u>	<u>ETC Direct Replacement</u>
MAX705CPA	ETC705N
MAX705CSA	ETC705M
MAX705EPA	ETC705N
MAX705ESA	ETC705M
ADM705AN	ETC705N
DS1705	ETC705
MAX706CPA	ETC706N
MAX706CSA	ETC706M
MAX706EPA	ETC706N
MAX706C/D	ETC706D
ADM706AN	ETC706N
DS1706	ETC706
MAX707CPA	ETC707N
MAX707CSA	ETC707M
MAX707EPA	ETC707N
MAX707ESA	ETC707M
MAX707C/D	ETC707D
ADM707AN	ETC707N
DS1707	ETC707
MAX708CPA	ETC708N
MAX708CSA	ETC708M
MAX708EPA	ETC708N
MAX708ESA	ETC708M
MAX708C/D	ETC708D
ADM708AN	ETC708N
DS1708	ETC708


ETC705/ETC706/ETC707/ETC708 μP Supervisory Circuits

Packaging Information

M Package, 8-Pin Small Outline



N Package, 8-Pin Plastic Dual-In-Line



Electronic Technology

402 Campus Drive ♦ Huxley, IA 50124 ♦ Phone: (515) 597-7000 ♦ <http://www.etcchcorp.com>

V011499 © 1999 This publication is to provide information only, and, unless specified to the contrary by the Company in writing, is not to form part of any order or contract. This information has been carefully checked and is believed to be entirely reliable. However, no responsibility is assumed for inaccuracies. Electronic Technology reserves the right to change the circuitry and specifications without notice at any time. No representation, implied or expressed, is made regarding the suitability of the products or services contained herein for intended use. All rights reserved. Written permission of Electronic Technology is required prior to reproduction or transmission by any method, mechanical, electronic, or otherwise. This information does not convey to the purchaser of the products or services any license under the patent rights of Electronic Technology or others. Electronic Technology does not authorize its components for use in life support or aircraft applications where malfunction or failure of such products may reasonably be expected to result in personal injury or death.